J03159

INSTRUCTIONS

2004-06-28



SOFTAIL REAR AXLE-NUT COVER KIT (FLUTED)

GENERAL

Kit Number

44575-04

Models

This kit fits all 2000 and later Softail model motorcycles, except FLSTS and models with accessory leather saddlebags or saddlebag support bracket part number 90238-00.

Kit Contents

See Figure 1 and Table 1.

INSTALLATION

NOTE

Inside each axle-nut cover is a LH or RH inscription for the left-hand and right-hand side of the vehicle to which the covers fasten.

The **shorter** axle-nut cover mounts on the right-hand side of the vehicle, and the **longer** cover on the left.

On a bike that has been previously serviced, check to ensure that the axle has not been removed and re-installed from the left side (with the castle nut on the right side of the wheel).

If it has, the axle **MUST** be re-installed from the right side of the motorcycle. See REAR WHEEL: REMOVAL and INSTALLATION in the Service Manual for procedure. A Service Manual for your model motorcycle is available from any Harley-Davidson dealer.

- 1. See Figure 1. Partially fasten a set screw (3) into the threaded hole in each axle-nut cover (1, 2).
- Position each axle-nut cover over the appropriate axle nut. The notch in each cover fits over the axle-adjusting screw.
- 3. Adjust the position of the exhaust system as necessary to provide axle-nut clearance.
- Tighten the axle-nut-cover set screws (3) to 7–9 N⋅m (70 in-lbs).

NOTE

The set screws in this kit are treated with a thread-locking compound. When replacing or re-installing the set screws, apply Loctite 243 (Blue) Threadlocker (Harley-Davidson Part Number 99642-97) to the set-screw threads.

SERVICE PARTS




Figure 1. Service Parts: Softail Rear Axle-Nut Cover Kit (Fluted)

Table 1. Service Parts: Softail Rear Axle-Nut Cover Kit (Fluted)

	ltem	Description (Quantity)	Part Number
Γ	1		Not Sold Separately
Γ			Not Sold Separately
Г		Set screw, with lock patch 1/4-20	3349
		x 0.25 inch long (2)	
Γ	4	Hex key, 1/8 inch	Not Sold Separately