



# INSTRUCTIONS

J03672

2005-07-08



## CHROME REAR BRAKE ROTOR HARDWARE KIT

### GENERAL

#### Kit Number

46647-05

#### Models

This kit fits all 1992 and later Harley-Davidson motorcycles.

#### Additional Parts Required

##### ⚠ WARNING

Rider and passenger safety depend upon the correct installation of this kit. Use the appropriate service manual procedures. If the procedure is not within your capabilities or you do not have the correct tools, have a Harley-Davidson dealer perform the installation. Improper installation of this kit could result in death or serious injury. (00333b)

##### NOTE

This instruction sheet references Service Manual information. A Service Manual for your model motorcycle is required for this installation and is available from a Harley-Davidson Dealer.

### Kit Contents

Table 1. Kit Contents

Description (Quantity)	Part Number
Screw, pan head, TORX <sup>®</sup> , 3/8-16 x 1 in., Grade 8 (5)	4563

### INSTALLATION

1. See the REAR WHEEL section of the Service Manual for brake rotor (disc) and wheel inspection, removal and disassembly procedures

##### ⚠ WARNING

Use Harley-Davidson replacement fasteners. Aftermarket fasteners can adversely affect performance, which could result in death or serious injury. (00013a)

- After market fasteners may not have the specific property requirements to perform properly.
2. Place a few drops of Loctite<sup>®</sup> 243 (blue) on the threads of the **new** chrome screws from the kit. Install the brake disc using **ONLY** the new chrome screws. Torque the screws to 40 ft-lbs (54 Nm).

##### NOTICE

Do not re-use brake disc/rotor screws. Re-using these screws can result in torque loss and damage to brake components. (00319c)

3. Install the rear wheel and brake caliper per the REAR WHEEL section of the Service Manual

