



INSTRUCTIONS

J05188

2010-05-18



CHROME ABS HARNESS COVER

GENERAL

Kit Number

32700002

Models

For model fitment information, see the P&A Retail Catalog or the Parts and Accessories section of www.harley-davidson.com (English only).

Kit Contents

There are no Service Parts available with this kit.

REMOVAL

1. Remove the lower bolt securing the front brake caliper.

2. Hold the brake caliper to avoid damaging the caliper or wheel and remove the upper caliper bolt. Gently lower the caliper.
3. If equipped with a plastic clip securing the wheel speed sensor harness to the brake cable, remove the plastic clip and discard.

INSTALLATION

1. Align the wheel speed sensor harness cover over the wheel speed sensor harness, verifying the harness routed through the groove in the new cover and the harness is not pinched.
2. Install the the upper caliper bolt through the mounting hole in the wheel speed sensor harness and caliper. Tighten finger-tight.

J05188



Many Harley-Davidson® Parts & Accessories are made of plastics and metals which can be recycled. Please dispose of materials responsibly.

1 / 2

3. Install the lower caliper bolt through the mounting holes in the wheel sensor harness and caliper. Tighten finger-tight.
4. Tighten both caliper bolts to 38–52 N·m (28–38 ft-lbs).