



INSTRUCTIONS

J05189

2010-03-29



STARTER MOUNTING SCREW AND WASHER

GENERAL

Kit Number

4615A

Models

The screw and washer in this kit replace the stock starter mounting screw, lock patch and captured washer (part no. 4615) on 2007 and 2008 Touring models.

⚠ WARNING

Rider and passenger safety depend upon the correct installation of this kit. Use the appropriate service manual procedures. If the procedure is not within your capabilities or you do not have the correct tools, have a Harley-Davidson dealer perform the installation. Improper installation of this kit could result in death or serious injury. (00333b)

NOTE

This instruction sheet references service manual information. A service manual for your model motorcycle is required for this installation and is available from a Harley-Davidson Dealer.

Additional Parts Required

Proper installation of this kit requires the use of Loctite® 243 Threadlocker and Sealant - Blue (99642-97).

J05189



Many Harley-Davidson® Parts & Accessories are made of plastics and metals which can be recycled. Please dispose of materials responsibly.

Kit Contents

This kit contains one starter mounting screw and one washer.

INSTALLATION

1. See the service manual for starter installation procedure.
2. Apply a small amount of Loctite 243 (blue) to the screw before installing the screw and washer. Tighten screw to 33.9–36.6 N·m (25–27 ft-lbs).