

INSTRUCTIONS



SADDLEBAG GUARD RAIL

GENERAL

Kit Number

90201044

Models

For model fitment information, see the P&A Retail Catalog or the Parts and Accessories section of www.harley-davidson.com (English only).

Installation Requirements

J05740

Separate purchase of LOCTITE® 243 Threadlocker and Sealant - Blue (99642-97) is required for proper installation of this kit.

A WARNING

Rider and passenger safety depend upon the correct installation of this kit. If the procedure is not within your capabilities or you do not have the correct tools, have a Harley-Davidson dealer perform the installation. Improper installation of this kit could result in death or serious injury. (00308b)

Kit Contents

See Figure 3 and Table 1.

INSTALLATION

- See the owner's manual. Remove left saddlebag.
- 2. See Figure 1. Remove outer mount screws (1).
- 3. Remove lower mount screws (2).
- 4. If necessary, clean threaded holes with a thread chaser.
- See Figure 2. Place saddlebag guard over saddlebag. Align mounting holes.
- 6. Apply a small amount of Loctite 243 blue to screws (2). Loosely install washers and lower mount screws (2).
- Apply a small amount of Loctite 243 blue to screws (1). Loosely install outer mount screws (1).
- 8. Tighten screws to 10.8–13.6 N·m (96–120 in-lbs).
- 9. See the owner's manual. Install left saddlebag.
- 10. Repeat procedure for opposite side.





Figure 1. Saddlebag Screws



- 1. Outer mount screw (2)
- 2. Washer and lower mount screw (3)
- 3. Saddlebag guard rail

Figure 2. Saddlebag Guard Rail

SERVICE PARTS




Figure 3. Service Parts: Saddlebag Guard Rail

Table 1. Service Parts

Item	Description (Quantity)	Part Number
	Saddlebag guard, right	90201047
	Saddlebag guard, left	90201048
	Screw, torx, long (6)	940
	Screw, torx, short (4)	941
5	Washer	6703
6	rubber pad (2)	61079-82
7	Bumper (2)	62123-66A
8	Plug (2)	12100067

2/2 J05740