INSTRUCTIONS





CHROME ROTARY LATCH KIT

GENERAL

Kit Numbers

12600036

Models

For model fitment information, see the P&A Retail Catalog or the Parts and Accessories section of www.harley-davidson.com (English only).

Additional Parts Required

J05355

Separate purchase of LOCTITE[®] 243 Threadlocker and Sealant - Blue (Part No. 99642-97) or equivalent is required for installation of this kit.

Separate purchase and installation of additional parts or accessories may be required for proper installation of this kit on your model motorcycle. See the P&A Retail Catalog or the Parts and Accessories section of www.harley-davidson.com (English only) for a list of required parts or accessories for your model.

Kit Contents

See Figure 2 and Table 1.


REMOVAL

 Make note of the mounting configuration of the latches before removal.

NOTE

Detachable styles may vary from those shown in the illustration.

- 2. Remove the detachable accessory.
- 3. See Figure 1. Remove the latch assembly and note number of flat washers (2 and 5).



- 2. Washer
- 3. Spring washer
- 4. Detachable sideplate (typical)
- 5. Optional stock washer

Figure 1. Remove Latch

INSTALLATION

- 1. See Figure 2. Install spring washer (4) on mounting hub with the concave side facing away from the hub.
- 2. Install the latch (1) on the mounting hub in the same configuration as the removed latch.
- 3. Apply Loctite 243 Threadlocker and Sealant Blue to threads of screw (3) and install screw and washer (2) and washer (5 if supplied with stock latch).
- 4. Tighten screw to 3.4–4.5 N·m (30–40 in-lbs).

SERVICE PARTS




Figure 2. Service Parts: Rotary Latch Kit

Table 1. Service Parts: Detachables Latch Kit

Item	Description (Quantity)	Part Number
1	Latch, rotary chrome, left	Not Sold Separately
	Latch, rotary chrome, right (not	
	shown)	
2	Flat washer	Not Sold Separately
3	Screw	Not Sold Separately
4	Spring washer	Not Sold Separately
5	Flat washer (only required if stock	6912
	latch included two flat washers)	

2/2 J05355