INSTRUCTIONS

J06531



UPRIGHT PASSENGER BACKREST PAD

GENERAL

Kit Numbers

52300504

Models

For model fitment information, see the P&A retail catalog or the Parts and Accessories section of www.harley-davidson.com (English only).

Installation Requirements

A WARNING

Rider and passenger safety depend upon the correct installation of this kit. If the procedure is not within your capabilities or you do not have the correct tools, have a Harley-Davidson dealer perform the installation. Improper installation of this kit could result in death or serious injury. (00308b)

Kit Contents

See Figure 1 and Refer to Table 1.

PREPARE

- On the rear of the backrest pad, feel through the backrest material and locate mounting holes.
- Carefully cut the clear plastic rain seal away from the screw holes. This will prevent the plastic from catching in the screw threads.

INSTALLATION

NOTE

Items A, B and C are in the Rigid Mount Sissy Bar Upright kit.

- Install backrest pad.
 - Align recessed channels of the backrest pad (1) with the upright bars of the backrest assembly (C).
 - b. Align backrest support (B) with the holes in the backrest pad (1).
 - c. Install screws (A).
 - d. Tighten.

Torque: 1.1-1.7 N·m (10-15 in-lbs)

NOTE

Do not over-tighten screws due to risk of stripping off threads.

SERVICE PARTS




Figure 1.

Table 1. Service Parts 52300502 Black Backrest

Item	Description (Quantity)	Part Number
1	Backrest pad	Not sold separately
Items mentioned in text but not included in kit.		
Α	Screw, 1/4-28 Button head Torx™ (2)	
В	Backrest support	
С	Backrest assembly	