# **INSTRUCTIONS**

2019-01-15



# **FXDRS RIDER SEAT KITS**

## **GENERAL**

#### Kit Number

52000390, 52000398, 52000399

J06711

# **Models**

For model fitment information, see the P&A Retail Catalog or the Parts and Accessories section of www.harley-davidson.com (English only).

#### **Kit Contents**

See Table 1 and Figure 1.

# **INSTALLATION**

#### **A WARNING**

Rider and passenger safety depend upon the correct installation of this kit. If the procedure is not within your capabilities or you do not have the correct tools, have a Harley-Davidson dealer perform the installation. Improper installation of this kit could result in death or serious injury. (00308b)

#### NOTE

When a solo seat is installed without a passenger seat, the passenger foot pegs or foot boards and the passenger grab strap must be removed.

1. Remove cowl cover and seat. See Owner's Manual.

- Retain Original Equipment (OE) hardware screws for installation of new seat.
- 3. Install **new** seat, inserting the tongue at front of seat into the channel into frame. See Owner's Manual.
- 4. Install screws (1). Tighten.

Torque: 10-12 N·m (7-9 ft-lbs)

5. After installing seat, pull up on the seat to verify that it is secure. See Owner's Manual.

## **SERVICE PARTS**




Figure 1. Service Parts: FXDRS Rider Seat

Table 1. Service Parts: FXDRS Rider Seat Kits

Item	Description (Quantity)	Part Number
1	Screw (2)	3909
2	Solo seat	Not Sold Separately