



INSTRUCTIONS

J05963

2021-08-02



HORN COVER KIT

GENERAL

Kit Number

68189-07A, 69039-09A, 69166-01B, 69167-02B, 61300452, 61300621, 61300622, 61300623, 61301045, 61301177

Models

For model fitment information, see the P&A Retail Catalog or the Parts and Accessories section of www.harley-davidson.com (English only).

ELECTRICAL OVERLOAD

⚠ WARNING

When installing any electrical accessory, be certain not to exceed the maximum amperage rating of the fuse or circuit breaker protecting the affected circuit being modified. Exceeding the maximum amperage can lead to electrical failures, which could result in death or serious injury. (00310a)

Additional Requirements

Separate purchase of LOCTITE® 271 MEDIUM STRENGTH THREADLOCKER AND SEALANT (Red) (part no. 99671-97) or equivalent is required for proper installation of this kit.

Kit Contents

See Figure 1 and Table 1.

PREPARE

⚠ WARNING

To prevent accidental vehicle start-up, which could cause death or serious injury, remove main fuse before proceeding. (00251b)

1. Remove main fuse. See service manual.

REMOVE

1. Remove acorn nut (1) and flat washer (2) to free horn assembly from rubber mount stud (C).
2. Disconnect elbow terminals from spade contacts and release main harness conduit from J-clamp (E).
3. Remove flange nut (F) from circular recess at back of horn bracket. Remove horn from chrome horn cover (5).
4. Remove flange screws (D).

5. Remove and retain speed nuts (4) from horn cover unless provided in kit.

INSTALL

1. Clip speed nuts (4) to horn bracket (5) at top and bottom holes.
2. Install supplied washer (6) in kit onto horn stud.
3. Fit horn into new horn cover so the stud at back slides through hole in horn bracket.
4. Apply two drops of Loctite® 271 (Red) to threads of nut (F) fastening the horn to the horn cover.

5.

NOTE

Over tightening the flange nut (F) can cause permanent horn damage resulting in reduced volume and tone quality.

Install flange nut (F) on horn stud and tighten.

Torque: 9–11.3 N·m (80–100 **in-lbs**) *Horn stud nut*

6. Install flange screws.
 - a. **All kits except 61301177:** Install flange screws (D).
 - b. **Kit 61301177:** Install flange screws (D, 7).
 - c. Tighten flange screws (D, 7).
Torque: 4–4.5 N·m (35–40 **in-lbs**)

7.

NOTE

The horn is not polarity sensitive. Elbow terminals can connect to either spade or contact.

Install elbow terminals onto spade contacts.

8. Capture main harness conduit in J-clamp. Install horn bracket onto rubber mount stud.
9. Apply 2 drops of Loctite 271 (Red) to threads on horn, rubber mount stud (C).
10. Install flat washer (2) and acorn nut (1).
11. Tighten acorn nut.
Torque: 9–11.3 N·m (80–100 **in-lbs**) *Horn mount acorn nut*

COMPLETE

1. Install main fuse. See service manual.



2. Test horn.

SERVICE PARTS




Figure 1. HORN COVER KIT (Cover shown may not reflect actual cover in kit.)

Table 1. Service Parts Table

Item	Description (Quantity)	Part Number
1	Nut, acorn (For kit 61300452)	10400023
2	Washer (For kit 61300452)	10600030
3	Horn bracket, black (For kit 61300452)	69274-10
	Horn bracket, chrome (For kit 68189-07A)	Not Sold Separately
4	Speed nuts, (2) (For kit 61300452)	8108
5	Horn cover assembly (For kit 61300452 only).	61300477
	Horn cover assembly (For kits 68189-07, 69039-09A, 69166-01B, 69167-02B, 61300621, 61300622, 61300623, 61301045, 61301177	Not Sold Separately
6	Washer (1) (For kits 61300452, 68189-07A, 69039-09A, 69166-01B, 69167-02B, 61300621, 61300622, 61300623, 61301045, 61301177)	10300085
7	Screw, flange (1) (For kit 61301177)	3588
Items mentioned in text, but not included in kit:		
A	Horn mount bracket assembly	
B	Horn, trumpet	
C	Horn, rubber mount	
D	Screw, large flange	
E	Clamp	
F	Hex nut, (metric, M6)	