



# INSTRUCTIONS

J06121

2014-11-01



## SAE 2-PIN TO USB ADAPTER

### GENERAL

#### Kit Number

69201149

#### ⚠ WARNING

Rider and passenger safety depend upon the correct installation of this kit. If the procedure is not within your capabilities or you do not have the correct tools, have a Harley-Davidson dealer perform the installation. Improper installation of this kit could result in death or serious injury. (00308b)

#### Electrical Overload

#### ⚠ WARNING

When installing any electrical accessory, be certain not to exceed the maximum amperage rating of the fuse or circuit breaker protecting the affected circuit being modified. Exceeding the maximum amperage can lead to electrical failures, which could result in death or serious injury. (00310a)

#### NOTICE

It is possible to overload the vehicle's charging system by adding too many electrical accessories. If the combined electrical accessories operating at any one time consume more electrical current than the vehicle's charging system can produce, the electrical consumption can discharge the battery and cause damage to the vehicle's electrical system. (00211d)

#### NOTE


- USB output 1 A at 5 V.
- Use with battery tender harness (fused) or pre-installed SAE 2 cable on 2014-Later Touring Models.

### Kit Contents

See Figure 2 and Table 1.

### Installation

1. Remove the left side cover.
2. See Figure 1. Locate the battery tender connector (1) under the left side cover.



1. Battery tender connector
2. Route connector through slot

Figure 1. Battery Tender Connector

3. See Figure 2. Plug the input connector (A) into battery tender connector.
4. Plug device into the USB connector (B).
5. Install left side cover.

### IN USE

#### NOTE

- Power outlet is not switched. It remains "ON" even with ignition key switch in "OFF" position.
- DO NOT leave items connected to the power outlet unattended.
- This device supports a wide variety of USB powered devices. Charging rates can vary with device input current, cable style and cable length.
- It is not recommended to permanently attach an adapter or a device to the battery tender connector.
- DO NOT mount electronic devices with a hard drive memory on the vehicle for use or charging while the vehicle is in operation. Vehicle vibration can permanently damage the device. Refer to the device instructions to determine if the version used has a hard drive memory.

## SERVICE PARTS




Figure 2. Service Parts, SAE 2-Pin to USB Adapter

Table 1. Service Parts

Item	Description (Quantity)	Part Number
1	SAE 2-pin to USB adapter	69201149
<b>Item mentioned in text.</b>		
A	Input connector	
B	USB connector	
C	Dust cover	