

# VRSC MODELS

2007 HARLEY-DAVIDSON® INTERNATIONAL OWNER'S MANUAL



Harley-Davidson Motor Company  
Service Communications  
Milwaukee WI 53208 USA

2025-03-29



99736-071

English

Printed in the USA

2007 HARLEY-DAVIDSON® INTERNATIONAL OWNER'S MANUAL  
VRSC MODELS - 99736-071



99736-071

# VRSC MODELS

2007 HARLEY-DAVIDSON® INTERNATIONAL OWNER'S MANUAL





99736-071

2007 HARLEY-DAVIDSON® INTERNATIONAL OWNER'S MANUAL - VRSC MODELS



# TABLE OF CONTENTS

## INTRODUCTION

Safety Definitions.....	1
Your Owner's Manual.....	1
We Care About You.....	1
United States Owners.....	2
Customer Service Assistance.....	2

## SAFETY FIRST

Safe Operating Rules: VRSC Models.....	5
Rules of the Road.....	10
Accessories and Cargo.....	11
Accessory and Cargo Guidelines.....	12

## IDENTIFICATION

Vehicle Identification Number: VRSC Models.....	15
Labels.....	17

## SPECIFICATIONS

Specifications: 2007 VRSC Models.....	19
Tire Data: VRSC Models.....	23
Catalytic Converters: VRSC Models.....	24
Gasoline Blends.....	24
Fuel.....	25

## CONTROLS AND INDICATORS

General: Controls and Indicators.....	27
Ignition Switch: VRSC Models.....	27
Hand Controls: Basic Operation.....	29
Electric Starter Switch.....	29
Engine OFF/RUN Switch.....	29
Throttle Control Grip.....	30
Clutch Hand Lever.....	30
Horn Switch.....	31
Headlamp Dimmer Switch.....	31
Turn Signal Switches.....	31
Turn Signal Switch Operation.....	32
Hazard Warning 4-Way Flasher.....	33
Indicator Lamps: VRSC Models.....	33
Instruments: VRSC Models.....	37
Speedometer.....	37
Setting Clock.....	37
Fuel Range Function.....	38
Tachometer.....	39
Tip Indicator Lamp.....	39
Sequential Port Fuel Injection.....	41
Check Engine Lamp.....	41
Low Fuel Lamp.....	41
Gear Shift Lever.....	41
Brake System.....	43

## TABLE OF CONTENTS

Jiffy Stand.....	44
Rear View Mirrors.....	44
Fuel Filler Cap: VRSC Models.....	44
Fork Lock: VRSC Models.....	46
Rear Shock Absorbers: VRSC Models.....	46
General.....	46
Adjustment.....	47

## HARLEY-DAVIDSON SMART SECURITY SYSTEM

HARLEY-DAVIDSON SMART SECURITY SYSTEM.....	49
Components.....	49
Options.....	49
FCC Regulations.....	50
Hands-Free Fob.....	50
Fob Assignment.....	50
Riding with a Fob.....	51
Personal Identification Number (PIN).....	52
Changing the PIN.....	52
Security Status Indicator.....	54
Arming and Disarming.....	55
Arming.....	55
Disarming.....	55
Disarming with a PIN.....	56
Hazard Warning 4-Way Flasher.....	57

Alarm.....	58
Warnings.....	58
The Alarm.....	58
Deactivate the Alarm.....	59
Siren Chirpless/Chirp Modes: International Models.....	59
Chirpless Mode.....	59
Chirp Mode.....	59
Switching Modes.....	59
Transport Mode.....	60
To Enter Transport Mode.....	60
To Exit the Transport Mode.....	60
Storage and Service Departments.....	60
Long Term Parking.....	60
Service Departments.....	60
Fob Battery.....	61
Replacing the Battery.....	61
Power Disconnects.....	62
Optional Siren.....	62
Troubleshooting.....	62
Key Icon.....	62
Fob.....	62
Siren.....	62

## OPERATION

Operating Recommendations: VRSC Models.....	65
---	----

# TABLE OF CONTENTS

Break-in Riding Rules: VRSC Models.....	66	Rear Drive Belt: VRSC Models.....	85
The First 500 Miles (800 Kilometers).....	66	Chassis Lubrication.....	86
Pre-Riding Checklist: VRSC Models.....	66	Oil Applications.....	87
Starting the Engine.....	68	Front Fork Oil.....	87
General.....	68	Fuel Filter.....	87
Starting.....	68	Clutch: VRSC Models.....	87
Stopping the Engine.....	69	Front Fork Bearings.....	90
Shifting Gears.....	70	Rear Fork Pivot Shaft.....	90
Getting Started.....	70	Brakes: VRSC Models.....	90
Upshift (Acceleration).....	70	Tires: VRSC Models.....	95
Downshift (Deceleration).....	71	Tire Replacement.....	96
		Inspection.....	96
		When To Replace Tires.....	96
<b>MAINTENANCE AND LUBRICATION</b>		Spark Plugs/Coils: VRSC Models.....	97
Safe Operating Maintenance: VRSC Models.....	73	Shock Absorbers.....	98
Break-in Maintenance.....	73	Ignition.....	98
Engine Lubrication.....	73	Air Cleaner: VRSC Models.....	98
Checking Oil Level: VRSC Models.....	74	Headlamp: VRSC Models.....	101
Cold Engine Oil Level Check.....	74	Headlamp Alignment: VRSC Models.....	104
Hot Engine Oil Level Check.....	76	Turn Signal Bulbs: Bullet Style.....	106
Changing Oil and Oil Filter: VRSC Models.....	77	Replacement.....	106
Winter Lubrication.....	79	Alignment.....	107
Coolant Level.....	79	Alternator/Voltage Regulator.....	107
Checking Coolant Level in Expansion Tank (All Models		Charging Rate.....	107
Except VRSCR).....	80	Battery: General.....	108
Checking Coolant Level in Expansion Tank (VRSCR Model		Type.....	108
Only).....	82		

# TABLE OF CONTENTS

Voltmeter Test.....	111
Cleaning and Inspection.....	111
Charging.....	111
Storage.....	114
Battery: All VRSC Models Except VRSCR.....	116
Disconnection and Removal.....	116
Installation and Connection.....	119
Battery: VRSCR Model Only.....	122
Disconnection and Removal.....	122
Installation and Connection: VRSCR Model Only.....	124
Jump Starting.....	126
Positive Cable.....	126
Negative Cable.....	127
Electrical Protection: VRSC Models.....	128
Accessing Fuse Blocks and Relays: All VRSC Models Except VRSCR.....	128
Accessing Fuse Block and Relays: VRSCR Model Only.....	130
Fuse Replacement: All VRSC Models Except VRSCR.....	132
Fuse Replacement: VRSCR Model Only.....	132
Replacing The Maxi-Fuse: All VRSC Models.....	133
Seat: VRSC Models.....	134
Opening.....	134
Closing.....	134

Motorcycle Storage: VRSC Models.....	135
Placing Motorcycle in Storage.....	135
Removing Motorcycle From Storage.....	136

## ACCESSORIES MAINTENANCE

General Maintenance.....	139
Black Denim Finish.....	139
General.....	139
How to Clean.....	139
Cleaning Your V-Rod.....	139
Leather Care.....	141
Wheel Care: VRSC Models.....	142
Windshields.....	143

## TROUBLESHOOTING

Troubleshooting: General.....	145
Engine: VRSC Models.....	145
Starter Does Not Operate or Does Not Turn Engine Over.....	145
Engine Turns Over But Does Not Start.....	145
Starts Hard.....	145
Starts But Runs Irregularly or Misses.....	146
A Spark Plug Fouls Repeatedly.....	146
Pre-ignition or Detonation (Knocks or Pings).....	146
Overheats.....	146



## TABLE OF CONTENTS

Excessive Vibration.....	146
Cooling System.....	146
Overheats.....	146
Electrical System.....	147
Alternator Does Not Charge.....	147
Alternator Charge Rate is Below Normal.....	147
Transmission: VRSC Models.....	147
Transmission Shifts Hard.....	147
Transmission Jumps Out of Gear.....	147
Clutch Slips.....	147
Clutch Drags or Does Not Release.....	147
Clutch Chatters.....	147
Brakes.....	147
Brakes Do Not Hold Normally.....	147

## WARRANTIES AND RESPONSIBILITIES

Warranty and Maintenance.....	149
Keeping It All Harley-Davidson.....	149


Important Moving Information.....	150
Warranty/Service Information.....	150
Owner Transfer Identification Form.....	150
Required Documentation for Imported Motorcycles.....	150

## LIMITED MOTORCYCLE WARRANTY

2007 HARLEY-DAVIDSON MOTORCYCLE LIMITED WARRANTY.....	151
24 Months/Unlimited Miles.....	151
Duration.....	151
Owner's Obligations.....	151
Exclusions.....	152
Other Limitations.....	152
Important: Read Carefully.....	152

## MAINTENANCE SCHEDULING

Regular Service Intervals.....	155
Service Literature.....	159



## NOTES

---



## SAFETY DEFINITIONS

Statements in this manual preceded by the following words are of special significance:

### ▲ WARNING

**WARNING** indicates a potentially hazardous situation which, if not avoided, could result in death or serious injury. (00119a)

### ▲ CAUTION

**CAUTION** indicates a potentially hazardous situation which, if not avoided, may result in minor or moderate injury. (00139a)

### NOTICE

**NOTICE** indicates a potentially hazardous situation which, if not avoided, may result in property damage. (00140b)

### NOTE

A *NOTE* refers to important information and is placed in italic type. It is recommended that you take special notice of these items.

**HARLEY-DAVIDSON MOTORCYCLES ARE FOR ON-ROAD USE ONLY**

This motorcycle is not equipped with a spark arrester and is designed to be used only on the road. Operation of off-road usage in some areas may be illegal. Obey local laws and regulations. This manual should be considered a permanent part of the motorcycle and should remain with the motorcycle when resold.

VISIT THE HARLEY-DAVIDSON WEB SITE

<http://www.harley-davidson.com>

## YOUR OWNER'S MANUAL

### We Care About You

Welcome to the Harley-Davidson Motorcycling Family! When enjoying your Harley-Davidson motorcycle, be sure to ride safely, respectfully and within the limits of the law and your abilities. Always wear a helmet, proper eyewear and protective clothing, and insist your passenger does too. Never ride while under the influence of alcohol or drugs. Know your Harley and read and understand your owner's manual from cover to cover.

This manual has been prepared to acquaint you with the operation, care and maintenance of your motorcycle and to provide you with important safety information. Follow these instructions carefully for maximum motorcycle performance and for your personal motorcycling safety and pleasure. Your Owner's Manual contains instructions for operation and minor

maintenance. Major repairs are covered in the Harley-Davidson Service Manual. Such major repairs require the attention of a skilled technician and the use of special tools and equipment. Your Harley-Davidson dealer has the facilities, experience and Genuine Harley-Davidson parts necessary to properly render this valuable service. We recommend that any emission system maintenance be performed by an authorized Harley-Davidson dealer.

Attend a rider safety course. To enroll in a Harley-Davidson Riding Academy course, call 1-414-343-4056 (U.S.) or visit [www.harley-davidson.com/learntoride](http://www.harley-davidson.com/learntoride). In the United States, for information about Motorcycle Safety Foundation rider courses, call 1-800-446-9227 or visit [www.msf-usa.org](http://www.msf-usa.org).

## United States Owners

Your Harley-Davidson motorcycle conforms to all applicable U.S. Federal Motor Vehicle Safety Standards and U.S. Environmental Protection Agency regulations effective on the date of manufacture. Protect your privilege to ride by joining the American Motorcyclist Association. Visit [www.americanmotorcyclist.com](http://www.americanmotorcyclist.com) for more information.

Harley-Davidson reserves the right to change specifications, equipment or designs at any time without notice and without incurring obligation.

## CUSTOMER SERVICE ASSISTANCE

Most sales or service issues are resolved at the dealership.

1. Discuss your problem with the appropriate personnel at the dealership in the Sales, Service or Parts area. If that proves unsuccessful, speak to the owner of the dealership or the general manager.
2. If you cannot resolve the issue with the dealership, contact the Harley-Davidson Customer Support Center. Harley-Davidson Motor Company Attention: Harley-Davidson Customer Support Center P.O. Box 653 Milwaukee, Wisconsin 53201 1-800-258-2464 (U.S. only) 1-414-343-4056

For customers outside the US, contact your local Harley-Davidson market office, call 1-414-343-4056 or visit [harley-davidson.com](http://harley-davidson.com).

**Table 2. Vehicle and Personal Data**

PERSONAL INFORMATION	DEALER INFORMATION
Date of Purchase:	
Name:	Name:
Address:	Address:
Address:	Address:
Vehicle Identification Number:	Sales Contact:
Key Number:	Service Contact:



## NOTES

---



## SAFE OPERATING RULES: VRSC MODELS

Before operating your new motorcycle it is your responsibility to read and follow the operating and maintenance instructions in this manual, and follow these basic rules for your personal safety.

- Know and respect the rules of the road (see RULES OF THE ROAD section). Carefully read and observe the rules contained in the RIDING TIPS booklet accompanying this Owner's Manual. Read and familiarize yourself with the contents of the MOTORCYCLE HANDBOOK for your state.
- Before starting engine, check for proper operation of brake, clutch, shifter, throttle controls, correct fuel and oil supply.

### ⚠ WARNING

**Harley-Davidson parts and accessories are designed for Harley-Davidson motorcycles. Using non-Harley-Davidson parts or accessories can adversely affect performance, stability or handling, which could result in death or serious injury. (00001b)**

### ⚠ WARNING

**Stop the engine when refueling or servicing the fuel system. Do not smoke or allow open flame or sparks near gasoline. Gasoline is extremely flammable and highly explosive, which could result in death or serious injury. (00002a)**

### ⚠ WARNING

**Do not loosen or remove pressure cap when cooling system is hot. The cooling system is under pressure and hot coolant and steam can escape from pressure cap, which could cause severe burns. Allow motorcycle to cool before servicing the cooling system. (00091c)**

### ⚠ CAUTION

**At operating temperature, radiators and oil coolers contain hot fluids. Contact with a radiator or oil cooler can result in minor or moderate burns. (00141b)**

- Use only Harley-Davidson approved parts and accessories. Use of certain other manufacturer's performance parts will void your new motorcycle warranty. See your Harley-Davidson dealer for details.

When refueling your motorcycle, the following rules should be observed.

- Refuel in a well ventilated area with the engine turned off.
- Remove fuel filler cap slowly.
- Do not smoke or allow open flames or sparks when refueling or servicing the fuel system.
- Leave air space to allow for fuel expansion.

**⚠ WARNING**

Do not store motorcycle with gasoline in tank within the home or garage where open flames, pilot lights, sparks or electric motors are present. Gasoline is extremely flammable and highly explosive, which could result in death or serious injury. (00003a)

**⚠ WARNING**

Engine exhaust from this product contains chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm. (00004f)

**⚠ WARNING**

Wheel weights on wheels without spokes contain lead and lead compounds, chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm. (00356d)

**⚠ WARNING**

Do not run motorcycle in a closed garage or confined area. Inhaling motorcycle exhaust, which contains poisonous carbon monoxide gas, could result in death or serious injury. (00005a)

**⚠ WARNING**

The jiffy stand locks when placed in the full forward (down) position with vehicle weight on it. If the jiffy stand is not in the full forward (down) position with vehicle weight on it, the vehicle can fall over which could result in death or serious injury. (00006a)

**⚠ WARNING**

Be sure jiffy stand is fully retracted before riding. If jiffy stand is not fully retracted, it can contact the road surface causing a loss of vehicle control, which could result in death or serious injury. (00007a)

- A new motorcycle must be operated according to the special break-in procedure. See OPERATION > BREAK-IN RIDING RULES: VRSC MODELS (Page 66).
- Operate motorcycle only at moderate speed and out of traffic until you have become thoroughly familiar with its operation and handling characteristics under all conditions.

**NOTE**

*We recommend that you obtain information and formal training in the correct motorcycle riding technique. The Motorcycle Safety Foundation® offers beginning and advanced rider safety courses. Call (949)727-3227 for information.*



### **⚠ WARNING**

**Travel at speeds appropriate for road and conditions and never travel faster than posted speed limit. Excessive speed can cause loss of vehicle control, which could result in death or serious injury. (00008a)**

- Do not exceed the legal speed limit or drive too fast for existing conditions. Always reduce speed when poor driving conditions exist. High speed increases the influence of any other condition affecting stability and increases the possibility of loss of control.
- Pay strict attention to road surfaces and wind conditions. Any two wheeled vehicle may be subject to upsetting forces such as wind blasts from passing trucks, holes in the pavement, rough road surfaces, rider control error, etc. These forces may influence the handling characteristics of your motorcycle. If this happens, reduce speed and guide the motorcycle with a relaxed grip to a controlled condition. Do not brake abruptly or force the handlebar. This may aggravate an unstable condition.
- Keep cargo weight concentrated close to the motorcycle and as low as possible to minimize the change in the motorcycle's center of gravity. Distribute weight evenly on both sides of the vehicle and do not load bulky items too far behind the rider or add weight to the handlebars or front forks. Do not exceed maximum specified load in each saddlebag.

### **NOTE**

*New riders should gain experience under various conditions while driving at moderate speeds.*

- Operate your motorcycle defensively. Remember, a motorcycle does not afford the same protection as an automobile in an accident. One of the most common accident situations occurs when the driver of the other vehicle fails to see or recognize a motorcycle and turns left into the on-coming motorcyclist. Operate only with headlamp on.

### **⚠ WARNING**

**Avoid contact with exhaust system and wear protective clothing that completely covers legs while riding. Exhaust pipes and mufflers get very hot when engine is running and remain too hot to touch, even after engine is turned off. Failure to wear protective clothing could result in burns or other serious injury. (00009a)**

- Wear an approved helmet, clothing, and foot gear suited for motorcycle riding. Bright or light colors are best for greater visibility in traffic, especially at night. Avoid loose, flowing garments and scarves.
- When carrying passengers, it is your responsibility to instruct them on proper riding procedures. (See Riding Tips included in your Harley-Davidson Owner's Kit.)

- Do not allow other individuals, under any circumstances, to operate your motorcycle unless you know they are experienced, licensed riders and are thoroughly familiar with the operation of your particular motorcycle.
- Protect your motorcycle against theft. After parking your motorcycle, lock the steering head and remove ignition key from switch. Set security alarm if present.
- Safe motorcycle operation requires alert mental judgment combined with a defensive driving attitude. Do not allow fatigue, alcohol or drugs to endanger your safety or that of others.
- Vehicles equipped with a sound system should have the volume adjusted to a nondistracting level before operating vehicle.
- Maintain your motorcycle in proper operating condition in accordance with Table 30. Particularly important to motorcycle stability is proper tire inflation pressure, tread condition, and proper adjustment of wheel bearings and steering head bearings.

#### **⚠ WARNING**

**Do not operate vehicle with forks locked. Locking the forks restricts the vehicle's turning ability, which could result in death or serious injury. (00035a)**

#### **⚠ WARNING**

**Perform the service and maintenance operations as indicated in the regular service interval table. Lack of regular maintenance at the recommended intervals can affect the safe operation of your motorcycle, which could result in death or serious injury. (00010a)**

#### **⚠ WARNING**

**Do not operate motorcycle with loose, worn or damaged steering or suspension systems. Contact a Harley-Davidson dealer for repairs. Loose, worn or damaged steering or suspension components can adversely affect stability and handling, which could result in death or serious injury. (00011a)**

#### **⚠ WARNING**

**Regularly inspect shock absorbers and front forks. Replace leaking, damaged or worn parts that can adversely affect stability and handling, which could result in death or serious injury. (00012a)**

#### **⚠ WARNING**

**Use Harley-Davidson replacement fasteners. Aftermarket fasteners can adversely affect performance, which could result in death or serious injury. (00013a)**

- See a Harley-Davidson service manual for proper torque values.
- Aftermarket fasteners may not have the specific property requirements to perform properly.

#### **⚠ WARNING**

**Be sure tires are properly inflated, balanced, undamaged, and have adequate tread. Inspect your tires regularly and see a Harley-Davidson dealer for replacements. Riding with excessively worn, unbalanced, improperly inflated, overloaded or damaged tires can lead to tire failure and adversely affect stability and handling, which could result in death or serious injury. (00014b)**

#### **⚠ WARNING**

**Replace punctured or damaged tires. In some cases, small punctures in the tread area may be repaired from within the removed tire by a Harley-Davidson dealer. Speed should NOT exceed 80 km/h (50 mph) for the first 24 hours after repair, and the repaired tire should NEVER be used over 129 km/h (80 mph). Failure to follow this warning could lead to tire failure and result in death or serious injury. (00015b)**

#### **⚠ WARNING**

**Do not exceed the motorcycle's Gross Vehicle Weight Rating (GVWR) or Gross Axle Weight Rating (GAWR). Exceeding these weight ratings can lead to component failure and adversely affect stability, handling and performance, which could result in death or serious injury. (00016f)**

- GVWR is the sum of the weight of the motorcycle, accessories, and the maximum weight of the rider, passenger and cargo that can be safely carried.
- GAWR is the maximum amount of weight that can be safely carried on each axle.
- The GVWR and GAWR are shown on the information plate, located on the frame down tube.

#### **⚠ WARNING**

**Do not tow a disabled motorcycle. Towing can adversely affect stability and handling, which could result in death or serious injury. (00017a)**

#### **⚠ WARNING**

Do not pull a trailer with a motorcycle. Pulling a trailer can cause tire overload, damage and failure, reduced braking performance, and adversely affect stability and handling, which could result in death or serious injury. (00018c)

#### **⚠ WARNING**

Contact with DOT 4 brake fluid can have serious health effects. Failure to wear proper skin and eye protection could result in death or serious injury.

- If inhaled: Keep calm, remove to fresh air, seek medical attention.
- If on skin: Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. If irritation develops, seek medical attention.
- If in eyes: Wash affected eyes for at least 15 minutes under running water with eye lids held open. If irritation develops, seek medical attention.
- If swallowed: Rinse mouth and then drink plenty of water. Do not induce vomiting. Contact Poison Control. Immediate medical attention required.
- See Safety Data Sheet (SDS) for more details available at [sds.harley-davidson.com](https://sds.harley-davidson.com)

(00240e)

#### **⚠ WARNING**

Batteries, battery posts, terminals and related accessories contain lead and lead compounds, and other chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm. Wash hands after handling. (00019e)

#### **⚠ WARNING**

Consult a Harley-Davidson dealer regarding any questions or problems that occur in the operation of your motorcycle. Failure to do so can aggravate an initial problem, cause costly repairs, cause an accident and could result in death or serious injury. (00020a)

- Be sure all equipment required by federal, state and local law is installed and in good operating condition.

### **RULES OF THE ROAD**

- Keep to the right side of the road centerline when meeting other vehicles coming in the opposite direction. Ride to left of center of your lane to avoid oily pavement ahead.

- Always sound your horn, actuate your turn signals, and exercise caution when passing other vehicles going in the same direction. Never try to pass another vehicle going in the same direction at street intersections, on curves, or when going up or down a hill.
- At street intersections give the right-of-way to the vehicle on your right. Do not presume you have the right-of-way, as the other driver may not know it is your turn.
- Always signal when preparing to stop, turn or pass.
- All traffic signs, including those used for the control of traffic at intersections, should be obeyed promptly. SLOW DOWN signs near schools and CAUTION signs at railroad crossings should always be observed and your actions governed accordingly.
- When intending to turn to the left, signal at least 100 feet (30.5 meters) before reaching the turning point. Move over to the centerline of the street (unless local rules require otherwise), slow down, enter the intersection of the street and then turn carefully to the left.
- Never anticipate a traffic light. When a change is indicated from GO to STOP (or vice versa) in the traffic control systems at intersections, slow down and wait for the light to change. Never run through a yellow or red traffic light.
- While turning either right or left, watch for pedestrians, animals, as well as vehicles.
- Do not leave the curb or parking area without signaling. Be sure your way is clear to enter moving traffic. A moving line of traffic always has the right-of-way.
- Be sure your license plate is installed in the position specified by law and is clearly visible at all times. Keep the plate clean.
- Ride at a safe speed that is consistent with the type of highway you are on. Pay strict attention to whether the road is dry, oily, icy or wet.
- Watch for debris such as leaves or loose gravel.
- Weather and traffic conditions on the highway dictate adjusting your speed and driving habits accordingly.

## ACCESSORIES AND CARGO

Harley-Davidson Motor Company cannot test and make specific recommendations concerning every accessory or combination of accessories sold. Therefore, the rider must be responsible for safe operation of the motorcycle when installing accessories or carrying additional weight.

#### **⚠ WARNING**

See **ACCESSORIES AND CARGO** section within the **SAFETY FIRST** section in your owner's manual. Improper cargo loading or accessory installation can cause component failure and adversely affect stability, handling and performance, which could result in death or serious injury. (00021c)

#### **⚠ WARNING**

**Do not exceed the motorcycle's Gross Vehicle Weight Rating (GVWR) or Gross Axle Weight Rating (GAWR). Exceeding these weight ratings can lead to component failure and adversely affect stability, handling and performance, which could result in death or serious injury. (00016f)**

- GVWR is the sum of the weight of the motorcycle, accessories, and the maximum weight of the rider, passenger and cargo that can be safely carried.
- GAWR is the maximum amount of weight that can be safely carried on each axle.
- The GVWR and GAWR are shown on the information plate which is located on the frame down tube.

#### **⚠ WARNING**

**Do not pull a trailer with a motorcycle. Pulling a trailer can cause tire overload, damage and failure, reduced braking performance, and adversely affect stability and handling, which could result in death or serious injury. (00018c)**

### **Accessory and Cargo Guidelines**

The following guidelines should be used when equipping a motorcycle, carrying passengers and/or cargo.

#### **⚠ WARNING**

**Travel at speeds appropriate for road and conditions and never travel faster than posted speed limit. Excessive speed can cause loss of vehicle control, which could result in death or serious injury. (00008a)**

- Do not exceed the legal speed limit or drive too fast for existing conditions. Always reduce speed when poor driving conditions exist. High speed increases the influence of any other condition affecting stability and increases the possibility of loss of control.

- Pay strict attention to road surfaces and wind conditions. Any two wheeled vehicle may be subject to upsetting forces such as wind blasts from passing trucks, holes in the pavement, rough road surfaces, rider control error, etc. These forces may influence the handling characteristics of your motorcycle. If this happens, reduce speed and guide the motorcycle with a relaxed grip to a controlled condition. Do not brake abruptly or force the handlebar. This may aggravate an unstable condition.
- Keep cargo weight concentrated close to the motorcycle and as low as possible. This minimizes the change in the motorcycle's center of gravity.
- Distribute weight evenly on both sides of the vehicle.
- Do not load bulky items too far behind the rider or add weight to the handlebars or front forks.
- Do not exceed maximum specified load in each saddlebag.
- Luggage racks are designed for lightweight items. Do not overload racks.
- Be sure cargo is secure and will not shift while riding and recheck the cargo periodically. Accessories that change the operator's riding position may increase reaction time and affect handling of the motorcycle.
- Additional electrical equipment may overload the motorcycle's electrical system possibly resulting in electrical system and/or component failure.

#### **⚠ WARNING**

**If Equipped: Front and/or rear guards are not intended to provide protection from bodily injury in a collision with another vehicle or any other object. (00022d)**

Large surfaces such as fairings, windshields, back rests, and luggage racks can adversely affect handling. Only genuine Harley-Davidson items designed specifically for the motorcycle model should be used with proper installation.

#### **⚠ WARNING**

**Harley-Davidson parts and accessories are designed for Harley-Davidson motorcycles. Using non-Harley-Davidson parts or accessories can adversely affect performance, stability or handling, which could result in death or serious injury. (00001b)**

#### **⚠ WARNING**

**Only Touring Harley-Davidson Motorcycles are suitable for sidecar use. Consult a Harley-Davidson dealer. Use of motorcycles other than Touring models with sidecars could result in death or serious injury. (00040a)**

## NOTES

---






## VEHICLE IDENTIFICATION NUMBER: VRSC MODELS

See Figure 1. The full 17-digit serial or Vehicle Identification Number (V.I.N.) is stamped on the steering head and on a label located on the left frame tube above the front engine cylinder.


An abbreviated V.I.N. is stamped on the left side crankcase above the sump.


### NOTE

*Always give the full 17-digit Vehicle Identification Number when ordering parts or making any inquiry about your motorcycle.*



**Figure 1. V.I.N. Stamping Location: VRSC Models**





- |                                     |                                      |
|-------------------------------------|--------------------------------------|
| 1. Market designation (1 character) | 6. Introduction date (1 character)   |
| 2. Manufacturer (2 characters)      | 7. V.I.N. check digit (1 character)  |
| 3. Motorcycle type (1 character)    | 8. Model year (1 character)          |
| 4. Model (2 characters)             | 9. Assembly plant (1 character)      |
| 5. Engine type (1 character)        | 10. Sequential number (6 characters) |

Figure 2. Typical Harley-Davidson Vehicle Identification Number: 2007 VRSC Models

Table 3. 2007 Harley-Davidson VRSC V.I.N. Breakdown

POSITION	DESCRIPTION	POSSIBLE VALUES
1	Market designation	1=Originally manufactured for sale <b>within</b> the United States 5=Originally manufactured for sale <b>outside</b> the United States
2	Manufacturer	HD=Harley-Davidson
3	Motorcycle type	1=Heavyweight motorcycle 901cc and larger

**Table 3. 2007 Harley-Davidson VRSC V.I.N. Breakdown**

POSITION	DESCRIPTION	POSSIBLE VALUES
4	Model	HC=VRSCR HD=VRSCD HF=VRSCA HH=VRSCDX HJ=VRSCX
5	Engine type	A=Revolution, 1130cc liquid-cooled, fuel injected 105 HP HDI only G=1250cc liquid-cooled, fuel injected Z=Revolution, 1130cc liquid-cooled, fuel injected
6	Introduction date	1=Regular 2=Mid-year 3=California/regular 4=Cosmetic changes and/or special introductory date 5=California/cosmetic changes and/or special introductory date 6=California/mid-year
7	V.I.N. check digit	Can be 0-9 or X
8	Model year	7=2007
9	Assembly plant	K=Kansas City, MO USA
10	Sequential number	varies

## **LABELS**

Refer to Table 4 for safety and maintenance labels which were on the vehicle when new. If removed, replacement labels may be purchased for your motorcycle.

**Table 4. Labels: VRSC Models**

<b>PART NO.</b>	<b>DESCRIPTION</b>	<b>LOCATION</b>
15348-01A	General warnings	Rear of airbox cover.
15368-01A	Battery warning	Right side of frame at rear of airbox cover (VRSCR), or under seat behind the fuel tank (all other VRSC models).
15369-01	Check oil level	On right side of frame behind fuel filler cap.
13694-07	Fuse block labels	Label with START RELAY and FAN RELAY is on fuse block located on top right of battery tray. Other half of label is on fuse block under passenger seat, behind fuel filler.



## SPECIFICATIONS: 2007 VRSC MODELS

**Table 5. Engine: 2007 VRSC Models (Except VRSCX)**

ITEM	SPECIFICATION	
Number of cylinders	2	
Type	4-cycle, DOHC, 60 degree V-Type, water cooled	
Compression ratio	11.3-1	
Bore	3.94 in.	100.00 mm
Stroke	2.84 in.	72.00 mm
Displacement	69 cu. in.	1130cc
Torque: VRSCA	74 ft-lbs @7000 RPM	100 Nm @7000 RPM
Torque: VRSCD, VRSCDX, VRSCR	80 ft-lbs @7000 RPM	109 Nm @7000 RPM

**Table 6. Engine: 2007 VRSCX Model**

ITEM	SPECIFICATION	
Number of cylinders	2	
Type	4-cycle, DOHC, 60 degree V-Twin, liquid cooled	
Compression ratio	11.5-1	
Bore	4.13 in.	105.00 mm
Stroke	2.84 in.	72.00 mm

**Table 6. Engine: 2007 VRSCX Model**

ITEM	SPECIFICATION	
Displacement	72 cu. in.	1250cc
Torque	86 ft-lbs @7000 RPM	116 Nm @7000 RPM

### NOTE

*Specifications in this publication may not match those of official certification in some markets due to timing of publication printing, variance in testing methods, and/or vehicle differences. Customers seeking officially recognized regulatory specifications for their vehicle should refer to certification documents and/or contact their respective dealer or distributor.*

**Table 7. Capacities: 2007 VRSC Models**

ITEM	U.S.	LITERS
Fuel tank	5.0 gal	18.9
Oil capacity with filter	5 qt.	4.3
Coolant capacity	2.5 qt.	2.4

**Table 8. Ignition System: 2007 VRSC Models**

ITEM	SPECIFICATION
Timing setting	Not adjustable
Battery	12 volt, 12 amp/hr (VRSCR) 12 volt, 19 amp/hr (all other models)
Spark plug type	10R12A

**Table 8. Ignition System: 2007 VRSC Models**

ITEM	SPECIFICATION	
Spark plug gap	0.035 in.	0.89 mm
Spark plug torque	17 ft-lbs	23 Nm

**Table 9. Drivetrain: 2007 VRSC Models**

COMPONENT	TYPE
Primary drive	gear
Final drive	belt
Rear sprocket	compensated
Clutch	hydraulic

**Table 10. Transmission: 2007 VRSC Models**

ITEM	SPECIFICATION
Type	foot shift
Speeds	5 forward
Gears	1st, 5th spur gears 2nd, 3rd, 4th helical gears

**Table 11. Sprocket Teeth: 2007 VRSC Models**

ITEM	DOMESTIC	INTERNATIONAL
Transmission	28	30
Rear wheel	72	72
Ratio	0.42	0.39

**Table 12. Gear Ratios: 2007 VRSC Models**

GEAR	DOMESTIC	INTERNATIONAL
1st gear	11.752	10.969
2nd gear	7.898	7.371
3rd gear	6.322	5.900
4th gear	5.459	5.095
5th gear	4.889	4.563

**Table 13. Weights: 2007 VRSC Models**

ITEM	VRSCA, VRSCD, VRSCX		VRSCDX		VRSCR	
	LB.	KG	LB.	KG	LB.	KG
Weight (as shipped from factory)	637	289	643	291.6	618	281
GVWR	1075	488	1075	488	1075	488
GAWR Front	377	171	377	171	377	171
GAWR Rear	698	317	698	317	698	317

**NOTE**  
Gross Vehicle Weight Rating GVWR (maximum allowable

loaded vehicle weight) and corresponding Gross Axle Weight Ratings (GAWR) are given on a label located on the left frame tube above the front engine cylinder.

**Table 14. Tire Sizes: 2007 VRSC Models**

MODEL	MOUNT	SIZE	NUMBER
VRSCA	Front	19 in.	D208F F120/70ZR19 60W
	Rear	18 in.	D419 240/40R18 79V
VRSCD	Front	19 in.	D208F F120/70ZR19 60W
	Rear	18 in.	D207 180/55ZR18 74W
VRSCR	Front	19 in.	D208F F120/70ZR19 60W
	Rear	18 in.	D207 180/55ZR18 74W
VRSCDX	Front	19 in.	D208F F120/70ZR19 60W
	Rear	18 in.	D419 240/40R18 79V
VRSCX	Front	19 in.	D208F F120/70ZR19 60W
	Rear	18 in.	D419 240/40R18 79V
All 2007 models use Dunlop radial tires only.			

**Table 15. Tire Pressures: 2007 VRSC Models**

MODEL	LOAD	TIRE PRESSURE (COLD)			
		FRONT		REAR	
		PSI	kPa	PSI	kPa
VRSCA	solo rider	36	248	38	262
	rider and passenger	36	248	42	290
VRSCD	solo rider	36	248	38	262
	rider and passenger	36	248	40	276

**Table 15. Tire Pressures: 2007 VRSC Models**

MODEL	LOAD	TIRE PRESSURE (COLD)			
		FRONT		REAR	
		PSI	kPa	PSI	kPa
VRSCR	solo rider	36	248	38	262
	rider and passenger	36	248	40	276
VRSCDX	solo rider	36	248	38	262
	rider and passenger	36	249	42	290
VRSCX	solo rider	36	248	38	262
	rider and passenger	36	249	42	290

**Table 16. Bulb Chart: 2007 VRSC Models**

LAMP	DESCRIPTION (ALL LAMPS 12 VOLT)	BULBS REQUIRED	CURRENT DRAW (AMPERAGE)	H-D PART NUMBER
Headlamp VRSCA/VRSCR/VRSCX	low beam	1	4.30	68881-01
	high beam	1	5.10	67717-01
Headlamp VRSCD/VRSCDX	low beam/high beam	1	4.58/5.00	68329-03
Position lamp international	position lamp	1	0.36	53436-97
Tail and stop lamp	tail lamp	1	0.59	68168-89A
	stop lamp	1	2.25	68168-89A
	license plate illumination	2	0.33	68193-95
	tail lamp international	1	0.42	68169-90A
	stop lamp international	1	1.75	68169-90A
	license plate illumination inter- national	2	0.37	53436-97



**Table 16. Bulb Chart: 2007 VRSC Models**

LAMP	DESCRIPTION (ALL LAMPS 12 VOLT)	BULBS REQUIRED	CURRENT DRAW (AMPERAGE)	H-D PART NUMBER
Turn signal lamp	front/running	2	2.25/0.59	68168-89
	rear	2	2.25	68572-64B
	front/running international	2	1.75	68163-84
	rear international	2	1.75	68163-84
Instrument panel	Speedometer, tachometer and odometer are illuminated with non-serviceable LED assemblies.			

**Table 17. Dimensions: 2007 VRSC Models**

ITEM	VRSCA		VRSCD		VRSCR		VRSCX		VRSCDX	
	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm
Wheelbase	67.2	1706	67.2	1706	66.8	1697.0	67.2	1706.0	67.2	1706
Overall length	94.4	2398.0	94.4	2398.0	93.7	2380.0	94.4	2398.0	94.4	2398.0
Overall width	34.5	876.0	37.3	947.0	32.4	823.0	32.3	820.0	34.6	879.0
Overall height	47.7	1212.0	45.0	1143.0	48.7	1237.0	44.5	1130.0	45.5	1156.0
Road clearance	5.0	127.0	5.0	127.0	6.7	170.0	5.0	127.0	4.2	107.0
Saddle height	26.0	660.4	26.0	660.4	30.0	762.0	26.0	660.4	25.2	640.0

## TIRE DATA: VRSC MODELS

### ⚠ WARNING

Match tires, tubes, rim strips or seals, air valves and caps to the correct wheel. Contact a Harley-Davidson dealer. Mismatching can lead to tire damage, allow tire slippage on the wheel or cause tire failure, which could result in death or serious injury. (00023c)

### ⚠ WARNING

Harley-Davidson recommends the use of its specified tires. Harley-Davidson vehicles are not designed for operation with non-specified tires, including snow, moped and other special-use tires. Use of non-specified tires can adversely affect stability, handling or braking and lead to loss of vehicle control, which could result in death or serious injury. (00024d)

Tubeless tires are used on all Harley-Davidson cast and disc wheels.

Tire sizes are molded on the tire sidewall. Inner tube sizes are printed on the tube.

#### **⚠ WARNING**

**Harley-Davidson front and rear tires are not the same. Interchanging front and rear tires can cause tire failure, which could result in death or serious injury. (00026a)**

#### **⚠ WARNING**

**Do not inflate tire beyond maximum pressure as specified on sidewall. Over inflated tires can blow out, which could result in death or serious injury. (00027b)**

#### **⚠ WARNING**

**Replace tire immediately with a Harley-Davidson specified tire when wear bars become visible or only 1 mm (1/32 in) tread depth remains. Riding with a worn tire could result in death or serious injury. (00090c)**

See SPECIFICATIONS > SPECIFICATIONS: 2007 VRSC MODELS (Page 19) for tire pressures and sizes.

## **CATALYTIC CONVERTERS: VRSC MODELS**

All international (HDI) motorcycles are equipped with catalytic converters. Domestic and destination Japan motorcycles are not equipped with catalytic converters.

#### **NOTICE**

**Do not operate catalytic converter-equipped vehicle with engine misfire. If you operate the vehicle under this condition, the exhaust will become abnormally hot, which can cause vehicle damage, including emission control loss. (00149c)**

## **GASOLINE BLENDS**

Your motorcycle was designed to get the best performance and efficiency using unleaded gasoline. Most gasoline is blended with alcohol and/or ether to create oxygenated blends. The type and amount of alcohol or ether added to the fuel is important.

#### **NOTICE**

**Do not use gasoline that contains methanol. Doing so can result in fuel system component failure, engine damage and/or equipment malfunction. (00148a)**

- Gasoline containing METHYL TERTIARY BUTYL ETHER (MTBE): Gasoline/MTBE blends are a mixture of gasoline and as much as 15% MTBE. Gasoline/MTBE blends can be used in your motorcycle.
- ETHANOL is a mixture of 10% ethanol (Grain alcohol) and 90% unleaded gasoline. Gasoline/ethanol blends can be used in your motorcycle if the ethanol content does **not** exceed 10%.
- REFORMULATED OR OXYGENATED GASOLINES (RFG): Reformulated gasoline is a term used to describe gasoline blends that are specifically designed to burn cleaner than other types of gasoline, leaving fewer tailpipe emissions. They are also formulated to evaporate less when you are filling your tank. Reformulated gasolines use additives to oxygenate the gas. Your motorcycle will run normally using this type of gas and Harley-Davidson recommends you use it when possible, as an aid to cleaner air in our environment.

You may find that some gasoline blends adversely affect the starting, driveability or fuel efficiency of your motorcycle. If you experience one or more of these problems, it is recommended you operate your motorcycle on straight unleaded gasoline.

## FUEL

Refer to Table 18. Always use a good quality unleaded gasoline. Octane ratings are usually found on the pump.

### ⚠ WARNING

**Avoid spills. Slowly open fuel filler cap. Do not fill above bottom of filler neck insert, leaving air space for fuel expansion. Secure filler cap after refueling. Gasoline is extremely flammable and highly explosive, which could result in death or serious injury. (00028b)**

### ⚠ WARNING

**Use care when refueling. Pressurized air in fuel tank can force gasoline to escape through filler tube. Gasoline is extremely flammable and highly explosive, which could result in death or serious injury. (00029a)**

Modern service station pumps dispense a high flow of gasoline into a motorcycle fuel tank making air entrapment and pressurization a possibility.

**Table 18. Octane Ratings**

SPECIFICATION	RATING
Pump Octane (R+M)/2	91 (95 RON)

## NOTES

---



## GENERAL: CONTROLS AND INDICATORS

### ⚠ WARNING

Identify and understand the specific features of your vehicle. Failure to understand how these features affect the vehicle's operation can lead to an accident, which could result in death or serious injury. (00043b)

Some features explained are unique to certain models. These features may be available as accessories for your Harley-Davidson motorcycle. See a Harley-Davidson dealer for a complete list of accessories that will fit your specific motorcycle.

## IGNITION SWITCH: VRSC MODELS

### ⚠ WARNING

The automatic-on headlamp feature provides increased visibility of the rider to other motorists. Be sure headlamp is on at all times. Poor visibility of rider to other motorists can result in death or serious injury. (00030b)

See the YOUR OWNER'S MANUAL section at the beginning of this manual. Be sure to record all your key numbers in the space provided at the front of this book.

The ignition switch controls electrical functions of the motorcycle.

### NOTICE

Protect your vehicle against theft. After parking your motorcycle, lock the steering head and ignition switch. Failure to lock your motorcycle can result in theft and/or equipment damage. (00491c)

### ⚠ WARNING

Do not operate vehicle with forks locked. Locking the forks restricts the vehicle's turning ability, which could result in death or serious injury. (00035a)

### NOTICE

Do not lubricate barrel locks with petroleum based lubricants or graphite. Inoperative locks may result. (00152a)

### NOTICE

Turn the ignition switch to the OFF position before locking the motorcycle. Leaving the switch in the ACC position will keep the instrument lights on and result in a discharged battery. (00492b)

To review the functions of each switch position, refer to Table 19.

1. See Figure 3. To remove the key from the ignition, turn it to the OFF position.
  2. To remove the key from ignition, pull the key outward.
  3. Always turn switch to LOCK position and remove key after operation and when leaving bike parked.
- *The lamps operate when the switch is in the IGN position, as required by law in some localities.*
  - *Harley-Davidson recommends removing key from ignition/fork lock before operating motorcycle. If you do not remove key, it can fall out during operation.*
  - *The ignition key also fits the front fork lock.*

**NOTE**

- *ACC-Accessories and hazard warning flasher can be turned on. Instrument lamps are on. Brake lamp and horn can be activated. Key may be removed.*

**Table 19. Ignition Switch: 2007 VRSC Models**

<b>SWITCH POSITION</b>	<b>REMOVE KEY</b>	<b>FUNCTIONS</b>
OFF	Yes	Turns off ignition, lamps and accessories (disconnects battery voltage from IGN and ACC terminals).
ACC	Yes	Turns on accessories. Hazard warning flashers can be operated. Instrument lamps are on. Brake lamp and horn can be activated (connects battery voltage to ACC terminal). NOTE: When switching to the ACC position, a startup diagnostic performs a systems check. The instrument background lighting illuminates, gauge needles sweep their full range of motion and the battery, security, coolant temperature and check engine indicator lamps illuminate.
IGN	Yes	Turns on ignition, lamps and accessories.




Figure 3. Ignition Switch: VRSC Models

## HAND CONTROLS: BASIC OPERATION

### Electric Starter Switch

#### NOTE

Off/Run switch **MUST** be in RUN position to operate engine.

See Figure 4. The electric starter switch is located on the right handlebar control group. See OPERATION > STARTING THE ENGINE (Page 68) for detailed operation procedures.

1. Put the engine off/run switch in the RUN position and the transmission in neutral. Neutral (green) indicator lamp should be illuminated.
2. See Figure 3. Turn ignition/headlamp key switch to IGNITION and push the START switch to operate starter motor.

### Engine OFF/RUN Switch

See Figure 4. The engine off/run switch (7) turns the ignition power ON or OFF. The engine off/run switch is located on the right handlebar control. Push the top portion of the engine off/run switch to turn off ignition power and shut the engine off. Push the bottom portion of the engine off/run switch to turn on ignition power.

#### NOTE

- The engine off/run switch must be in the RUN position to start or operate the engine.
  - The engine off/run switch should be used to shut the engine off.
1. To shut the engine off, push the top of the off/run switch to the ignition OFF position.

2. See Figure 3. Turn the ignition key to the OFF position to turn the ignition power completely OFF.

## Throttle Control Grip

See Figure 4. The throttle control grip (9) is located on the right handlebar control and is operated with the right hand.

To reduce rider fatigue on long trips, a spring loaded throttle friction adjustment screw (10) is located at the bottom of the throttle grip clamp on non-cruise equipped models.

1. Slowly turn throttle control grip clockwise (toward the front of the bike) to close the throttle (decelerate).
2. Slowly turn throttle control grip counterclockwise (toward rear of bike) to open the throttle (accelerate).

### ⚠ WARNING

**Do not tighten throttle friction adjustment screw to the point where the engine will not return to idle automatically. Over-tightening can lead to loss of vehicle control, which could result in death or serious injury. (00031b)**

3. Unscrew the throttle friction adjustment screw so the throttle returns to the idle position when the hand is removed from the grip.

4. Screw the throttle adjustment screw in to increase friction on grip. This provides a damping effect on throttle motion.

### NOTE

*The throttle friction adjustment screw should not be used under normal stop and go operating conditions.*

## Clutch Hand Lever

### ⚠ WARNING

**Do not position fingers between hand control lever and handlebar grip. Improper hand positioning can impair control lever operation and cause loss of vehicle control, which could result in death or serious injury. (00032a)**

See Figure 4. The clutch hand lever (1) is located on the left handlebar and is operated with the fingers of the left hand.

1. Slowly pull clutch hand lever in against handlebar grip to fully disengage clutch.
2. Shift to first gear using the gear shifter lever. See OPERATION > SHIFTING GEARS (Page 70).
3. Slowly release the clutch hand lever to engage clutch.

A clutch switch is incorporated into the left handlebar switch assembly. It enables the rider to start the vehicle in any gear



(or in neutral) as long as the clutch lever is pulled in. If the clutch is not disengaged, the vehicle will not start.

## Horn Switch

See Figure 4. The horn is operated by pushing on the horn switch (2) located on the left handlebar control group.

## Headlamp Dimmer Switch

See Figure 4. The headlamp dimmer switch (3) is located on the left handlebar. The switch has two positions to activate the headlamps high or low beams.

- Press the top of the headlamp dimmer beam switch to activate the high beam.
- Press the bottom of the headlamp dimmer switch to return to the low beam.

See Figure 5. The (blue) high beam indicator lamp will illuminate when the high beam is on.


## Turn Signal Switches


See Figure 4. Each handlebar control group contains a turn signal switch.

- The right turn signal switch (11) operates the right front and right rear flashing lamps.
- The left turn signal switch (4) operates the left front and left rear flashing lamps.

### NOTE

*Front turn signal lamps also function as running lamps (except International models).*





1. Clutch hand lever
2. Horn switch
3. Headlamp dimmer switch
4. Left turn signal switch
5. Front brake master cylinder reservoir
6. Electric starter switch

7. Engine off/run switch
8. Brake hand lever
9. Throttle control grip
10. Throttle friction adjusting screw
11. Right turn signal switch
12. Clutch master cylinder reservoir

**Figure 4. Handlebar Controls: VRSC Models**

## TURN SIGNAL SWITCH OPERATION

The turn signal switches are used by the turn signal module to control turn signal operation based on vehicle speed, vehicle acceleration and turn completion.

Momentarily depress the desired turn signal switch. The turn signal lamps will begin and continue flashing until they are manually or automatically cancelled. As long as the motorcycle is stationary, the signals will flash.

### NOTE

- *If you are signaling to turn in one direction and you depress the switch for the opposite turn signal, the first signal is cancelled and the opposite side begins flashing.*
- *If you want to stop the lamps from flashing, briefly depress the turn signal switch a second time. The turn signal lamps will stop flashing.*

## HAZARD WARNING 4-WAY FLASHER

Use the following method to activate the four-way flashers.

1. With the ignition key ON and security system disarmed (models with security only), press the left and right turn signal switches at the same time.
2. Turn the ignition key OFF and arm the security system if present and desired. The four-way flashers will continue for two hours.
3. To cancel four-way flashing, disarm the security system if necessary, turn the ignition key ON and press the left and right turn signal switches at the same time.

This system allows a stranded vehicle to be left in the four-way flashing mode and secured until help is found.

## INDICATOR LAMPS: VRSC MODELS

See Figure 5. Ten indicator lamps are provided.

- The two green TURN indicator lamps flash when turn signals are activated; therefore, flashing indicates the chosen turn direction. When the 4-way hazard flashers are operating, both turn indicators flash simultaneously.
- The blue HIGH BEAM indicator lamp, when lit, signals high beam headlamp operation.
- The green NEUTRAL lamp, when lit, signals the transmission is in neutral gear.
- The red OIL PRESSURE indicator lamp, when lit, signals that oil is not circulating through the engine.
- The red ENGINE COOLANT TEMPERATURE indicator lamp, when lit, signals the coolant temperature has exceeded 243° F (117° C).
- The red ENGINE DIAGNOSTIC indicator lamp, when lit, signals that the vehicle's computer has detected an engine malfunction.
- The red ALTERNATOR indicator lamp, when lit, signals there is a malfunction in the charging circuit and the battery is not being properly charged.
- The red SECURITY STATUS indicator lamp indicates the status of the vehicle's security system. It is normal for this to light with or without a security system.
- The yellow LOW FUEL indicator lamp, when lit, signals the fuel tank is almost empty.

#### NOTE

- The OIL PRESSURE indicator lamp will glow when the ignition is turned on prior to starting the engine. With the engine running, the lamp should be off when engine speed is above idle.
- To learn more about the SECURITY STATUS indicator lamp, see the H-D Factory Security Section later in this manual.

Several other circumstances that could cause the red oil pressure indicator lamp to illuminate include:

- An insufficient or diluted oil supply causing the oil pressure indicator lamp to remain lit at speeds above idling.
- An oil feed clogged with ice and sludge in freezing weather, preventing oil circulation.
- A grounded oil signal switch wire.
- A faulty oil signal switch.
- A damaged or improperly installed check valve.
- Trouble with the oil pump.

#### NOTICE

**If the oil pressure indicator lamp remains lit, always check the oil supply first. If the oil supply is normal and the lamp is still lit, stop the engine at once and do not ride further until the trouble is located and the necessary repairs are made. Failure to do so may result in engine damage. (00157a)**

Several other circumstances that could cause the red engine coolant temperature indicator lamp to illuminate include:

- Cooling fan malfunction.
- Low coolant level.
- Thermostat malfunction.
- Temperature gauge malfunction.
- Blocked coolant passages.
- Radiator cap malfunction.
- Coolant malfunction.


#### NOTICE

If the engine coolant temperature indicator lamp remains lit, always check the coolant level. If the coolant level is normal and the lamp is still lit, stop the engine at once and do not ride further until the trouble is located and the necessary repairs are made. Failure to do so may result in engine damage. (00158a)

#### ⚠ WARNING

Do not loosen or remove pressure cap when cooling system is hot. The cooling system is under pressure and hot coolant and steam can escape from pressure cap, which could cause severe burns. Allow motorcycle to cool before servicing the cooling system. (00091c)





- 1. Left turn
- 2. High beam
- 3. Neutral
- 4. Oil
- 5. Engine coolant

- 6. Right turn
- 7. Low fuel
- 8. Security system
- 9. Alternator
- 10. Engine diagnostic

Figure 5. Indicator Lamps: VRSC Models

## INSTRUMENTS: VRSC MODELS

### Speedometer

#### ⚠ WARNING

**Travel at speeds appropriate for road and conditions and never travel faster than posted speed limit. Excessive speed can cause loss of vehicle control, which could result in death or serious injury. (00008a)**

See Figure 6. The speedometer registers miles per hour (U.S. models) or kilometers per hour (international models) of forward speed. The speedometer also provides the following selectable functions:

- Odometer
- Trip odometers A and B
- 12 or 24 hour clock
- Fuel range

#### NOTICE

**Never attempt to tamper with or alter the vehicle odometer. This is illegal. Tampering with or altering a vehicle odometer may cause equipment damage. (00160a)**

The speedometer has a single display window for the above functions.

1. See Figure 6. Pressing the function switch with the ignition switch in any position will activate the odometer reading and time. Time and mileage or kilometers may be checked without unlocking ignition switch. Press and release function switch once to view odometer. Press and release switch again to display time.
2. To check mileage on trip odometers, the ignition switch must be in the ACC or IGNITION position. Press and release the function switch until the desired trip odometer reading is displayed. An 'A' or 'B' in the upper left of the display window identifies trip odometers.
3. To reset or zero trip odometers, have desired odometer (A or B) in display window. Press function switch and hold switch for 2-3 seconds. The trip odometer will be reset to zero.
4. Repeat the previous step if you wish to zero both trip odometers.

### Setting Clock

1. Turn the ignition switch to ACC or IGNITION.

2. See Figure 6. Press function switch until time (hour and minutes) is displayed. Press and hold the function switch for five seconds or until 12HR begins to blink in the speedometer display window. Release the button.
3. Press and release the function switch once to advance to a blinking 24HR military style time display. Each time you press and release the button, the display will switch between 12HR and 24HR.
4. When the desired time style is displayed, press and hold the function switch for five seconds. The display will switch to the time display with the hours blinking.
5. Press and release the function switch repeatedly to advance the hours. Each time you press and release the switch, the display will advance one hour.

#### NOTE

*No AM or PM time setting is required. When correct hour is reached, press and hold function switch to advance to minute setting.*

6. When the correct hour is displayed, press and hold the function switch for five seconds. The minutes display will start blinking.
7. Press and release the function switch repeatedly to advance the minutes display. Each time you press and release the button, the display will advance one minute.

8. When the correct minutes are displayed, press and hold the function switch for five seconds. The minutes display will stop blinking, indicating that the clock has been set.
9. Turn the ignition switch OFF.

## Fuel Range Function

The fuel range function shows the approximate mileage available with the amount of fuel currently in the fuel tank.

1. With the ignition switch in the ACC or IGNITION position, press function switch until fuel range function is displayed, as indicated by the letter 'r' in the left side of the display. The calculated remaining distance (miles or kilometers) before empty is displayed, based on the amount of fuel in tank.
2. When low fuel lamp lights, the fuel range function displays "r lo" and no miles (kilometers) are shown in the fuel range display.

#### NOTE

*When low fuel lamp lights, there is approximately 1.0 gallon (3.8 liters) of fuel remaining in tank. Refuel as soon as possible.*



3. After low fuel lamp lights, the speedometer displays the trip odometer (A or B) and automatically resets the trip odometer to zero. The trip odometer will display the distance traveled since the low fuel lamp lit.

## Tachometer

See Figure 6. The tachometer registers the engine speed in revolutions per minute (RPM).

### NOTICE


**See OPERATING RECOMMENDATIONS section. Do not operate the engine above maximum safe RPM as shown under OPERATION (red zone on tachometer). Lower the RPM by upshifting to a higher gear or reducing the amount of throttle. Failure to lower RPM may cause equipment damage. (00159a)**

## Tip Indicator Lamp

### ▲ WARNING

**If tip occurs, check all controls for proper operation. Restricted control movement can adversely affect the performance of the brakes, clutch or ability to shift, which could result in loss of vehicle control and death or serious injury. (00350a)**

Should motorcycle be tipped over, the word "tip" will appear in the odometer window. Engine will not start until reset. To reset, cycle ignition/headlamp key switch ON-OFF-ON.






Figure 6. Instrument Cluster: VRSC Models

## SEQUENTIAL PORT FUEL INJECTION

### Check Engine Lamp


See Figure 7. The engine check lamp is located inside the instrument cluster. Its purpose is to indicate whether or not the engine/engine management system is operating normally. The engine lamp color is red.

The engine lamp normally comes on when the bike's ignition is first turned on and remains on for approximately 4 seconds, as the engine management system runs a series of self-diagnostics.

If the engine lamp comes on at any other time, see a Harley-Davidson dealer.

### Low Fuel Lamp

See Figure 7. There is a low fuel warning lamp within the instrument cluster. The low fuel lamp lights up to indicate that there is approximately 1 gallon (3.8 liters) of gasoline left in the tank. The low fuel lamp color is amber.



**Figure 7. Check Engine and Low Fuel Lamp: VRSC Models**  
**GEAR SHIFT LEVER**

#### NOTICE

The clutch must be fully disengaged before attempting a gear shift. Failure to fully disengage the clutch can result in equipment damage. (00182a)

See Figure 8. The gear shift lever is located on the left side of the motorcycle and is operated with the left foot. The transmission is a five speed sequential gear box.

1. Push the gear shift lever all the way down (full stroke) to shift the transmission to the next lower gear.
2. Lift the gear shift lever all the way up (full stroke) to shift the transmission to the next higher gear.

**NOTE**

- *Release the gear shift lever after each gear change.*
- *The lever must return to its central position before another gear change can be made.*

First gear is the last gear position that can be found by pushing the gear shift lever full stroke downward.

Neutral is located between first and second gear. The green neutral indicator lamp on the dash will illuminate when the transmission is in neutral.

To shift from first gear to neutral, lift the gear shift lever 1/2 of its full stroke.

When the motorcycle is standing still and the engine is not running, shifting gears requires a different technique. Before shifting in this condition, move the motorcycle backward and forward with the clutch fully disengaged (clutch lever pulled

in). While maintaining slight pressure on the shift lever, shift from one gear to another.

Even with the engine running and the motorcycle standing still, difficulty may be experienced in shifting gears. This difficulty occurs because transmission gears are not turning and shifting parts are not lined up to permit engagement.

**NOTICE**

**When difficulty of shifting gears is experienced, do not under any circumstances, attempt to force the shift. The results of such abuse will be a damaged or broken shifter mechanism. (00161a)**

See OPERATION > SHIFTING GEARS (Page 70) for more information.




Figure 8. Gear Shift Lever (Downshift): VRSC Models

## BRAKE SYSTEM

### ⚠ WARNING

**Do not apply brake strongly enough to lock the wheel. A locked wheel will skid and can cause loss of vehicle control, which could result in death or serious injury. (00053a)**

The rear brake pedal controls the rear wheel brake and is located on the motorcycle's right side. Operate the rear brake pedal with the right foot.

The front brake hand lever controls the front wheel brake and is located on the right handlebar. Operate the hand lever with the fingers of the right hand.

### ⚠ WARNING

**Do not position fingers between hand control lever and handlebar grip. Improper hand positioning can impair control lever operation and cause loss of vehicle control, which could result in death or serious injury. (00032a)**

Brakes should be applied uniformly and evenly to prevent wheels from locking up. A balance between rear and front braking is generally best.

## JIFFY STAND

### ⚠ WARNING

Always park motorcycle on a level, firm surface. An unbalanced motorcycle can fall over, which could result in death or serious injury. (00039a)

The jiffy stand is located on the left side of the motorcycle and swings outward to support the motorcycle for parking.

### ⚠ WARNING

The jiffy stand locks when placed in the full forward (down) position with vehicle weight on it. If the jiffy stand is not in the full forward (down) position with vehicle weight on it, the vehicle can fall over which could result in death or serious injury. (00006a)

### ⚠ WARNING

Be sure jiffy stand is fully retracted before riding. If jiffy stand is not fully retracted, it can contact the road surface causing a loss of vehicle control, which could result in death or serious injury. (00007a)

## REAR VIEW MIRRORS

### ⚠ WARNING

Objects in mirrors are closer than they appear. Use caution when judging distance of objects in mirrors. Failure to judge correct distances could result in death or serious injury. (00033a)

Your vehicle is equipped with two convex rear view mirrors.

This type of mirror is designed to give a much wider view to the rear than a flat mirror. However, cars and other objects seen in this type of mirror will look smaller and farther away than they actually are.

- Use caution when judging the size or relative distance of objects seen in rear view mirrors.
- Always adjust the rear view mirrors to clearly reflect the area behind the motorcycle before riding.

### NOTE

*Adjust mirrors so you can see a small portion of your shoulders in each mirror. This will help you establish the relative distance of vehicles to the rear of your motorcycle.*

## FUEL FILLER CAP: VRSC MODELS

See Figure 9. The fuel filler cap is located under the seat.

To open, turn the fuel filler cap counterclockwise and lift up. To close, turn the fuel filler cap clockwise until it clicks. The ratchet action of the cap prevents overtightening.

**NOTE**

*The fuel filler cap turns approximately 3/4 turn before it begins unscrewing.*

See SAFE OPERATING RULES section and review safety procedures.

**NOTICE**

**Do not spill fuel onto the motorcycle while refueling. Immediately wipe up fuel spills on your motorcycle. Fuel can cause damage to cosmetic surfaces. (00147b)**

**NOTICE**


**Use only unleaded fuel in catalytic converter-equipped motorcycles. Using leaded fuel will damage the emission control system. (00150c)**

**⚠ WARNING**

**Do not store motorcycle with gasoline in tank within the home or garage where open flames, pilot lights, sparks or electric motors are present. Gasoline is extremely flammable and highly explosive, which could result in death or serious injury. (00003a)**

**⚠ WARNING**

**Avoid spills. Slowly open fuel filler cap. Do not fill above bottom of filler neck insert, leaving air space for fuel expansion. Secure filler cap after refueling. Gasoline is extremely flammable and highly explosive, which could result in death or serious injury. (00028b)**



**Figure 9. Fuel Filler Cap: VRSC Models**

## FORK LOCK: VRSC MODELS

### NOTICE

**Protect your vehicle against theft. After parking your motorcycle, lock the steering head and ignition switch. Failure to lock your motorcycle can result in theft and/or equipment damage. (00491c)**

See Figure 10. VRSC models have the fork lock incorporated in the steering head on the right hand side.

### ⚠ WARNING

**Do not operate vehicle with forks locked. Locking the forks restricts the vehicle's turning ability, which could result in death or serious injury. (00035a)**

Using the fork lock immediately after parking your motorcycle will discourage unauthorized use or theft when parking your motorcycle.

1. Turn the fork to the full left position.
2. Insert the ignition key into the fork lock.
3. Push down on the fork lock switch and turn to the full clockwise position.
4. Remove the ignition key.



**Figure 10. Fork Lock: VRSC Models**

## REAR SHOCK ABSORBERS: VRSC MODELS

### General

See Figure 11. The rear shock absorber spring preload can be adjusted for the weight the motorcycle is to carry and has



five preload graduations. Notice the adjustment settings as you turn the collar.

## Adjustment

### ⚠ WARNING

**Adjust both shock absorbers equally. Improper adjustment can adversely affect stability and handling, which could result in death or serious injury. (00036b)**

The average weight solo rider might use the extended spring preload position (adjustment setting 1 or 2).

1. Place the shock absorber adjustment tool around the lower collar of the shock absorber.
2. Turn the collar clockwise (toward higher numbers) to increase the preload or pressure.

Use the adjustment setting numbers as a reference for equal adjustment of shock absorbers on both the right and left side of the motorcycle. A heavy solo rider might require additional preload or pressure (adjustment setting 3).

### NOTICE

**Do not turn the shock absorber adjustment collar clockwise beyond adjustment setting 5. Doing so may result in equipment damage. (00166b)**


Adding a passenger may require maximum preload (adjustment setting 5).

Turn the collar counterclockwise to decrease the preload or pressure.

See Figure 11. To adjust the rear shock absorber spring preload, turn the spring adjusting cam to the desired position with a spanner wrench. When returning to off-cam position, cams should be backed off in opposite direction. A SPANNER WRENCH (PART NUMBER: 94700-52C) is available from your Harley-Davidson dealer.



**Figure 11. Adjusting Rear Shock: VRSC Models**



**Figure 12. Spanner Wrench**

## HARLEY-DAVIDSON SMART SECURITY SYSTEM

### Components

See Figure 13. The Harley-Davidson Smart Security System (H-DSSS) consists of a Hands-Free Security Module (HFSM) (1) and a Hands-Free Antenna (2) mounted on the motorcycle, and a Hands-Free Fob **carried** by the rider/passenger.

After parking the motorcycle, turn the ignition key to OFF and the Smart Security System will automatically **arm** within five seconds. While armed, the starter and ignition are disabled and the rider may leave the motorcycle knowing that the module will activate an alarm if someone tampers with the ignition or attempts to move the motorcycle.

If the fob is present, the module will automatically **disarm** when the ignition key is turned to IGNITION or ACCESS.

#### NOTE

*Do not relocate the module or the antenna on the motorcycle.*

### Options

Several options are available for the Harley-Davidson Smart Security System from the Harley-Davidson Genuine Motor Accessories and Motor Parts catalog. Options include:

- Smart Siren and Smart Siren II.
- Security Pager and Security Pager Receiver II.
- Replacement Fobs.

See a Harley-Davidson dealer for details.




Figure 13. Security Module w/Antenna

## FCC REGULATIONS

FCC ID: L2C0027TR IC ID: 3432A-0027TR

FCC ID: L2C0028TR IC ID: 3432A-0028TR

This device complies with Part 15 of the FCC Rules and with RSS-210 of Industry Canada rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

**WARNING:** Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

The term "IC:" before the radio certification number only signifies that Industry Canada technical specifications were met.

## HANDS-FREE FOB

### Fob Assignment


See Figure 14. Hands-Free Fobs are electronically assigned to the Harley-Davidson Smart Security System by a Harley-Davidson dealer so that the module can recognize a fob's unique signal. Only two fobs can be assigned to the module at any one time.

Replacement fobs can be purchased from a dealership but can only be assigned to the motorcycle by a trained Harley-Davidson technician.

#### NOTE

- The reusable label found on the fob packaging lists the serial number of the fob. For reference, fix the label to a blank "NOTES" page in the Owner's Manual.
- The serial number of the fob is also found on the inside of the fob. See HARLEY-DAVIDSON SMART SECURITY SYSTEM > FOB BATTERY (Page 61).
- The module will arm only if the fob has been assigned by a Harley-Davidson dealer and a Personal Identification Number (PIN) has been entered in the system. The PIN should be recorded on the Personal Information page in the front of this Owner's Manual and on the removable wallet card.
- Should the rider misplace the fob or if the fob fails, the rider can refer to the wallet card and use the PIN to manually disarm the system. Refer to HARLEY-DAVIDSON SMART SECURITY SYSTEM > ARMING AND DISARMING (Page 55) and HARLEY-DAVIDSON SMART SECURITY SYSTEM > TROUBLESHOOTING (Page 62).
- The PIN can easily be changed by the rider at any time. Refer to HARLEY-DAVIDSON SMART SECURITY SYSTEM > PERSONAL IDENTIFICATION NUMBER (PIN) (Page 52).

299447



**Figure 14. Hands-Free Fob: Smart Security System**

#### Riding with a Fob

- Always carry the fob when riding, loading, fueling, moving, parking or servicing the motorcycle. Carry the fob in a convenient pocket.

- Do not leave the fob attached to the handlebars or store the fob in a saddlebag or Tour-Pak®. Unintentionally leaving the fob with the motorcycle when it's parked prevents the system from activating the alarm.
- Do not ride with the fob stored in a metal case or with the fob closer than 3.0 in. (76 mm) to a cell phone, PDA, display or other electronic device. Any electromagnetic interference may prevent the fob from disarming the system.
- For added security, always lock the fork and remove the ignition key when parked. If the fob is within range and the motorcycle is unlocked, tampering with the motorcycle will not activate the alarm.

## PERSONAL IDENTIFICATION NUMBER (PIN)

The Personal Identification Number (PIN) is a number that can be used to disarm the Harley-Davidson Smart Security System in case an assigned fob is misplaced, fails or if the fob and module cannot communicate because of electromagnetic interference.

A PIN is a five-digit number (1-9, no zeros).

## Changing the PIN

To maintain security, the rider can change the PIN at any time. Refer to Table 20.

Table 20. Changing the PIN

STEP NO.	ACTION	WAIT FOR CONFIRMATION	NOTES
1	Select a 5-digit (1 thru 9) PIN and record on the wallet card from Owner's Manual.		
2	With an assigned fob present, turn <b>IGN</b> key <b>IGNITION-OFF-IGNITION-OFF-IGNITION</b> .		
3	Press <b>left</b> turn signal switch <b>3 times</b> .		
4	Press <b>right</b> turn signal switch <b>1 time</b> and release.	Turn signals will flash 3 times. Current PIN will appear in odometer. The first digit will be flashing.	See figure showing the odometer window with PIN display.

**Table 20. Changing the PIN**

<b>STEP NO.</b>	<b>ACTION</b>	<b>WAIT FOR CONFIRMATION</b>	<b>NOTES</b>
5	Enter first digit (a) of new PIN by pressing <b>left</b> turn signal switch <b>a</b> times.		
6	Press <b>right</b> turn signal switch <b>1 time</b> and release.	The new digit (a) will replace the current in odometer window.	
7	Enter second digit (b) of new PIN by pressing <b>left</b> turn signal switch <b>b</b> times.		
8	Press <b>right</b> turn signal switch <b>1 time</b> and release.	The new digit (b) will replace the current in odometer window.	
9	Enter third digit (c) of new PIN by pressing <b>left</b> turn signal switch <b>c</b> times.		
10	Press <b>right</b> turn switch <b>1 time</b> and release.	The new digit (c) will replace the current in odometer window.	
11	Enter fourth digit (d) of new PIN by pressing <b>left</b> turn signal switch <b>d</b> times.		
12	Press <b>right</b> turn switch <b>1 time</b> and release.	The new digit (d) will replace the current in odometer window.	
13	Enter fifth digit (e) of new PIN by pressing <b>left</b> turn signal switch <b>e</b> times.		

Table 20. Changing the PIN

STEP NO.	ACTION	WAIT FOR CONFIRMATION	NOTES
14	Press <b>right</b> turn switch <b>1 time</b> and release.	The new digit (e) will replace the current in odometer window.	
15	Before the module rearms, turn the ignition key to <b>OFF</b> .	The odometer will return to mileage.	Turning the ignition key to <b>OFF</b> stores the new PIN in the module.




Figure 15. Odometer Windows - PIN

## SECURITY STATUS INDICATOR

See Figure 16. The illuminated key icon in the speedometer face indicates the status of the Harley-Davidson Smart Security System.

- **Armed:** A key icon that blinks approximately every 3 seconds indicates that the system is armed.
- **Disarmed:** After the ignition/headlamp switch is turned to IGNITION and the system disarms, the key icon will remain illuminated for approximately four seconds and then turn off.
- **Service:** A key icon that remains illuminated longer than four seconds indicates that service of the module is required.






Figure 16. Security Status Indicator

## ARMING AND DISARMING

### Arming

When the motorcycle is parked and the ignition key is turned to OFF, the Harley-Davidson Smart Security System arms automatically within five seconds if no motion is detected. Even when the fob is present, the system will arm.

On arming, the turn signals will flash twice and the optional siren will chirp twice. While armed, the key icon in the speedometer face will flash every three seconds.

#### NOTE

**International Models:** The HFSM must be in the Chirp Mode for the siren to chirp on arming or on disarming. See HARLEY-DAVIDSON SMART SECURITY SYSTEM > SIREN CHIRPLESS/CHIRP MODES: INTERNATIONAL MODELS (Page 59).

### Disarming

Once disarmed, the rider may ride or move the motorcycle for parking, storage or service without setting off the alarm.

**Fob:** An armed Smart Security System is automatically disarmed when the ignition key is turned to IGNITION with the fob present.

When the module disarms, the optional siren will chirp once and the key icon will illuminate for a solid four seconds and then turn off.

#### NOTE

*Any motion, like lifting the motorcycle up off of its jiffy stand, or turning the ignition key to IGNITION and the module will electronically "poll" for the presence of the fob. If the fob is present, the system disarms.*

**Personal Identification Number (PIN):** If the fob is misplaced or if the present fob fails to communicate with the module, the system can be disarmed with the Personal Identification Number (PIN).

## Disarming with a PIN

Do not turn handlebars, straddle seat or lift motorcycle off the jiffy stand. During a PIN disarm, if the Smart Security System detects motorcycle motion the system will activate the alarm.

**Table 21. Entering a PIN to Disarm Harley-Davidson Smart Security System**

STEP NO.	ACTION	WAIT FOR CONFIRMATION	NOTES
1	If necessary, verify the current 5-digit PIN.		Should be recorded on wallet card.
2	Turn ignition key to <b>IGNITION</b> .		
3	Quickly (within 2 seconds of turning ignition key) hold <b>both</b> turn signal switches in until confirmation.	Key icon flashes at fast rate. In the odometer window, a flashing dash will be followed by four more dashes.	See figure showing the odometer window with PIN display. Five dashes will appear in the odometer window.
4	Enter first digit ( <b>a</b> ) in the PIN by pressing <b>left</b> turn switch <b>a times</b> .	The first digit ( <b>a</b> ) in the odometer will be the first digit in the PIN.	
5	Press <b>right</b> turn switch <b>1 time</b> .	The first digit is stored and the dash will flash.	Serves as enter key.
6	Enter second digit ( <b>b</b> ) in the PIN by pressing <b>left</b> turn switch <b>b times</b> .	The second digit ( <b>b</b> ) in the odometer will be the second digit in the PIN.	
7	Press <b>right</b> turn switch <b>1 time</b> .	The second digit is stored and the next dash will flash.	Serves as enter key.
8	Enter third digit ( <b>c</b> ) in the PIN by pressing <b>left</b> turn switch <b>c times</b> .	The third digit ( <b>c</b> ) in the odometer will be the third digit in the PIN.	
9	Press <b>right</b> turn switch <b>1 time</b> .	The third digit is stored and the next dash will flash.	Serves as enter key.

**Table 21. Entering a PIN to Disarm Harley-Davidson Smart Security System**

STEP NO.	ACTION	WAIT FOR CONFIRMATION	NOTES
10	Enter fourth digit ( <b>d</b> ) in the PIN by pressing <b>left</b> turn switch <b>d times</b> .	The fourth digit ( <b>d</b> ) in the odometer will be the fourth digit in the PIN.	
11	Press <b>right</b> turn switch <b>1 time</b> .	The fourth digit is stored and the next dash will flash.	Serves as enter key.
12	Enter fifth digit ( <b>e</b> ) in the PIN by pressing <b>left</b> turn switch <b>e times</b> .	The fifth digit ( <b>e</b> ) in the odometer will be the fifth digit in the PIN.	
13	Press <b>right</b> turn switch <b>1 time</b> .	The fifth digit is stored. The key icon stops blinking.	Smart Security System is disarmed.

**NOTE**

- *At any time during a PIN disarm, if the fob is brought within range of the motorcycle, the Smart Security System will disarm when the module receives the coded signal from the fob.*
- *If a mistake is made while entering PIN, wait two minutes before another disarming attempt.*
- *The Smart Security System will remain disarmed until the ignition key is turned to OFF.*

## Hazard Warning 4-Way Flasher

If it should be necessary to leave a motorcycle parked along side a roadway, the hazard warning four-way flashers can be turned ON and the Smart Security System armed.

## To arm the H-DSSS with the Hazard Warning 4-Way Flashers ON

1. Turn ignition key to ACCESS.
2. Simultaneously press both left and right turn signal switches to turn the four-way flashers ON.
3. Turn the ignition key to OFF to arm the Smart Security System.

## To Turn Hazard Warning 4-Way Flashers OFF

1. Turn ignition key to IGNITION.
2. Simultaneously press the left and right turn signal switches.

# ALARM

## Warnings

Once armed, if the motorcycle is moved or lifted up off of its jiffy stand or if the ignition key is turned to IGNITION and the fob is not present, the alarm will warn the operator with three alternate flashes of the turn signals and a chirp of the optional siren.

Within four seconds, if the motorcycle is back on its jiffy stand and no further motion is detected and/or the ignition key is turned to OFF, the module will remain armed without activating the alarm.

If the motorcycle motion continues or the ignition key is not turned back to OFF, the module will issue a second warning four seconds after the first.

### NOTE

*During warnings and alarms, the starter motor and the ignition circuits are disabled.*

## The Alarm

If the Smart Security System is still detecting motion and/or if the ignition key has not been turned back to OFF after a second warning, the system will activate the alarm.

When activated, the Smart Security System will:


- Alternately flash the four turn signals.
- See Figure 17. Sound the optional siren.

**Duration:** The alarm will stop within 30 seconds and if no motion is detected, the alarm will not restart.

However, if motorcycle motion continues the system will repeat the 30 second alarm and recheck for motion. The alarm will repeat this 30 second alarm cycle for five minutes (10 cycles) or until the alarm is deactivated.

### NOTE

*The alarm will also activate the LED, vibration or audible modes of a Harley-Davidson Security Pager. A pager can operate either in silent or in combination with an optional Smart Siren. The range of a pager can be up to 0.5 mile (0.8 km). See a Harley-Davidson dealer for details.*



**Figure 17. Optional Smart Siren**

## Deactivate the Alarm

**Key Fob:** Bring the fob to the motorcycle. After the module identifies that the fob is present, the system will terminate the alarm.

## SIREN CHIRPLESS/CHIRP MODES: INTERNATIONAL MODELS

### Chirpless Mode

In the Chirpless Mode, the siren does not chirp on arming or disarming.

#### NOTE

*Even when armed in the chirpless mode, the siren still chirps warnings on movement and will activate the alarm through all alarm cycles.*

### Chirp Mode

On arming in the Chirp Mode, the siren responds with two chirps. When disarming, the siren responds with a single chirp.

### Switching Modes

Cycling quickly through arming and disarming twice will switch the system from either the chirpless or the chirp mode to its opposite.

1. With the fob present, the ignition key ON and the system disarmed, turn the ignition key OFF.
2. When the system arms (2 flashes of turn signals), immediately turn the ignition key back ON.

3. When the system disarms (1 flash of the turn signals), immediately turn the ignition key OFF.
4. When the system arms (2 flashes of turn signals), immediately turn the ignition key ON and wait for the system to arm.

## **TRANSPORT MODE**

In the transport mode, the Harley-Davidson Smart Security System is armed but the motion detectors are inactive. The motorcycle can be transported on a trailer or moved in storage without activating the alarm while the starter and ignition remain disabled.

### **To Enter Transport Mode**

1. With the fob present, turn the ignition key to IGNITION.
2. Rock the engine OFF/RUN switch to OFF.
3. With an assigned fob within range, turn the ignition key from OFF to ACCESS.
4. Simultaneously press both the left and right turn signal switches. The turn signals will flash once.
5. Turn the ignition key to OFF to arm the system. The turn signals will flash three times as the system arms in the transport mode.

### **To Exit the Transport Mode**

With a fob present, turn the ignition key to IGNITION and the engine OFF/RUN switch to RUN. The system exits the transport mode when the OFF/RUN switch is in RUN.

## **STORAGE AND SERVICE DEPARTMENTS**

### **Long Term Parking**

To maintain arming, store the fob beyond the range of the module. If the motorcycle is to be moved while parked, have the fob present.

If the motorcycle will not be operated for several months, such as during the winter season, follow the Owner's Manual instructions for storage. Refer to MAINTENANCE AND LUBRICATION > MOTORCYCLE STORAGE: VRSC MODELS (Page 135).

### **Service Departments**

When the motorcycle is to be left at a Harley-Davidson dealer, there are two options:

1. Leave an assigned fob with the dealer.
2. To maintain possession of the fob, ask the dealer to disable the module for service (service mode) before leaving the dealership.

## FOB BATTERY

### Replacing the Battery

Replace the key fob battery every year.

1. See Figure 18. Slowly turn a thin blade in the thumbnail slot (1) on the side of the fob to separate the two halves.
2. Remove the battery (2) and discard.

#### NOTE

*Dispose of the old battery in accordance with local regulations.*

3. Install a **new** battery (Panasonic 2032 or equivalent) with the positive (+) side down.
4. Align the two halves of the fob and snap together.




Figure 18. Hands-Free Fob Battery

## POWER DISCONNECTS

### Optional Siren

On a power disconnect, to prevent the module from actuating the optional siren:

1. Verify that the fob is present.
2. Turn the ignition key to IGNITION.
3. Pull the maxi-fuse from its holder or disconnect the battery.

## TROUBLESHOOTING

### Key Icon

If the system key icon stays illuminated while riding, see a Harley-Davidson dealer.

### Fob

With the fob present, if the Smart Security System continues to actuate warnings and alarms, one of the following can be the cause:

1. **Electromagnetic Interference:** Other electronic devices, power lines, or other electromagnetic sources can cause the Smart Security System to operate inconsistently.
  - a. Verify that the fob is not in a metal enclosure or within 3.0 in. (76 mm) of any other electronic devices.
  - b. Place the fob on the seat and turn the ignition key to IGNITION. After the module disarms, return the fob to a convenient location.
  - c. Move motorcycle at least 15 feet (5 m) from the spot of interference.
2. **Discharged Fob Battery:** Use the PIN to disarm the module. Replace the battery. Refer to HARLEY-DAVIDSON SMART SECURITY SYSTEM > FOB BATTERY (Page 61).
3. **A Damaged Fob:** Use the PIN to disarm the motorcycle. Replacement fobs are available for purchase from a Harley-Davidson dealer.

### Siren

- If the siren does not chirp two or three times on a valid arming command from the security module, the siren is either in the Chirpless Mode, not connected, not working, or the siren wiring was opened or shorted while the siren was disarmed.



- If the siren is armed and the internal siren battery is dead, shorted, disconnected, or has been charging for a period longer than 24 hours, the siren will respond with three chirps on arming instead of two.
- The internal siren battery may not charge if the vehicle's battery is less than 12.5 volts.
- If the siren enters the self-driven mode where it is powered from the siren's internal 9 volt battery, the turn signal lamps may or may not alternately flash. If the security module activates the siren, the turn signal lamps will alternately flash. If the siren has been armed and a security event occurs, and the siren is in self-driven mode, the siren will alarm for 20 to 30 seconds and then turn off for 5 to 10 seconds. This alarm cycle will be repeated ten times if the siren is in the self-driven mode.



## NOTES

---



## OPERATING RECOMMENDATIONS: VRSC MODELS

### NOTICE

**Do not run the engine at extremely high RPM with clutch disengaged or transmission in neutral. Running an engine at high RPM can result in engine damage. (00177a)**

- The maximum recommended safe engine speed is 9000 RPM.
- Do not idle engine unnecessarily for more than a few minutes with motorcycle standing still.

### NOTICE

**Do not exceed the maximum safe RPM specified below under any conditions. Exceeding the maximum safe engine RPM can result in equipment damage. (00248a)**

### NOTE

*The maximum recommended engine speed for VRSC model motorcycles is 9000 RPM.*

If motorcycle will not be ridden for a period of three weeks or more with security system armed, it is recommended to connect a Battery Tender to maintain battery charge. If security system will not be armed, it is recommended that the 40 Amp maxi-fuse be removed. See MAINTENANCE AND

LUBRICATION > ELECTRICAL PROTECTION: VRSC MODELS (Page 128).

### NOTICE

**Use only Genuine Harley-Davidson Extended Life Antifreeze and Coolant. Use of other coolants/mixtures may lead to motorcycle damage. (00179c)**

Have the engine checked regularly and keep it well tuned. This applies particularly to a motorcycle equipped with windshield and fairing.

### ▲ WARNING

**When riding on wet roads, brake efficiency and traction are greatly reduced. Failure to use care when braking, accelerating or turning on wet roads can cause loss of control, which could result in death or serious injury. (00041a)**

### NOTE

- While the motorcycle is operating, electronically controlled cooling fans will turn on periodically. This is normal operation.
- When descending upon a long, steep grade, downshift and use engine compression together with intermittent application of both brakes to slow the motorcycle.

### **⚠ WARNING**

**Continuous use of brake causes overheating and reduced efficiency, which could result in death or serious injury. (00042a)**

### **NOTICE**

**Do not coast for long distances with the engine off or idling. The transmission is properly lubricated only when the engine is running. Coasting long distances can result in transmission damage. (00180b)**

### **⚠ WARNING**

**Do not tow a disabled motorcycle. Towing can adversely affect stability and handling, which could result in death or serious injury. (00017a)**

## **BREAK-IN RIDING RULES: VRSC MODELS**

### **The First 500 Miles (800 Kilometers)**

The sound design, quality materials, and workmanship that are built into your new Harley-Davidson will give you optimum performance right from the start.

To allow your engine to wear in its critical parts, we recommend that you observe the riding rules provided below for the first 500 miles (800 kilometers). Adherence to these

suggestions will help to assure good future durability and performance.

1. During the first 50 miles (80 kilometers) of riding, keep the engine speed below 5000 RPM in any gear. Do not lug the engine by running or accelerating at very low RPM, or by running at high RPM longer than needed for shifting or passing.
2. Up to 500 miles (800 kilometers), vary the engine speed and avoid operating at any steady engine speed for long periods. Engine speed up to 7000 RPM in any gear is permissible.
3. Drive slowly and avoid fast starts at wide open throttle until the engine has warmed up.
4. Avoid lugging the engine by not running the engine at very low speeds in higher gears.
5. Avoid hard braking. New brakes need to be broken-in by moderate use for the first 200 miles (300 kilometers).

## **PRE-RIDING CHECKLIST: VRSC MODELS**

### **⚠ WARNING**

**Identify and understand the specific features of your vehicle. Failure to understand how these features affect the vehicle's operation can lead to an accident, which could result in death or serious injury. (00043b)**

Before riding your motorcycle at any time, make a general inspection to be sure it is in safe riding condition.

1. Check the amount of fuel in the tank and add fuel if required.

**⚠ WARNING**

**Avoid spills. Slowly open fuel filler cap. Do not fill above bottom of filler neck insert, leaving air space for fuel expansion. Secure filler cap after refueling. Gasoline is extremely flammable and highly explosive, which could result in death or serious injury. (00028b)**

**⚠ WARNING**

**Use care when refueling. Pressurized air in fuel tank can force gasoline to escape through filler tube. Gasoline is extremely flammable and highly explosive, which could result in death or serious injury. (00029a)**

**⚠ WARNING**

**Stop the engine when refueling or servicing the fuel system. Do not smoke or allow open flame or sparks near gasoline. Gasoline is extremely flammable and highly explosive, which could result in death or serious injury. (00002a)**

**NOTICE**

**Do not spill fuel onto the motorcycle while refueling. Immediately wipe up fuel spills on your motorcycle. Fuel can cause damage to cosmetic surfaces. (00147b)**

2. Adjust mirrors to proper riding positions.
3. Check the oil level. See MAINTENANCE AND LUBRICATION > CHECKING OIL LEVEL: VRSC MODELS (Page 74).
4. Check the coolant level. See MAINTENANCE AND LUBRICATION > COOLANT LEVEL (Page 79).
5. Check the controls to be sure they are operating properly. Operate the front and rear brakes, throttle, clutch and shifter.
6. Check steering for smoothness by turning the handlebars through the full operating range.

### **▲ WARNING**

**Be sure tires are properly inflated, balanced, undamaged, and have adequate tread. Inspect your tires regularly and see a Harley-Davidson dealer for replacements. Riding with excessively worn, unbalanced, improperly inflated, overloaded or damaged tires can lead to tire failure and adversely affect stability and handling, which could result in death or serious injury. (00014b)**

7. Refer to Table 15 . Check tire condition and pressure. Incorrect pressure will result in poor riding characteristics and can affect handling and stability. Adhere to tire specifications for correct inflation pressures to use.

### **▲ WARNING**

**Be sure headlamp, tail and stop lamp and turn signals are operating properly before riding. Poor visibility of rider to other motorists can result in death or serious injury. (00478b)**

8. Check all electrical equipment and switches including the stop lamp, turn signals and horn, for proper operation.
9. Check for any fuel, oil or hydraulic fluid leaks.

10. Check rear belt adjustment.

11. Service your motorcycle as necessary.

## **STARTING THE ENGINE**

### **General**

#### **NOTICE**

**The engine should be allowed to run slowly for 30-60 seconds. This will allow the engine to warm up and let oil reach all surfaces needing lubrication. Failure to comply can result in engine damage. (00181b)**

Do not roll the throttle before starting. Rolling the throttle before starting the motorcycle is unnecessary.

### **Starting**

#### **▲ WARNING**

**Shift transmission to neutral before starting engine to prevent accidental movement, which could result in death or serious injury. (00044a)**

1. Turn ignition/headlamp key switch to IGNITION position. Do not roll the throttle.

#### NOTE

*The engine lamp will light for approximately 4 seconds and you will hear the fuel pump purr for approximately 2 seconds as it operates to fill the fuel lines with gasoline.*

2. See Figure 19. Turn the off/run switch to RUN position.
3. Squeeze the clutch lever in against the handgrip.


#### NOTE

*To activate the starting system, the clutch interlock circuitry requires the clutch be disengaged, clutch lever pulled in against left handgrip, and/or the transmission be shifted to the neutral position (green neutral lamp lit).*

4. Press the starter button to start the motorcycle.
5. When the engine has started, you can operate your motorcycle as you normally would after raising the jiffy stand.

#### NOTE

*If the fuel tank becomes completely dry, it may take a few seconds longer to start the motorcycle after filling the tank. It will not be necessary to take any extraordinary measures before starting the motorcycle.*



**Figure 19. Right Handlebar Controls: VRSC Models**  
**STOPPING THE ENGINE**

1. Stop the engine by turning OFF the engine stop switch on the right handlebar.

2. Turn OFF the ignition/headlamp key switch. If the engine should be stalled or stopped in any way, turn off the ignition/headlamp key switch at once to prevent battery discharge.

## SHIFTING GEARS

### Getting Started

#### NOTICE

**The clutch must be fully disengaged before attempting a gear shift. Failure to fully disengage the clutch can result in equipment damage. (00182a)**

The shift pattern is first gear down, next four gears up.

#### NOTE

*Always start engine with transmission in neutral. Always start motorcycle forward motion in first gear.*

1. With motorcycle engine running and jiffy stand retracted, pull the clutch hand lever in against handlebar grip to fully disengage clutch.
2. Press the foot shift lever down to end of its travel and release. The transmission is now in first gear.
3. To start forward motion, ease out the clutch lever slowly and at the same time, open throttle gradually.

## Upshift (Acceleration)

Refer to Table 22. Engage second gear after the motorcycle has reached at the appropriate shifting speed.

**Table 22. Upshift (Acceleration) Gear Speeds: VRSC Models**


GEAR CHANGE	MPH	KPH
First to second	15	25
Second to third	25	40
Third to fourth	35	55
Fourth to fifth	45	72

1. Close the throttle.
2. Disengage the clutch (pull clutch lever in).
3. See Figure 20. Lift the gear shift lever up to the end of its travel and release.
4. Ease out the clutch lever and gradually open the throttle.
5. Repeat the previous steps to engage third, fourth, and fifth gears.

#### NOTE

- *Disengage the clutch completely before each gear change.*
- *Partially close the throttle so the engine will not drag when clutch is again engaged (clutch lever released).*





**Figure 20. Gear Shift Lever (Upshift): VRSC Models**

## Downshift (Deceleration)

### ⚠ WARNING

**Do not downshift at speeds higher than those listed. Shifting to lower gears when speed is too high can cause the rear wheel to lose traction and lead to loss of vehicle control, which could result in death or serious injury. (00045b)**

Gear shift pattern is first gear down; next four gears up. Refer to Table 23 for shifting speeds.

**Table 23. Downshift (Deceleration) Gear Speeds: VRSC Models**

GEAR CHANGE	MPH	KPH
Fifth to fourth	40	65
Fourth to third	30	50
Third to second	20	30
Second to first	10	15

### NOTE

*The shifting points shown in the tables are recommendations. Vehicle owners may determine that their own individual shifting patterns may differ than those stated and are additionally appropriate for individual riding styles.*

See Figure 21. When engine speed decreases, as in climbing a hill or running at a reduced speed, shift to the next lower gear while partially closing the throttle so the engine accelerates as soon as the clutch lever is released.


**NOTE**

- *Disengage the clutch completely before each gear change.*
- *Partially close the throttle so the engine will not drag when clutch is again engaged (clutch lever released).*

**NOTICE**

**Shift to neutral before stopping engine. Shifting mechanism can be damaged by shifting gears while engine is stopped. (00183a)**

The gear shifter mechanism permits shifting the transmission to neutral from either first or second gear.



**Figure 21. Gear Shift Lever (Downshift): VRSC Models**

## SAFE OPERATING MAINTENANCE: VRSC MODELS

### ⚠ WARNING

Perform the service and maintenance operations as indicated in the regular service interval table. Lack of regular maintenance at the recommended intervals can affect the safe operation of your motorcycle, which could result in death or serious injury. (00010a)

Good maintenance means a safe machine. A careful check of certain equipment must be made after periods of storage and frequently between the regular service intervals to determine if additional maintenance is necessary.

Check the following items:

1. Tires for correct pressure, abrasions or cuts.
2. Drive belt for proper tension.
3. Brakes, steering and throttle for responsiveness.
4. Brake fluid level and condition. Hydraulic lines and fittings for leaks. Also, check brake pads and discs for wear.
5. Throttle cables for fraying or crimping and free operation.
6. Engine oil level.
7. Engine coolant level.

8. Clutch fluid level.
9. Headlamp, tail lamp, brake lamp and directional lamp operation.

## BREAK-IN MAINTENANCE

### NOTE

*The performance of new motorcycle initial service is required to keep your new motorcycle warranty in force and to assure proper emissions system operation.*

Refer to Table 30. After a new motorcycle has been ridden its first 1000 miles (1600 kilometers), it should be taken to an authorized Harley-Davidson dealer for initial service operations.

## ENGINE LUBRICATION

### NOTICE

**Do not switch lubricant brands indiscriminately because some lubricants interact chemically when mixed. Use of inferior lubricants can damage the engine. (00184a)**

Engine oil is a major factor in the performance and service life of the engine. Always use the proper grade of oil for the lowest temperature expected before the next scheduled oil change. Refer to Table 24. Your authorized dealer has the proper oil to suit your requirements.

If it is necessary to add oil and Harley-Davidson oil is not available, use an oil certified for diesel engines. Acceptable diesel engine oil designations include: CF-4, CG-4, CH-4 and CI-4.

The preferred viscosities for the diesel engine oils in descending order are: 20W50, 15W40 and 10W40.

At the first opportunity, see an authorized dealer to change back to 100 percent Harley-Davidson oil.

**Table 24. Recommended Engine Oils: VRSC Models**

HARLEY-DAVIDSON TYPE	VISCOSITY	HARLEY-DAVIDSON RATING	LOWEST AMBIENT TEMPERATURE	COLD WEATHER STARTS BELOW 50° F (10° C)
HD Multi-grade	SAE 10W40	HD 360	Below 40° F (4° C)	Excellent
HD Multi-grade	SAE 20W50	HD 360	Above 40° F (4° C)	Good

## CHECKING OIL LEVEL: VRSC MODELS

### NOTE

*This engine has a wet sump, an integral transmission, gear driven primary drive and wet clutch. This design allows engine oil in the sump to be used to lubricate the engine, transmission and primary drive. The clutch and primary drive are housed on the right side of the engine.*

### NOTICE

**Oil level cannot be accurately measured on a cold engine. For pre-ride inspection with the motorcycle upright (not leaning on jiffy stand) on level ground, the oil should register approximately at the midpoint of the cross-hatch area on the dipstick when the engine is cold. Do not add oil to bring the level to the full mark on a cold engine. (00186b)**

See Figure 22. Dipstick is located on left side at front of engine.

## Cold Engine Oil Level Check

Check the oil level with the engine **COLD** as follows:


1. Stand the motorcycle upright (not leaning on the jiffy stand) on a level surface.
2. See Figure 22. Unscrew the oil filler cap (with attached dipstick) by turning the filler cap counterclockwise. Remove the filler cap and dipstick and wipe the dipstick clean.
3. Screw the filler cap into the engine. Make sure the cap is fully seated on the crankcase.
4. See Figure 23. Remove the filler cap again and check the oil level on the dipstick.
5. If the oil level is below the midpoint of the cross-hatch area on the dipstick, add enough Harley-Davidson oil to bring the level up to the midpoint of the cross-hatch area shown.

**NOTICE**


**Do NOT operate the engine when the oil level is below the add mark on the dipstick at operating temperature. Engine damage could result. (00493b)**

**NOTICE**

**To avoid over-filling the oil sump, wait approximately three minutes after adding oil before checking the oil level with the dipstick. An over-filled sump can cause engine damage. (00188a)**



**Figure 22. Dipstick Location: VRSC Models**



1. Full mark
2. Add mark. Do NOT operate the engine when the oil level is below the add mark at operating temperature.

Figure 23. Engine Oil Level: VRSC Models

## Hot Engine Oil Level Check

Check the oil level with the engine at normal operating temperature as follows:

1. Stop the engine and allow the oil to drain into the sump for about two minutes.

2. Stand the motorcycle upright (not leaning on the jiffy stand) on a level surface.
3. See Figure 22. Unscrew the oil filler cap (with attached dipstick) by turning the filler cap counterclockwise. Remove the filler cap and dipstick and wipe the dipstick clean.
4. Screw the filler cap into the engine. Make sure the cap is fully seated on the crankcase.
5. See Figure 23. Remove the filler cap again and check the oil level on the dipstick.

### NOTICE

Do not allow hot oil level to fall below Add/Fill mark on dipstick. Doing so can result in equipment damage and/or equipment malfunction. (00189a)

### NOTICE

Do not overfill oil sump. Doing so can result in oil carryover to the air cleaner leading to equipment damage and/or equipment malfunction. (00191a)

6. If the oil level is below the FULL mark on the dipstick, add enough Harley-Davidson oil to bring the level up to the FULL mark shown in Figure 23.

**NOTE**

*The engine will require a longer warm-up period in colder weather.*

- Check the engine oil supply at each complete fuel refill.
- Refer to Table 30. The oil should be changed according to the Regular Service Intervals in the Maintenance Schedule in normal service at warm or moderate temperatures.
- Oil change intervals should be shorter in cold weather. See MAINTENANCE AND LUBRICATION > WINTER LUBRICATION (Page 79).
- The oil ADD mark is 1/2 quart (0.473 liters) to full.

Refer to the vehicle's service manual or see a Harley-Davidson dealer for proper procedures on draining the oil.

**NOTE**

*Dispose of oil in accordance with local regulations.*

## CHANGING OIL AND OIL FILTER: VRSC MODELS

See Figure 24. The oil filter is located on an oil filter mount in front of the engine.

**⚠ WARNING**

**Be sure that no lubricants or fluids get on tires, wheels or brakes when changing fluid. Traction can be adversely affected, which could result in loss of control of the motorcycle and death or serious injury. (00047d)**

**NOTICE**

**Do not switch lubricant brands indiscriminately because some lubricants interact chemically when mixed. Use of inferior lubricants can damage the engine. (00184a)**

VRSC vehicles require a premium oil filter (Part No. 63793-01K).

1. See Figure 25. Loosen the oil drain plug and completely drain the oil.
2. Remove the oil filter using an OIL FILTER WRENCH (PART NUMBER: HD-42311).

#### NOTE

- Removal of lower radiator support may make oil filter access easier.
  - Dispose of oil and oil filter in accordance with local regulations.
3. Clean the filter gasket contact surface on the mounting plate (the surface should be smooth and free of any debris or old gasket material).
  4. See Figure 24. Apply a thin film of oil to the gasket contact surface on the mounting plate, gasket and **new** oil filter.
  5. Screw the filter onto the adapter until the gasket contacts the plate surface, then apply another 2/3-1 full turn.
  6. See Figure 25. Install the engine oil drain plug. Tighten the drain plug to 30–40 N·m (22–30 ft-lbs).
  7. Refer to Table 7. Fill the engine with the recommended amount of oil.





Figure 24. Applying Thin Oil Film





**Figure 25. Oil Drain Plug: VRSC Model**  
**WINTER LUBRICATION**

In colder climates, the engine oil should be changed often. If motorcycle is used frequently for short trips, less than 15 miles (24 kilometers), in ambient temperatures below 60° F (16° C), oil change intervals should be reduced to 1500 miles (2400 kilometers). Motorcycles used only for short runs must have

a thorough tank flush-out before **new** oil is put in. See an authorized dealer.

#### **NOTE**

*The further below freezing the temperature drops, the shorter the oil change interval should be.*

Water vapor is a normal by-product of combustion in any engine. During cold weather operation, some of the water vapor condenses to liquid form on the cool metal surfaces inside the engine. In freezing weather this water will become slush or ice and, if allowed to accumulate too long, may block the oil lines and cause damage to the engine.

If the engine is run frequently and allowed to thoroughly warm up, most of this water will become vapor again and will be blown out through the crankcase breather.

If the engine is not run frequently and allowed to thoroughly warm up, this water will accumulate, mix with the engine oil and form a sludge that is harmful to the engine.

## **COOLANT LEVEL**

GENUINE HARLEY-DAVIDSON EXTENDED LIFE ANTIFREEZE & COOLANT (Part No. 99822-02) provides protection to -34° F (-36.7° C). In climates where the temperature falls below -34° F (-36.7° C), consult a local Harley-Davidson dealer for the proper mixture.

#### NOTICE

**Use only Genuine Harley-Davidson Extended Life Antifreeze and Coolant. Use of other coolants/mixtures may lead to motorcycle damage. (00179c)**

If you find yourself in a location where Genuine Harley-Davidson Extended Life Antifreeze & Coolant is not available, you may use a 50-50 mixture of de-ionized water and Ethylene Glycol-based Antifreeze.

#### NOTICE

**De-ionized water must be used with the antifreeze in the cooling system. Hard water can cause scale accumulation in water passages which reduces cooling system efficiency, leading to overheating and motorcycle damage. (00195b)**

### Checking Coolant Level in Expansion Tank (All Models Except VRSCR)

1. Open the seat.
2. See Figure 26. Remove the airbox cover by turning the bailhead fastener 1/4 turn counterclockwise. Pull the airbox cover away from the front locating holes.

#### ⚠ WARNING

**Do not loosen or remove pressure cap when cooling system is hot. The cooling system is under pressure and hot coolant and steam can escape from pressure cap, which could cause severe burns. Allow motorcycle to cool before servicing the cooling system. (00091c)**

#### ⚠ CAUTION

**At operating temperature, radiators and oil coolers contain hot fluids. Contact with a radiator or oil cooler can result in minor or moderate burns. (00141b)**

3. See Figure 27. Check coolant level in expansion tank with coolant cold and motorcycle on jiffy stand.

#### ⚠ WARNING

**Coolant mixture contains toxic chemicals, which may be fatal if swallowed. If swallowed, do not induce vomiting; call a physician immediately. Use in a well ventilated area. Irritation to skin or eyes can occur from vapors or direct contact. In case of skin or eye contact, flush thoroughly with water and go to hospital, if necessary. Dispose of used coolant according to federal, state and local regulations. (00092a)**

4. If level is below "COLD FULL" line on tank, remove cap from tank by using pull tab and add Harley-Davidson Extended Life Antifreeze & Coolant until fluid level reaches the "COLD FULL" line.

**NOTE**

*Genuine Harley-Davidson Extended Life Antifreeze & Coolant is pre-diluted and ready to use full-strength. Do NOT add water.*


5. Replace the cap on the expansion tank.
6. Reinstall the airbox cover. Secure the cover by turning the bailhead fastener 1/4 turn clockwise.

**NOTE**


*If the coolant expansion tank is empty when the engine is cold, it is possible that air has been drawn into the cooling system. The system must be purged of any trapped air and refilled with coolant. See the VRSC service manual for instructions on the correct procedure.*

**NOTICE**

**Clean the inlet surface of the radiator regularly. Leaves and other debris can collect on the radiator surface and degrade radiator performance which could lead to overheating and motorcycle damage. (00197d)**



**Figure 26. Airbox Cover: VRSC Models**



**Figure 27. Cold Full Line On Coolant Expansion Tank:  
VRSC Models Except VRSCR**

### **Checking Coolant Level in Expansion Tank (VRSCR Model Only)**


1. See Figure 28. Remove the fastener and louvered side cover with vehicle on jiffy stand.

#### **⚠ WARNING**


Do not loosen or remove pressure cap when cooling system is hot. The cooling system is under pressure and hot coolant and steam can escape from pressure cap, which could cause severe burns. Allow motorcycle to cool before servicing the cooling system. (00091c)

#### **⚠ CAUTION**

At operating temperature, radiators and oil coolers contain hot fluids. Contact with a radiator or oil cooler can result in minor or moderate burns. (00141b)



**Figure 28. Side Cover: VRSCR Model**



**Figure 29. Cold Full Line on Expansion Tank: VRSCR Model**

2. See Figure 29. Check the coolant level in the expansion tank with the coolant cold.

**▲ WARNING**

**Coolant mixture contains toxic chemicals, which may be fatal if swallowed. If swallowed, do not induce vomiting; call a physician immediately. Use in a well ventilated area. Irritation to skin or eyes can occur from vapors or direct contact. In case of skin or eye contact, flush thoroughly with water and go to hospital, if necessary. Dispose of used coolant according to federal, state and local regulations. (00092a)**

**NOTE**

*Genuine Harley-Davidson Extended Life Antifreeze & Coolant is pre-diluted and ready to use full-strength. Do NOT add water.*

3. If the level is below the "COLD FULL" line on the tank, follow the procedure below to top off the coolant level:
  - a. Open seat.
  - b. See Figure 30. Remove the airbox cover by turning the bailhead fastener 1/4 turn counterclockwise. Pull the airbox cover away from the front locating holes.

- c. See Figure 31. Remove filler cap from the coolant expansion tank and add Genuine Harley-Davidson Extended Life Antifreeze & Coolant until the fluid level reaches the "COLD FULL" line.
- d. Replace the cap on the expansion tank.
- e. Reinstall the airbox cover. Secure the cover by turning the bailhead fastener 1/4 turn clockwise.
- f. Close the seat.


4. Reinstall the right side cover. Tighten the fastener to 4.1–6.8 N·m (36–60 **in-lbs**).

**NOTE**


*If the coolant expansion tank is empty when the engine is cold, it is possible that air has been drawn into the cooling system. The system must be purged of any trapped air and refilled with coolant. See the VRSC service manual for instructions on the correct procedure.*

**NOTICE**

**Clean the inlet surface of the radiator regularly. Leaves and other debris can collect on the radiator surface and degrade radiator performance which could lead to overheating and motorcycle damage. (00197d)**



**Figure 30. Airbox Cover: VRSCR Model**



**Figure 31. Expansion Tank Filler Cap: VRSCR Model  
(Battery Removed For Illustration Purposes Only)**

## **REAR DRIVE BELT: VRSC MODELS**

The inner tooth surface of the secondary belt has a thin coating of polyethylene lubricant. During initial operation, this coating will wear off as it is burnished into the belt fabric. This is a normal condition and not an indication of belt wear.

Refer to Table 30. Belt tension is set at the factory and should be checked after the first 1000 miles (1600 kilometers) and at regular intervals thereafter.



### NOTE


*Belt deflection window on the debris deflector is graduated in 2.0 mm increments.*

See Figure 32. Check belt tension with motorcycle cold, standing upright, transmission in neutral and no rider on the motorcycle. Use the BELT TENSION GAUGE (PART NUMBER: HD-35381) to apply 10 lbs. (4.5 kg) of force at the midpoint of the bottom belt strand. Belt deflection should be 10 mm for VRSCR or 8 mm for all other VRSC models. If belt tension adjustment is necessary, see a Harley-Davidson dealer or follow the instructions given in the applicable Service Manual.

Check rear brake caliper position on rear brake disc. Disc should run true within brake caliper.

### ▲ WARNING

**Be sure wheel and brake caliper are aligned. Riding with a misaligned wheel or brake caliper can cause the brake disc to bind and lead to loss of control, which could result in death or serious injury. (00050a)**



**Figure 32. Check Belt Deflection: VRSC Models**  
**CHASSIS LUBRICATION**

Refer to Table 30 for all maintenance schedules.



## NOTICE

**Do not switch lubricant brands indiscriminately because some lubricants interact chemically when mixed. Use of inferior lubricants can damage the engine. (00184a)**

1. Use recommended special purpose grease for steering head bearings. Use a multipurpose chassis grease for other applications.
2. Remove and lubricate handlebar throttle control grip sleeve with fresh graphite at proper intervals.
3. Lubricate throttle control cables and clutch control cable at proper intervals.
4. Lubricate front brake hand lever and clutch control hand lever only if necessary.
5. Inspect rear fork pivot shaft bearings.
6. Pack the steering head bearings with fresh grease at proper intervals.
7. Lubricate the jiffy stand mechanism with LOCTITE AEROSOL ANTI-SEIZE at proper intervals.

### NOTE

*For model specific information regarding the chassis lubrication, refer to the appropriate Service Manual or see a Harley-Davidson dealer.*

## OIL APPLICATIONS

Refer to Table 30 for all control connections and parts. Vehicle should be oiled at regular intervals, particularly after washing motorcycle or driving in wet weather.

## FRONT FORK OIL

Refer to Table 30. Have a Harley-Davidson dealer drain the front fork oil and refill at proper intervals. If fork does not appear to be working properly or an appreciable amount of oil leakage should develop, see a Harley-Davidson dealer. If there is insufficient oil in either side of fork, the rebound action will be incorrect.

## FUEL FILTER

Fuel injected motorcycles have a fuel filter attached to the fuel pump.

### NOTE

*For model specific information regarding fuel filter maintenance, refer to the appropriate Service Manual or see a Harley-Davidson dealer.*

## CLUTCH: VRSC MODELS

Squeezing the left hand lever causes the clutch master cylinder to actuate and apply pressure to the clutch actuation cylinder mounted in the engine right side cover. The actuation

cylinder piston extends and contacts the clutch release bearing to release the clutch.

#### NOTICE

**DOT 4 brake fluid will damage painted and body panel surfaces it comes in contact with. Always use caution and protect surfaces from spills whenever brake work is performed. Failure to comply can result in cosmetic damage. (00239c)**

Refer to Table 30. Check the fluid level as follows:

1. Stand the motorcycle upright (not leaning on the jiffy stand) on a level surface, so the top of the clutch master cylinder is level.
2. See Figure 33. Clean all dirt and debris from the clutch master cylinder cover (1). Remove the two clutch master cylinder cover screws (2) and remove the cover.
3. Verify the fluid level in the clutch master cylinder reservoir is at the FULL LEVEL mark at the top of the ledge on the rear inside wall of the reservoir. If the fluid level is low, add D.O.T. 4 HYDRAULIC BRAKE FLUID (Part No. 99953-99A) approved for clutch system use and available from a Harley-Davidson dealer.

#### NOTE

*Do not overfill the clutch master cylinder reservoir. As the clutch friction discs wear, the piston in the clutch cylinder will force fluid back into the reservoir which could cause fluid overflow.*

#### NOTICE

**DOT 4 hydraulic brake fluid is used in the hydraulic clutch. Do not use other types of fluids as they are not compatible and could cause equipment damage. (00353b)**

#### NOTICE

**Do not allow dirt or debris to enter the master cylinder reservoir. Dirt or debris in the reservoir can cause improper operation and equipment damage. (00205c)**

#### ⚠ WARNING

**Contact with DOT 4 brake fluid can have serious health effects. Failure to wear proper skin and eye protection could result in death or serious injury.**

- **If inhaled: Keep calm, remove to fresh air, seek medical attention.**
- **If on skin: Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. If irritation develops, seek medical attention.**


- **If in eyes:** Wash affected eyes for at least 15 minutes under running water with eye lids held open. If irritation develops, seek medical attention.
- **If swallowed:** Rinse mouth and then drink plenty of water. Do not induce vomiting. Contact Poison Control. Immediate medical attention required.
- See Safety Data Sheet (SDS) for more details available at [sds.harley-davidson.com](https://sds.harley-davidson.com)

(00240e)

4. Inspect the clutch master cylinder cover gasket for rips, cuts, cracks, or other signs of damage. Replace the gasket if necessary. Carefully place the cover and cover gasket on the master cylinder reservoir and secure with the two cover screws. Tighten the screws to 0.68–0.9 N·m (6–8 in-lbs).

#### NOTE

*If the fluid level in the clutch master cylinder reservoir is correct but the clutch does not operate properly, refer to the VRSC Service Manual or see a Harley-Davidson dealer for service.*



**Figure 33. Clutch Master Cylinder Reservoir**

## FRONT FORK BEARINGS

### ⚠ WARNING

Adjustments to steering head bearings should be performed by a Harley-Davidson dealer. Improperly adjusted bearings can adversely affect handling and stability, which could result in death or serious injury. (00051b)

Refer to Table 30. Check front fork for proper bearing adjustment and lubricate bearings at proper intervals.

With motorcycle front end raised off the floor, be sure front fork turns freely without any binding or interference and that there is no appreciable front to rear fork shake indicating excessive bearing looseness. Steering head bearings should be adjusted according to Service Manual procedure, if necessary.

## REAR FORK PIVOT SHAFT

Refer to Table 30. Check the tightness of the rear fork pivot shaft fastener at proper intervals.

### NOTE

*For model specific information regarding the rear fork pivot shaft, refer to the appropriate Service Manual or see a Harley-Davidson dealer.*

## BRAKES: VRSC MODELS

### ⚠ WARNING

Inspect brake pads for wear at service maintenance intervals. If you ride under adverse conditions (steep hills, heavy traffic, etc.), inspect more frequently. Excessively worn brake pads can lead to brake failure, which could result in death or serious injury. (00052a)

### NOTICE

**DOT 4 brake fluid will damage painted and body panel surfaces it comes in contact with. Always use caution and protect surfaces from spills whenever brake work is performed. Failure to comply can result in cosmetic damage. (00239c)**

### NOTE

- Master cylinder cover specifies correct brake fluid.
- When adding or changing brake fluid, be sure to use only the type specified for your motorcycle.
- Use only Harley-Davidson D.O.T. 4 HYDRAULIC BRAKE FLUID (Part No. 99953-99A).

Harley-Davidson has provided your new motorcycle with the optimum brake pad friction material available. It is selected to give the best performance possible under dry, wet and high operating temperature conditions. It exceeds all regulatory

requirements currently in effect. However, during some braking conditions you may experience noise. This is normal for this friction material.


Refer to Table 30 for brake system inspection intervals.

#### NOTE

*The rear brake master cylinder fluid level can also be viewed with a flashlight through back area of radiator cover trim making radiator cover removal unnecessary.*

#### ⚠ WARNING

**To prevent accidental vehicle start-up, which could cause death or serious injury, remove main fuse before proceeding. (00251b)**



**Figure 34. Removing Right Side Radiator Cover Trim**



**Figure 35. Rear Brake Master Cylinder Reservoir: VRSCR Model**

1. Check the fluid level in the rear brake master cylinder reservoir.
  - a. See Figure 34. Remove the fastener that secures the radiator cover side trim. Gently pull the bottom of the side trim outward, lift up on the trim to detach it from its upper attachment point and remove it from the motorcycle.

- b. See Figure 35. Verify the fluid level in the rear brake master cylinder reservoir is 12.7 mm (1/2 in.) below the top of the reservoir, as viewed through the translucent plastic case of the reservoir.
- c. If the level is low, clean all dirt and debris from the reservoir cover. Remove the two reservoir cover screws and remove the cover. Add D.O.T. 4 HYDRAULIC BRAKE FLUID (Part No. 99953-99A) which is available from a Harley-Davidson dealer. Replace the reservoir cover and cover fasteners. Tighten the fasteners to 0.68–0.9 N·m (6–8 in-lbs).
- d. Carefully reinstall the radiator cover side trim and fastener. Tighten the fastener to 3–4 N·m (26.5–35.3 in-lbs).

2. Check the fluid level in the front brake master cylinder reservoir.
  - a. Stand the motorcycle upright (not leaning on the jiffy stand) on a level surface, so the top of the front brake master cylinder is level.
  - b. See Figure 4. Clean all dirt and debris from the front brake master cylinder cover. Remove the two master cylinder cover screws and remove the cover.

- c. Verify the fluid level in the front brake master cylinder reservoir is 5 mm (1/5 in.) below the reservoir top. If the fluid level is low, add D.O.T. 4 HYDRAULIC BRAKE FLUID (Part No. 99953-99A) which is available from a Harley-Davidson dealer.
- d. Replace reservoir cover and cover fasteners. Tighten fasteners to 0.8–1.2 N·m (6–8 in-lbs).

**NOTE**

*Use only D.O.T. 4 HYDRAULIC BRAKE FLUID (Part No. 99953-99A) approved for brake system use and available from a Harley-Davidson dealer.*

**NOTICE**

**DOT 4 brake fluid will damage painted and body panel surfaces it comes in contact with. Always use caution and protect surfaces from spills whenever brake work is performed. Failure to comply can result in cosmetic damage. (00239c)**

**⚠ WARNING**

**Inspect brake pads for wear at service maintenance intervals. If you ride under adverse conditions (steep hills, heavy traffic, etc.), inspect more frequently. Excessively worn brake pads can lead to brake failure, which could result in death or serious injury. (00052a)**

- 3. Check the brake discs for wear.

**⚠ WARNING**

**Always replace brake pads in complete sets for correct and safe brake operation. Improper brake operation could result in death or serious injury. (00111a)**

**⚠ WARNING**

**Brakes are a critical safety component. Contact a Harley-Davidson dealer for brake repair or replacement. Improperly serviced brakes can adversely affect brake performance, which could result in death or serious injury. (00054a)**

**⚠ WARNING**

**Perform routine scheduled brake maintenance. Lack of maintenance at recommended intervals can adversely affect brake performance, which could result in death or serious injury. (00055a)**


- 4. See Figure 36. Visual inspection of brake pads can be made without removing the caliper by viewing the lower area of each caliper with the aid of a flashlight. Replace the brake pads if the brake friction material is 0.4 mm (0.016 in.) or less above the backing plate.

#### NOTE

- If the brake pad friction material is 0.4 mm (0.016 in.) thick or less, the pads must be replaced immediately.
- Always replace brake pads in pairs.

The rear brake outer pad on all models can be measured from the caliper bracket side using a thin plastic 152 mm (6 in.) rule.

Place the rule against the brake disc through the space alongside the caliper. If friction material measures less than 0.4 mm (0.016 in.), replace both brake pads immediately.



**Figure 36. Brake Friction Material**



## TIRES: VRSC MODELS

### ⚠ WARNING

**Do not inflate tire beyond maximum pressure as specified on sidewall. Over inflated tires can blow out, which could result in death or serious injury. (00027b)**

- Refer to Table 15. Be sure to keep tires properly inflated.
- Follow the data for correct cold tire inflation pressures.
- Check before riding when tires are cold.
- Do not over-inflate tires.

### ⚠ WARNING

**Match tires, tubes, rim strips or seals, air valves and caps to the correct wheel. Contact a Harley-Davidson dealer. Mismatching can lead to tire damage, allow tire slippage on the wheel or cause tire failure, which could result in death or serious injury. (00023c)**

- Check inflation pressure and inspect the tread for punctures, cuts breaks, etc., at least weekly if in daily use or before each trip if used occasionally.

### NOTE

*The VRSC features performance-oriented tires. These tires require more frequent inspection and may require more*

*frequent replacement than Harley-Davidson touring model tires.*

Refer to Table 14. Same original equipment tires should be used. Other tires may not fit correctly, could adversely affect handling and may be hazardous to use.

### ⚠ WARNING

**Tires are a critical safety component. Contact a Harley-Davidson dealer for tire repair or replacement. Improper tire service can adversely affect stability and handling, which could result in death or serious injury. (00057a)**

### ⚠ WARNING

**Replace punctured or damaged tires. In some cases, small punctures in the tread area may be repaired from within the removed tire by a Harley-Davidson dealer. Speed should NOT exceed 80 km/h (50 mph) for the first 24 hours after repair, and the repaired tire should NEVER be used over 129 km/h (80 mph). Failure to follow this warning could lead to tire failure and result in death or serious injury. (00015b)**

### **⚠ WARNING**

**Striking an object, such as a curb or pothole can cause internal tire damage. If an object is struck, have the tire inspected immediately inside and out by a Harley-Davidson dealer. A damaged tire can fail while riding and adversely affect stability and handling, which could result in death or serious injury. (00058b)**

## **TIRE REPLACEMENT**

### **Inspection**

### **⚠ WARNING**

**Replace tire immediately with a Harley-Davidson specified tire when wear bars become visible or only 1 mm (1/32 in) tread depth remains. Riding with a worn tire could result in death or serious injury. (00090c)**


See Figure 37. Arrows on tire sidewalls pinpoint location of wear bar indicators.

Tread wear indicator bars will appear on tire tread surfaces when 1/32 in. (0.8 mm) or less of tire tread remains. See Figure 38. Always replace tires before the tread wear indicator bars appear.

## **When To Replace Tires**

New tires are needed if any of the following conditions exist:

1. Tread wear indicator bars become visible on the tread surfaces.
2. Tire cords or fabric become visible through cracked sidewalls, snags or deep cuts.
3. A bump, bulge or split in the tire.
4. Puncture, cut or other damage to the tire that cannot be repaired.



**Figure 37. Tire Sidewall: VRSC Models**



**Figure 38. Tread Surface Wear Bar (Typical): VRSC Models**  
**SPARK PLUGS/COILS: VRSC MODELS**

Refer to Table 30. Check the spark plugs at proper mileage intervals.

### ▲ CAUTION

**Do NOT pull on any electrical wires. Pulling on electrical wires may damage the internal conductor causing high resistance, which may result in minor or moderate injury. (00168a)**

Before installing spark plugs, the gap should be checked and adjusted if necessary to 0.035 in. (0.89 mm).

Be sure your motorcycle has the correct spark plug. Use a **10R12A** spark plug.

Spark plugs must be tightened to the torque specified for proper heat transfer. Tighten spark plugs to 23 N·m (17 ft-lbs) per spark plug.

### NOTE

- *If a torque wrench is not available, tighten the spark plugs finger tight; then tighten an additional one quarter turn with a spark plug wrench.*
- *The VRSC is equipped with plug-top coils. To inspect the spark plugs, the coils must be removed. Consult the VRSC Service Manual for the proper service procedure.*

## SHOCK ABSORBERS

Refer to Table 30. Inspect shock absorbers and rubber bushings for leaks and bushing deterioration at proper intervals.


## IGNITION

The engine in your motorcycle has been designed specifically to achieve optimum fuel economy within exhaust emission controls. Factory programmed ignition characteristics provide maximum engine performance and driveability.


## AIR CLEANER: VRSC MODELS

Refer to Table 30. The engine air cleaner is a paper/wire mesh air filter element. Inspect the filter element. Inspect more often under dusty conditions. Remove the air cleaner as follows:

1. Open seat.
2. See Figure 39. Remove the airbox cover by turning the bailhead fastener 1/4 turn counterclockwise. Pull the airbox cover away from the front locating holes.
3. See Figure 40. Remove electrical connector (3) by pushing down on bail wire to unlock. The airbox top is retained by eight clips, three per side, one at the rear and one in the front under the snorkel. Release the clips and remove the airbox top.



**Figure 39. Airbox Cover: VRSCR Model**



**Figure 40. Airbox Top: VRSC Models**

4. See Figure 41. Unscrew the wing nut securing the air cleaner cap. Remove the air cleaner cap and paper/wire mesh air filter element.

### NOTICE

**To prevent objects from falling down the velocity stacks, temporarily reinstall the air cleaner cap. (00208a)**

5. Wash the paper/wire mesh air filter element in luke warm water with a mild detergent. Rinse thoroughly.

### ⚠ WARNING

**Compressed air can pierce the skin and flying debris from compressed air could cause serious eye injury. Wear safety glasses when working with compressed air. Never use your hand to check for air leaks or to determine air flow rates. (00061a)**

6. Allow the filter element to either air dry or blow it dry from the inside with low pressure air.
7. Hold the filter element up to a strong light source. If light is uniformly visible through the element, it is sufficiently clean. Replace the filter element if it is damaged or if the filter media cannot be adequately cleaned.

### NOTE


*Do not use air cleaner filter oil on Harley-Davidson paper/wire mesh air filter elements.*

8. Remove the air cleaner cap. Place the air filter element in the bottom tray of the airbox. Install the air cleaner cap over the air filter element and secure with the wing nut.


### NOTICE

**Install air filter before running engine. Failure to do so can draw debris into the engine and could result in engine damage. (00207a)**

9. Position the airbox top over the air filter assembly and fasten the clips along each side and the clip at the rear.
10. See Figure 42. The front clip under the snorkel is attached to the airbox top. Fasten the clip over the lip on the airbox bottom.
11. See Figure 39. Position the airbox cover with the locating pins in the holes on the frame tabs.
12. Turn the bailhead fastener 1/4 turn clockwise to secure the airbox cover to the motorcycle.
13. Close seat.



**Figure 41. Air Cleaner Assembly: VRSC Models**



**Figure 42. Front Airbox Clip  
HEADLAMP: VRSC MODELS**

See Figure 43. All VRSC headlamp assemblies use replaceable quartz halogen bulb(s).

**NOTE**

*Refer to Table 16 and see a service manual for more details.*

#### NOTICE

When replacement is required, use only the specified sealed beam unit or bulb, available from a Harley-Davidson dealer. An improper wattage sealed beam or bulb, can cause charging system problems. (00209a)

#### NOTICE

Never touch the quartz bulb. Fingerprints will etch the glass and decrease bulb life. Handle the bulb with paper or a clean, dry cloth. Failure to do so could result in bulb damage. (00210b)


#### ⚠ WARNING

Handle bulb carefully and wear eye protection. Bulb contains gas under pressure, which, if not handled carefully, could cause serious eye injury. (00062b)






om00672a



VRSCA  
VRSCR  
VRSCX



VRSCD  
VRSCDX

1. Headlamp bulbs
2. Position lamp harness (international only)

3. Position bulb (international only)

Figure 43. Headlamp: VRSC Models

SERVICE

## HEADLAMP ALIGNMENT: VRSC MODELS

### ⚠ WARNING

The automatic-on headlamp feature provides increased visibility of the rider to other motorists. Be sure headlamp is on at all times. Poor visibility of rider to other motorists can result in death or serious injury. (00030b)

Check headlamp for proper height and lateral alignment:

- When the new owner takes delivery of the motorcycle.
  - When there is a change in load (adding luggage, etc.).
1. Refer to Table 15. Verify correct front and rear tire pressure.
  2. Place motorcycle on level floor (or pavement) in an area with minimum light.
  3. See Figure 44. Position motorcycle 7.6 m (25 ft) away from a screen or wall. Measure the vertical distance from center of headlamp to floor, and draw a horizontal line (2) 0.9 m (35 in.) on screen or wall at same height above floor.





Figure 44. Headlamp Alignment: VRSC Models




**Figure 45. Headlamp Switch High Beam Setting**

4. Load vehicle with rider, passenger (if normally present) and any cargo. Weight will compress vehicle suspension slightly.

5. Stand motorcycle upright with both tires resting on floor and with front wheel held in straight alignment (directly forward).
6. See Figure 45. Turn ignition switch ON. Set handlebar headlamp switch to HIGH beam position.
7. Check lamp beam for alignment.
8. See Figure 46 or Figure 47. If adjustment is required:
  - a. Loosen left and right fasteners.
  - b. Move headlamp assembly to adjust vertical alignment.
  - c. Tighten fasteners. For VRSCD/VRSCDX models, tighten to 31–41 N·m (23–30 ft-lbs). For all other VRSC models, tighten to 4.5–7.5 N·m (40–66 in-lbs).



**Figure 46. Headlamp Alignment Fastener: VRSC Models**



**Figure 47. Headlamp Alignment Fastener: VRSCD Models**

## **TURN SIGNAL BULBS: BULLET STYLE**

### **Replacement**

1. See Figure 48. To access the front or rear turn signal bulbs for replacement, locate a notch on the turn signal lens cap.
2. Insert a coin in the lens cap notch, and carefully twist until the lens cap pops out of the lamp housing.

3. Push in and twist the lamp bulb counterclockwise and pull lamp bulb out of the socket.
4. Orient index pins on **new** lamp bulb with pin guides inside bulb socket.
5. Push lamp bulb in and turn clockwise to lock in place.
6. Snap lens cap back into the lamp holder.

### Alignment

Refer to service manual for alignment procedure.




Figure 48. Lens Cap Notch

## ALTERNATOR/VOLTAGE REGULATOR

### Charging Rate

The alternator output is controlled and changed to direct current by the voltage regulator.

- The voltage regulator increases charging rate when battery is low or lamps are lit.

- The voltage regulator decreases charging rate when battery charge is up.

#### NOTICE

It is possible to overload the vehicle's charging system by adding too many electrical accessories. If the combined electrical accessories operating at any one time consume more electrical current than the vehicle's charging system can produce, the electrical consumption can discharge the battery and cause damage to the vehicle's electrical system. (00211d)

#### NOTE

- This unit requires no interval attention. If any electrical system trouble is experienced that might be traceable to the alternator or voltage regulator, the motorcycle should be taken to a Harley-Davidson dealer who has the necessary electrical testing equipment to give the required attention.
- For model specific information regarding the voltage regulator, refer to the appropriate Service Manual or see a Harley-Davidson dealer.

## BATTERY: GENERAL

### Type

Your motorcycle uses a permanently sealed, maintenance-free, lead/calcium and sulfuric acid battery. All

batteries are shipped precharged and ready to be put into service. Do not attempt to open the battery for any reason.

Table 25. Antidotes for Battery Acid

CONTACT	TREATMENT
External	Flush with water.
Internal	Drink large quantities of milk or water, followed by milk of magnesia, vegetable oil or beaten eggs. Get immediate medical attention.
Eyes	Flush with water. Get immediate medical attention.

#### ⚠ WARNING

Batteries contain sulfuric acid, which could cause severe burns to eyes and skin. Wear a protective face shield, rubberized gloves and protective clothing when working with batteries. **KEEP BATTERIES AWAY FROM CHILDREN.** (00063a)

#### ⚠ WARNING

Explosive hydrogen gas, which escapes during charging, could cause death or serious injury. Charge battery in a well-ventilated area. Keep open flames, electrical sparks and smoking materials away from battery at all times. **KEEP BATTERIES AWAY FROM CHILDREN.** (00065a)


**⚠ WARNING**

Batteries, battery posts, terminals and related accessories contain lead and lead compounds, and other chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm. Wash hands after handling. (00019e)

**⚠ WARNING**

Never remove warning label from battery. Failure to read and understand all precautions contained in warning, could result in death or serious injury. (00064b)

om00034



**Figure 49. Battery Warning Label Location**



1



2



3



4



5



6

**NON-SPILLABLE**

This is a ready filled,  
activated SEALED BATTERY.  
NEVER remove strip.

Refer to owner's manual  
or instruction sheet for  
charging procedure.

**! DANGER/POISON**

3-4580

**SHIELD EYES.**

**EXPLOSIVE GASES CAN CAUSE BLINDNESS OR INJURY.**



**NO**  
• SPARKS  
• FLAMES  
• SMOKING



**SULFURIC ACID CAN CAUSE BLINDNESS OR SEVERE BURNS.**

**FLUSH EYES IMMEDIATELY WITH WATER.****GET MEDICAL HELP FAST.****KEEP OUT OF REACH OF CHILDREN. DO NOT OPEN BATTERY.**

1. Contents are corrosive
2. Wear safety glasses
3. Contents are explosive

4. Keep flames away
5. Read instructions
6. Keep away from children

Figure 50. Battery Warning Label



## Voltmeter Test

Refer to Table 26. The voltmeter test provides a general indicator of battery condition. Check the voltage of the battery to verify that it is in a 100 percent fully charged condition. If the open circuit (disconnected) voltage reading is below 12.6V, charge the battery and then re-check the voltage after the battery has set for one to two hours.

**Table 26. Voltmeter Test**

READING IN VOLTS	PERCENT OF CHARGE
12.7	100
12.6	75
12.3	50
12.0	25
11.8	0

## Cleaning and Inspection

Battery top must be clean and dry. Dirt and electrolyte on top of the battery can cause battery to self-discharge.

1. Clean battery top.
2. Clean cable connectors and battery terminals using a wire brush or fine grit sandpaper to remove any oxidation.
3. Inspect and clean the battery screws, clamps and cables. Check for breakage, loose connections and corrosion.

4. Check the battery posts for melting or damage caused by overtightening.
5. Inspect the battery for discoloration, a raised top or a warped or distorted case. This might indicate that the battery has been frozen, overheated or overcharged.
6. Inspect the battery case for cracks or leaks.

## Charging

Never charge a battery without first reviewing the instructions for the charger being used. In addition to the manufacturer's instructions, follow these general safety precautions.

Charge the battery if any of the following conditions exist:

- Vehicle lamps appear dim.
- Electric starter sounds weak.
- Battery has not been used for an extended period of time.

### **⚠ WARNING**

**Explosive hydrogen gas, which escapes during charging, could cause death or serious injury. Charge battery in a well-ventilated area. Keep open flames, electrical sparks and smoking materials away from battery at all times. KEEP BATTERIES AWAY FROM CHILDREN. (00065a)**

### **⚠ WARNING**

**Batteries contain sulfuric acid, which could cause severe burns to eyes and skin. Wear a protective face shield, rubberized gloves and protective clothing when working with batteries. KEEP BATTERIES AWAY FROM CHILDREN. (00063a)**

1. Perform a voltmeter test to determine the state of charge. If battery needs to be charged, proceed to the next step.

### **NOTICE**

**Remove battery from motorcycle before charging. Electrolyte leakage will damage motorcycle parts. (00213a)**

2. Remove the battery from the motorcycle. See MAINTENANCE AND LUBRICATION > BATTERY: VRSCR MODEL ONLY (Page 122) for VRSCR models or see MAINTENANCE AND LUBRICATION > BATTERY: ALL VRSC MODELS EXCEPT VRSCR (Page 116) for all other VRSC models.
3. Place the battery on a level surface.

### **NOTE**

- The figures listed in the Amp-hour table assume that the battery is charging at room temperature. If warmer than room temperature, use a slightly shorter charging time. If colder, use a slightly longer charging time.
- The use of constant current chargers to charge sealed maintenance free batteries is not recommended. Any overcharge will cause dry-out and premature battery failure. If a constant current charger is the only type available, do not exceed the charge times listed in Table 28 (VRSCR models) or in Table 27 (all other VRSC models). Do not continue charging the battery if it gets hot. When charging, never exceed 15 volts.

### **⚠ WARNING**

**Unplug or turn OFF battery charger before connecting charger cables to battery. Connecting cables with charger ON can cause a spark and battery explosion, which could result in death or serious injury. (00066a)**

### **⚠ WARNING**

**Connect positive (+) battery cable first. If positive (+) cable should contact ground with negative (-) cable connected, the resulting sparks can cause a battery explosion, which could result in death or serious injury. (00068a)**

**⚠ WARNING**

**Disconnect negative (-) battery cable first. If positive (+) cable should contact ground with negative (-) cable connected, the resulting sparks can cause a battery explosion, which could result in death or serious injury. (00049a)**

**NOTICE**

**Do not reverse the charger connections described in the following steps or the charging system of the motorcycle could be damaged. (00214a)**

4. Connect the red battery charger lead to positive (+) terminal of the battery.
5. Connect the black battery charger lead to negative (-) terminal of the battery.

**NOTE**

*If the battery is still in the vehicle, connect the negative lead to the chassis ground. Make sure that the ignition and all electrical accessories are turned off.*

6. Step away from the battery and turn on the charger.

**⚠ WARNING**

**Unplug or turn OFF battery charger before disconnecting charger cables from battery. Disconnecting clamps with charger ON can cause a spark and battery explosion, which could result in death or serious injury. (00067a)**

7. After the battery is fully charged, turn OFF the charger and disconnect the black battery charger lead to the negative (-) terminal of the battery.
8. Disconnect the red battery charger lead to the positive (+) terminal of the battery.
9. Mark the charging date on the battery.

**Table 27. 19 Amp Hour Battery Charging Rates/Times (All VRSC Models Except VRSCR)**

READING (VOLTS)	PERCENT OF CHARGE	3 AMP CHARGER	6 AMP CHARGER	10 AMP CHARGER	20 AMP CHARGER
12.7	100	N/A	N/A	N/A	N/A
12.6	75	1 hour 50 minutes	55 minutes	30 minutes	15 minutes
12.3	50	3 hours 40 minutes	1 hour 50 minutes	1 hour 5 minutes	30 minutes
12.0	25	5 hours 15 minutes	2 hours 40 minutes	1 hours 35 minutes	45 minutes
11.8	0	7 hours	3 hours 30 minutes	2 hours 5 minutes	1 hour 5 minutes

**Table 28. 12 Amp-Hour Battery Charging Rates and Times (VRSCR Model Only)**

READING (VOLTS)	PERCENT CHARGE	3 AMP CHARGER	6 AMP CHARGER	10 AMP CHARGER	20 AMP CHARGER
12.7	100	N/A	N/A	N/A	N/A
12.6	75	1 hour 10 minutes	34 minutes	20 minutes	10 minutes
12.3	50	2 hours 20 minutes	70 minutes	40 minutes	20 minutes
12.0	25	3 hours 20 minutes	1 hour 40 minutes	1 hour	30 minutes
11.8	0	4 hours 30 minutes	2 hours 14 minutes	1 hour 20 minutes	40 minutes

## Storage

### NOTICE

Turn engine over a few times to be sure there is no oil in the crankcase and that all oil has been pumped back into the oil tank. Stop engine and re-check oil level. Failure to do so can result in engine damage. (00071a)

### NOTICE


Do not allow battery to completely discharge. The electrolyte in a discharged battery will freeze. The more discharged a battery is, the more easily it can freeze and crack the battery case. (00218a)

If the motorcycle will not be operated for several months, such as during the winter season, remove the battery from the motorcycle and fully charge.

If the motorcycle is to be stored with the battery installed, it will be necessary to connect a battery tender to maintain charge. See an authorized dealer for more information.

Self-discharge is a normal condition and occurs continuously. The rate of self-discharge depends on the ambient temperature and the battery's state of charge.

- Batteries discharge at a faster rate at higher ambient temperatures.
- To reduce the self-discharge rate, store battery in a cool (not freezing), dry place.
- Charge the battery every month if stored at temperatures below 60° F (16° C).
- Charge the battery more frequently if stored in a warm area above 60° F (16° C).



**Figure 51. Effective Rate of Temperature on Battery Self-discharging Rate**

## BATTERY: ALL VRSC MODELS EXCEPT VRSCR

### NOTE

See MAINTENANCE AND LUBRICATION > BATTERY: VRSCR MODEL ONLY (Page 122) for VRSCR model battery procedures.

### Disconnection and Removal

Before you can inspect or disconnect the battery you must read the section containing information about air cleaner removal.


1. Remove the maxi-fuse. See MAINTENANCE AND LUBRICATION > ELECTRICAL PROTECTION: VRSC MODELS (Page 128).
2. Remove the air cleaner. See MAINTENANCE AND LUBRICATION > AIR CLEANER: VRSC MODELS (Page 98).
3. See Figure 52. Compress hose clamp with a needle nose pliers and remove rear breather hose from cam cover.
4. See Figure 53. Slide the o-ring (4) up each velocity stack (1) body to reveal the three retaining fasteners (5). Unscrew the fasteners and lift off the velocity stacks.

5. Carefully lift up the airbox bottom tray. Two breather hoses are attached to the underside of the airbox bottom tray. The front breather hose is a press-fit on a brass tube and will disconnect. The rear breather hose was disconnected in Step 3.


### NOTICE

**Cover the throttle body bores with duct tape to prevent objects from falling down the injector bores. Do NOT use shop cloths or objects that could damage the throttle plates. (00212d)**

6. See Figure 54. Cover injector intakes.




**Figure 52. Removing Rear Breather Hose Clamp (VRSCR Shown)**



1. Velocity stacks
2. Rear breather hose
3. Air-oil separator
4. O-rings
5. Retaining fasteners (6)

**Figure 53. Velocity Stacks**



**Figure 54. Covering Injector Intakes**

**▲ WARNING**

**Disconnect negative (-) battery cable first. If positive (+) cable should contact ground with negative (-) cable connected, the resulting sparks can cause a battery explosion, which could result in death or serious injury. (00049a)**

7. See Figure 55. Remove the battery negative cable from the negative (-) terminal of the battery.

8. Remove the battery positive cable from the positive (+) terminal of the battery.
9. Stretch battery hold down strap and remove from tab to release tension on strap. Battery hold down strap will become free from lower tab and can be completely removed.
10. Firmly pull battery out and slightly upward to remove battery from battery caddy.






Figure 55. Battery: VRSC Models Except VRSCR

## Installation and Connection

1. Connect hold down strap to bottom of battery caddy.

2. See Figure 55. Slide the fully charged battery into battery caddy, terminal side up, negative (-) battery terminal toward the right side of the motorcycle.

### NOTE

*Battery must sit flat on bottom of tray pad. Verify that battery does not sit on front edge of pad.*

*VRSCR battery terminals are reversed from other VRSC model motorcycles. Verify terminal polarity before connecting cables to battery.*

3. See Figure 55. Verify proper routing of throttle cable.
4. Stretch hold down strap over top of battery. Latch hold down strap to tab on top of battery.

### ⚠ WARNING

**Never route throttle cable over the battery. Fire due to short circuit could occur and cause death or serious injury. (00494c)**

### NOTICE

**Connect the cables to the correct battery terminals. Failure to do so could result in damage to the motorcycle electrical system. (00215a)**

**▲ WARNING**

**Connect positive (+) battery cable first. If positive (+) cable should contact ground with negative (-) cable connected, the resulting sparks can cause a battery explosion, which could result in death or serious injury. (00068a)**

**▲ WARNING**

**Do not allow positive (+) battery cable to contact ground with negative (-) cable connected. Resulting sparks can cause a battery explosion, which could result in death or serious injury. (00069a)**

**NOTICE**

**Do not over-tighten bolts on battery terminals. Use recommended torque values. Over-tightening battery terminal bolts could result in damage to battery terminals. (00216a)**

5. Insert a battery terminal bolt through the battery positive cable (+) (red), into the threaded hole of the battery positive (+) terminal.
6. Tighten the bolt to 6–10 N·m (53–89 in-lbs).

7. Insert the other battery terminal bolt through the battery negative cable (black), into the threaded hole of the battery negative (-) terminal.
8. Tighten the bolt to 6–10 N·m (53–89 in-lbs).

**NOTICE**

**Keep battery clean and lightly coat terminals with petroleum jelly to prevent corrosion. Failure to do so could result in damage to battery terminals. (00217a)**

9. Apply a light coat of petroleum jelly or corrosion retardant material to both battery terminals.
10. Remove the covering from the injector intakes.
11. See Figure 56. Inspect the gasket on the bottom of the airbox tray. The gasket is located by the three alignment pins on the mating surface.

**NOTE**

*Replace the gasket if it is torn or damaged in any way.*


12. Place the airbox tray over the injectors. Make sure the taller slanted lip of the tray faces the front of the motorcycle. Slide the rectangular hole in the tray down over the threaded mounting stud.
13. See Figure 52. Attach the rear breather hose to the fitting on the cam cover. Retain hose with the spring clamp.
14. Align the front breather hose on the airbox tray with the brass tube and press the airbox tray down firmly. Make sure the tray sits flush on top of the injectors.

#### NOTE

*In the next step, you will install the velocity stacks. Each velocity stack has an index mark. Align the index mark on the velocity stack with the corresponding index mark on the airbox tray.*

15. See Figure 57. Align the index marks and install the velocity stacks, the longest stack toward the front of the motorcycle. Start all fasteners by hand first, making sure none are cross-threaded. Tighten the three fasteners on each velocity stack to 6 N·m (53 in-lbs).
16. Slide the o-ring down each velocity stack until it contacts the three fasteners. Slide the breather hose onto the rear breather hose fitting.

17. Reinstall the air filter element, air cleaner cap, wing nut and airbox cover. Lower the seat down.
18. Install the maxi-fuse. See MAINTENANCE AND LUBRICATION > ELECTRICAL PROTECTION: VRSC MODELS (Page 128).



**Figure 56. Air Cleaner Gasket and Alignment Pins**




Figure 57. Velocity Stack and Airbox Tray Index Marks

## BATTERY: VRSCR MODEL ONLY

### Disconnection and Removal

Before you can inspect or disconnect the battery you must read the section containing information about air cleaner removal.

1. Remove the air cleaner. See MAINTENANCE AND LUBRICATION > AIR CLEANER: VRSC MODELS (Page 98).
2. See Figure 52. Compress hose clamp with a needle nose pliers and remove rear breather hose from cam cover.
3. See Figure 53. Slide the o-ring (4) up each velocity stack (1) body to reveal the three retaining fasteners (5). Unscrew the fasteners and lift off the velocity stacks.

### NOTICE

**Cover the throttle body bores with duct tape to prevent objects from falling down the injector bores. Do NOT use shop cloths or objects that could damage the throttle plates. (00212d)**

4. Carefully lift up the airbox bottom tray. Two breather hoses are attached to the underside of the airbox bottom tray. The front breather hose is a press-fit on a brass tube and will disconnect. The rear breather hose was disconnected in Step 2.

**⚠ WARNING**


**Disconnect negative (-) battery cable first. If positive (+) cable should contact ground with negative (-) cable connected, the resulting sparks can cause a battery explosion, which could result in death or serious injury. (00049a)**

5. See Figure 58. Remove the battery negative cable from the negative (-) terminal of the battery.
6. Remove the battery positive cable from the positive (+) terminal of the battery.


**NOTE**

*Do not remove battery hold-down strap clip from battery tray.*

7. See Figure 59. Stretch rubber hold-down strap over the airbox cover grommet bracket and remove battery.



**Figure 58. Battery (12 amp-hour): VRSCR Model**



**Figure 59. Hold-down Strap Over Grommet Bracket:  
VRSCR Model**

### **Installation and Connection: VRSCR Model Only**

1. See Figure 59. Slide the fully charged battery under hold-down strap, terminal side up, negative (-) battery terminal toward the left side of the motorcycle.

2. Remove hold-down strap from grommet bracket.

#### **⚠ WARNING**

**Never route throttle cable over the battery. Fire due to short circuit could occur and cause death or serious injury. (00494c)**

#### **NOTICE**

**Connect the cables to the correct battery terminals. Failure to do so could result in damage to the motorcycle electrical system. (00215a)**

#### **⚠ WARNING**

**Connect positive (+) battery cable first. If positive (+) cable should contact ground with negative (-) cable connected, the resulting sparks can cause a battery explosion, which could result in death or serious injury. (00068a)**

#### **⚠ WARNING**

**Do not allow positive (+) battery cable to contact ground with negative (-) cable connected. Resulting sparks can cause a battery explosion, which could result in death or serious injury. (00069a)**

### NOTICE

**Do not over-tighten bolts on battery terminals. Use recommended torque values. Over-tightening battery terminal bolts could result in damage to battery terminals. (00216a)**

3. Insert a battery terminal bolt through the battery positive cable (+) (red), into the threaded hole of the battery positive (+) terminal.
4. Tighten the bolt to 6–10 N·m (53–89 **in-lbs**).
5. Insert the other battery terminal bolt through the battery negative cable (black), into the threaded hole of the battery negative (-) terminal.
6. Tighten the bolt to 6–10 N·m (53–89 **in-lbs**).

### NOTICE

**Keep battery clean and lightly coat terminals with petroleum jelly to prevent corrosion. Failure to do so could result in damage to battery terminals. (00217a)**

7. Apply a light coat of petroleum jelly or corrosion retardant material to both battery terminals.

8. Remove the duct tape from the injector intakes.
9. See Figure 56. Inspect the gasket on the bottom of the airbox tray. The gasket is located by the three alignment pins on the mating surface.

### NOTE

*Replace the gasket if it is torn or damaged in any way.*

10. Place the airbox tray over the injectors. Make sure the taller slanted lip of the tray faces the front of the motorcycle. Slide the rectangular hole in the tray down over the threaded mounting stud.
11. See Figure 52. Attach the rear breather hose to the fitting on the cam cover. Retain hose with the spring clamp.
12. Align the front breather hose on the airbox tray with the brass tube and press the airbox tray down firmly. Make sure the tray sits flush on top of the injectors.

### NOTE

*In the next step, you will install the velocity stacks. Each velocity stack has an index mark. Align the index mark on the velocity stack with the corresponding index mark on the airbox tray.*

13. See Figure 57. Align the index marks and install the velocity stacks, the longest stack toward the front of the motorcycle. Start all fasteners by hand first, making sure none are cross-threaded. Tighten the three fasteners on each velocity stack to 6 N·m (53 in-lbs).
14. Slide the o-ring down each velocity stack until it contacts the three fasteners. Slide the breather hose onto the rear breather hose fitting.
15. Reinstall the air filter element, air cleaner cap, wing nut and airbox cover.
16. Lower the seat back down.

## JUMP STARTING

Harley-Davidson does not recommend jump-starting a motorcycle. However, there may be circumstances when it is necessary to do so. Therefore, we suggest jump-starting be performed as follows:

### ⚠ WARNING

**Be sure jumper cables touch only appropriate battery terminals or ground. Allowing jumper cables to touch each other can result in sparks and a battery explosion, which could result in death or serious injury. (00072a)**

### ⚠ WARNING

**Explosive hydrogen gas, which escapes during charging, could cause death or serious injury. Charge battery in a well-ventilated area. Keep open flames, electrical sparks and smoking materials away from battery at all times. KEEP BATTERIES AWAY FROM CHILDREN. (00065a)**

### NOTICE

**Be sure both vehicles have the same battery voltage when jump starting. Connecting vehicles with different system voltages can result in vehicle damage. (00220c)**

### NOTE

*This procedure presumes the BOOSTER battery is in another vehicle.*

1. Turn off all unnecessary lamps and accessories.

## Positive Cable

1. See Figure 60. Connect one end of a jumper cable to the DISCHARGED battery positive (+) terminal (1).
2. Connect the other end of the same cable to the BOOSTER battery positive (+) terminal (2).



## Negative Cable

### ⚠ WARNING


**Do not connect negative (-) cable to or near the discharged battery negative (-) terminal. Doing so could cause a spark and explosion, which could result in death or serious injury. (00073a)**

1. Connect one end of a jumper cable to the BOOSTER battery negative (-) terminal (3).

### NOTICE

**Do not connect the negative (-) cable to painted or chrome parts. Doing so could result in discoloration at the attachment point. (00221a)**

2. Connect other end of the same cable (4) to a safe ground, (away from the DISCHARGED battery).
3. Start motorcycle.
4. Disconnect cables in reverse order of steps 2, 3, 4, 5. That is: steps 5, 4, 3, 2.



**Figure 60. Jump Start Cable Connections**


## ELECTRICAL PROTECTION: VRSC MODELS

For electrical problems, it is best to see a Harley-Davidson dealer who has the necessary parts and equipment to perform electrical services.

### Accessing Fuse Blocks and Relays: All VRSC Models Except VRSCR

VRSC models (except VRSCR) have a front fuse block and rear fuse block.

1. Make sure the ignition is turned OFF.
2. See Figure 61 and Figure 63. To access front fuse block, remove the fastener from the front right side cover and carefully lift the side cover off the mounting tabs. The front fuse block is mounted on the top right side of the battery box.
3. See Figure 62 and Figure 64. To access rear fuse block, open the seat. The rear fuse block is located on frame crossmember behind fuel filler cap.




**Figure 61. Front Fuse Block and Maxi-Fuse: VRSC Models Except VRSCR**



**Figure 62. Rear Fuse Block Location: VRSC Models Except VRSCR**

om00933




1. Spare (15 amp.)
2. Start relay
3. Battery (15 amp.)
4. Ignition (15 amp.)
5. Fan relay

**Figure 63. Front Fuse Block: All VRSC Models Except VRSCR**

AUTHORIZED  
SERVICE

om00934




1. Spare (15 amp.)
2. Security (15 amp.)
3. Accessory (15 amp.)
4. P&A Ignition (2 amp. max)
5. Lights (15 amp.)
6. ECM power (15 amp.)
7. Fuel pump
8. System relay

**Figure 64. Rear Fuse Block: All VRSC Models Except VRSCR**

### **Accessing Fuse Block and Relays: VRSCR Model Only**


1. Make sure the ignition is turned OFF.
2. Open the seat.
3. Remove the airbox cover by turning the bailhead fastener 1/4 turn counterclockwise. Pull the airbox cover away from the front locating holes in the frame.
4. See Figure 66. Gently lift up each fuse block cover release tab and slide each fuse block assembly out of the fuse block cover.
5. See Figure 65. Each fuse block assembly contains both fuses and relays.



1. Start relay
2. Accessories (15 amp.)
3. Security (15 amp.)
4. Lamps (15 amp.)
5. Spare (15 amp.)
6. Spare (15 amp.)

7. Fuel pump (15 amp.)
8. System relay
9. Fan relay
10. Ignition (15 amp.)
11. ECM power (15 amp.)
12. Battery (15 amp.)

**Figure 65. Fuses and Relays: VRSCR Models Only**



**Figure 66. Fuse Block Assembly: VRSCR Models Only**

## **Fuse Replacement: All VRSC Models Except VRSCR**

Fuses do not reset. A blown fuse must be replaced.

1. For rear fuse block, slide the fuse block off the mount.
2. Remove the suspect fuse and inspect the element.

### **NOTICE**

**Be sure both vehicles have the same battery voltage when jump starting. Connecting vehicles with different system voltages can result in vehicle damage. (00220c)**

3. Replace the fuse if the element is burned or broken.

### **NOTE**

*Use only automotive type ATO fuses as replacements.*

4. For rear fuse block, slide the fuse block onto the mount. Close the seat.
5. For front fuse block, replace side cover on the mounting tabs. Line up the hole on the cover with the threaded hole in the frame tab and install the fastener. Tighten the fastener to 11–17 N·m (97.2–150 in-lbs).

## **Fuse Replacement: VRSCR Model Only**

Fuses do not reset. A blown fuse must be replaced.

1. Remove the suspect fuse and inspect the element.

### NOTICE

**Be sure both vehicles have the same battery voltage when jump starting. Connecting vehicles with different system voltages can result in vehicle damage. (00220c)**

2. Replace the fuse if the element is burned or broken.

### NOTE

*Use only automotive type ATO fuses as replacements.*

3. Slide each fuse block assembly back into the fuse block cover. Push the fuse block assembly into the cover until the cover release tab snaps into place.
4. Replace the airbox cover. Turn the bailhead fastener 1/4 turn clockwise to secure the cover.

### ⚠ WARNING

**Never route throttle cable over the battery. Fire due to short circuit could occur and cause death or serious injury. Throttle cables must be routed alongside battery, between hold down strap and coolant overflow bottle. (00224a)**

5. Close seat.

## Replacing The Maxi-Fuse: All VRSC Models

All VRSC models have a main fuse to protect the motorcycle wiring. This 40-amp maxi-fuse provides main battery power to the motorcycle. It is located in a rubber-coated fuse holder behind the motorcycle's right side cover.

1. See Figure 67. Remove the fastener, carefully lift the side cover off the mounting tabs and set it aside.
2. Grasp the fuse holder in one hand, the plastic body of the maxi-fuse in the other, and pull the maxi-fuse straight out of the fuse holder.
3. Insert the prongs of the **new** maxi-fuse in the fuse holder slots. Push the maxi-fuse firmly down into the fuse holder.
4. Replace the side cover on the mounting tabs, line up the hole in the cover with the threaded hole in the frame tab, and install the fastener. Tighten the fastener to 11–17 N·m (97.2–150 in-lbs).



Figure 67. Inserting Maxi-Fuse (Typical)

## SEAT: VRSC MODELS

### Opening

Seat is hinged on the left side. Grasp lower edge of right side and lift.

#### NOTE

See Figure 68. The lanyard will hold the seat in position on the motorcycle frame.

### Closing

Rotate seat down to close seat.

#### NOTE

Refer to the VRSC Service Manual for information pertaining to seat installation and removal.



Figure 68. Seat Lanyard: VRSC Models



## MOTORCYCLE STORAGE: VRSC MODELS

### Placing Motorcycle in Storage

#### NOTICE

**Proper storage is important for the trouble-free operation of your motorcycle. See your Owner's Manual for storage recommendations or see a Harley-Davidson dealer. Improper storage procedures can lead to equipment damage. (00046a)**

If the motorcycle will not be operated for several months, such as during the winter season, there are several tasks which should be performed. These steps will protect parts against corrosion, preserve the battery and prevent the build-up of gum and varnish in the fuel system.

#### ⚠ WARNING

**Do not store motorcycle with gasoline in tank within the home or garage where open flames, pilot lights, sparks or electric motors are present. Gasoline is extremely flammable and highly explosive, which could result in death or serious injury. (00003a)**

#### NOTE

*Make a list of everything you do and fasten it to a handgrip. When you take the motorcycle out of storage, this list will be*

*your reference/checklist to get your motorcycle in operating condition.*

1. Fill fuel tank and add a gasoline stabilizer. Use one of the commercially available gasoline stabilizers and follow the manufacturer's instructions.
2. Warm motorcycle to operating temperature. Change oil and turn engine over to circulate the new oil.
3. Adjust the belt.
4. Check tire inflation. Adjust to proper inflation pressure.
5. Prepare battery for winter storage. See MAINTENANCE AND LUBRICATION > BATTERY: GENERAL (Page 108).

#### ⚠ WARNING

**Explosive hydrogen gas, which escapes during charging, could cause death or serious injury. Charge battery in a well-ventilated area. Keep open flames, electrical sparks and smoking materials away from battery at all times. KEEP BATTERIES AWAY FROM CHILDREN. (00065a)**

6. If the motorcycle is to be stored with security system armed, it will be necessary to connect a Battery Tender to maintain battery charge. If security system will not be armed and a Battery Tender is not available, remove the Maxi-fuse.

#### NOTICE

**Use only Genuine Harley-Davidson Extended Life Antifreeze and Coolant. Use of other coolants/mixtures may lead to motorcycle damage. (00179c)**

7. Check and fill the cooling system.
8. To protect the vehicle's body panels, engine, chassis and wheels from corrosion, follow the cosmetic care procedures described in the Accessory Maintenance section of this owner's manual prior to storage.
9. If motorcycle is to be covered, use a material such as light canvas that will breathe. Plastic materials that do not breathe promote the formation of condensation.

## Removing Motorcycle From Storage

### ⚠ WARNING

**The clutch failing to disengage can cause loss of control, which could result in death or serious injury. Prior to starting after extended periods of storage, place transmission in gear and push vehicle back and forth several times to assure proper clutch disengagement. (00075a)**

1. See MAINTENANCE AND LUBRICATION > BATTERY: GENERAL (Page 108) for proper battery care. Charge and install the battery.
2. Remove and inspect the spark plugs. Replace if necessary.
3. Clean the air cleaner element.
4. Start the engine and run until it reaches normal operating temperature. Turn off engine.
5. Check the oil.
6. Check the clutch fluid level.

7. Check controls to be sure they are operating properly. Operate the front and rear brakes, throttle, clutch and shifter.
8. Check steering for smoothness by turning the handlebars through the full operating range.

#### **⚠ WARNING**


**Coolant mixture contains toxic chemicals, which may be fatal if swallowed. If swallowed, do not induce vomiting; call a physician immediately. Use in a well ventilated area. Irritation to skin or eyes can occur from vapors or direct contact. In case of skin or eye contact, flush thoroughly with water and go to hospital, if necessary. Dispose of used coolant according to federal, state and local regulations. (00092a)**

9. Check the radiator connections and coolant level.

#### **⚠ WARNING**

**Be sure tires are properly inflated, balanced, undamaged, and have adequate tread. Inspect your tires regularly and see a Harley-Davidson dealer for replacements. Riding with excessively worn, unbalanced, improperly inflated, overloaded or damaged tires can lead to tire failure and adversely affect stability and handling, which could result in death or serious injury. (00014b)**

10. Check tire pressure. Incorrect pressure will result in poor riding characteristics and can affect handling and stability.
11. Check all electrical equipment and switches including the stop lamp, turn signals and horn for proper operation.
12. Check for any fuel, oil, coolant or brake fluid leaks.



## NOTES

---



## GENERAL MAINTENANCE

Maintain chrome and aluminum regularly to check that they retain their original shine and luster. Take care to keep your new Harley-Davidson motorcycle cleaned and waxed as often as possible to inhibit rust and corrosion.

## BLACK DENIM FINISH

### General

If your vehicle has flat (or matte) black finish please read below.

- The Black Denim finish has qualities which differ from high gloss finishes on all other Harley-Davidson motorcycles. Like denim fabric, Black Denim paint will burnish or mar with age and use, thus adding character and personality to the finish of the motorcycle.
- If scratched, the color coat of paint does nick/scuff and these marks can not be rubbed out.
- If polished, the finish will become less matte and more glossy over time.

## How to Clean

1. For heavier deposits:
  - a. Use grease cutting dishwashing detergent and a clean H-D wash-mitt. (Dilute the detergent per the instruction provided by its manufacturer.)
  - b. Rinse thoroughly with clean water.
2. For light deposits, use glass cleaner (ammonia base) and H-D Soft Cloth. This helps remove finger prints and light soil.
3. For final detailing use H-D Gloss with H-D Soft Cloth.

## CLEANING YOUR V-ROD

### NOTICE

**Improper cleaning, or the use of non-recommended care products, or lack of proper maintenance of your VRSC will void your cosmetic warranty coverage. (00226b)**

### ⚠ WARNING

**Observe warnings on labels of cleaning compounds. Failure to follow warnings could result in death or serious injury. (00076a)**

To aid you in keeping your motorcycle clean, see a Harley-Davidson dealer for cleaning and polishing products.

As a general guideline, it is recommended that you use the following products for the purposes listed in Table 29.

**Table 29. Recommended Cleaning Care Products**

PRODUCT	PART NUMBER	FRAME	BODY PANELS	WHEELS	DENIM FINISH
H-D Sunwash	94659-98	Yes	Yes	Yes	No
H-D Bug Remover	94657-98	Yes	Yes	Yes	No
Harley-Gloss	94627-98	Yes	Yes	Yes	Yes
Harley Spray Cleaner and Polish	99817-99	Yes	Yes	Yes	No
Wheel and Tire Cleaner	94658-98	No	No	Yes	No
S100 Total Cycle Cleaner (complete rinse required)	99760-85T	Yes	Yes	Yes	No
Grease cutting dishwasher detergent. Dilute per manufacturer's instructions.	N/A	No	No	No	Yes
Ammonia base glass cleaner	N/A	No	No	No	Yes

1. Use HARLEY SUN WASH (94659-98) first, for general cleaning and washing of all surface finishes. Sunwash has a formulated sheeting action that prevents hard water spots and rinses clean even on hot days in the sun.

**NOTICE**

**Using a pressure washer to clean radiators or oil coolers can damage cooling fins and reduce airflow. Reduced airflow can lead to overheating, resulting in motorcycle damage. (00056c)**

**NOTICE**

**Do not use a pressure washer to clean motorcycle. Using a pressure washer can result in equipment damage. (00489c)**

2. Next, use HARLEY BUG REMOVER (94657-98) to remove bugs from all surface finishes. Bug Remover will not damage metal, plastic or painted surfaces.

3. Finally, use HARLEY GLOSS (94627-98) as an all-purpose surface protectant that provides UV protection and a gloss finish. Harley Gloss contains no waxes, silicones, oils or hydrocarbon solvents.
4. Use HARLEY SPRAY CLEANER AND POLISH (99817-99) for quick touch-ups. It's an all-purpose aerosol cleaner and quick detailer, great for all metal surfaces. This product also reduces static attraction to dust.
5. Use HARLEY WHEEL AND TIRE CLEANER (94658-98) to clean and degrease wheels and tires. Do not use on frame or anodized parts.

#### NOTICE

We recommend use of the products listed above. If you wish to use non-recommended cleaning products, test them only in an inconspicuous area on the vehicle's surface first. Do NOT use abrasive or etching cleaners on anodized surfaces! Doing so can result in damage to the surface. (00227b)

#### NOTICE

Use ONLY Harley Spray Cleaner and Polish, or Harley Gloss on painted surfaces. Use of other cleaners or polishes can damage painted surfaces. (00228a)

#### NOTE

See a Harley-Davidson dealer for repair, restoration, or customization of anodized or painted surfaces.

#### ⚠ WARNING

**Observe warnings on labels of cleaning compounds. Failure to follow warnings could result in death or serious injury. (00076a)**

#### ⚠ CAUTION

**Cooling fans operate automatically, even when the ignition switch is off. Keep hands away from fan blades. Contact with a rotating fan blade can result in minor or moderate injury. (00093a)**

#### NOTICE

Clean the inlet surface of the radiator regularly. Leaves and other debris can collect on the radiator surface and degrade radiator performance which could lead to overheating and motorcycle damage. (00197d)

## LEATHER CARE

#### NOTE

Many Harley-Davidson accessories and seats are either made of leather or have leather inserts. Natural materials age differently and require different care than man-made materials.

*Seat covers and panels made of leather will gain "character", such as wrinkles, with age. Leather is porous and organic and each leather product will settle into its own distinct form with use. Your leather product will mature into its own custom shape and style from the sun, rain and the miles. This maturing is natural and will enhance the custom quality of your Harley-Davidson motorcycle.*

Leather must be periodically cleaned and treated to maintain its appearance and extend its life. Clean and treat leather once a season or more frequently under adverse conditions.

#### NOTICE

**Do not use bleach or detergents containing bleach on saddlebags, seats, tank panels or painted surfaces. Doing so can result in equipment damage. (00229a)**

- Do not use ordinary soap to clean leather or fur. It could dry or remove the oils from the leather.
  - Use **ONLY** a good quality saddle soap to clean leather. Be sure you rinse saddle soap off thoroughly before treating leather.
  - Never try to dry leather quickly, using artificial means. Always let leather dry naturally, at room temperature.
1. Vacuum or blow dust off.

2. Thoroughly clean leather with a good quality saddle soap, following manufacturer's directions. Rinse thoroughly with clean sponge or cloth and water. Allow leather to dry.
3. Once leather is dry, treat with a good quality leather treatment, such as LEATHERCARE (Part No. 98261-91).
4. Always allow leather to dry completely before using.

## WHEEL CARE: VRSC MODELS

### ⚠ WARNING

**Be careful not to get the brakes wet when washing vehicle. Wet brake pads and/or discs can adversely affect brake performance, which could result in death or serious injury. (00079b)**

The vehicle's wheels are cast aluminum. Damage from harsh chemicals, acid based wheel cleaners, brake dust and lack of maintenance can occur. Regular washing and the use of a corrosion protectant will help to maintain their original appearance. HARLEY WHEEL AND TIRE CLEANER (94658-98) is recommended for cleaning wheels and tires. Then use HARLEY GLOSS (94627-98) to protect the aluminum wheel surfaces.

### NOTE

- *Follow recommended service procedures for your tire if applicable.*



- *It is imperative that the wheels are cared for weekly, according to the instructions above, to guard against pitting and corrosion.*
- *Corrosion of these components is not considered to be a defect in materials or workmanship.*

See a Harley-Davidson dealer for cleaning and polishing products.

## WINDSHIELDS

### NOTICE

**Harley-Davidson windshields are made of Lexan. Lexan is a more durable and distortion-resistant material than other types of motorcycle windshield material, but still requires attention and care to maintain. Failure to maintain Lexan properly can result in damage to the windshield. (00230b)**

### NOTICE

**Use only Harley-Davidson recommended products on Harley-Davidson windshields. Do not use harsh chemicals or rain sheeting products, which can cause windshield surface damage, such as dulling or hazing. (00231c)**

### NOTICE

**Do not use benzine, paint thinner, gasoline or any other type of harsh cleaner on the windshield. Doing so will damage the windshield surface. (00232c)**

### NOTE

- *To remove minor surface scratches use NOVUS<sup>®</sup> No. 2 SCRATCH REMOVER (Part No. 99836-94T).*
- *Covering the windshield with a clean, wet cloth for approximately 15-20 minutes before washing will make dried bug removal easier.*

1. Use mild soap and warm water to wash the windshield.
2. Wipe dry with a soft, clean towel.

### NOTE

*To treat your Lexan windshield with water repellent use WINDSHIELD WATER REPELLENT TREATMENT (Part No. 99841-02).*

## NOTES

---



## TROUBLESHOOTING: GENERAL

### ⚠ WARNING

**The troubleshooting section of the Owner's Manual is a guide to diagnose problems. Read the service manual before performing any work. Improper repair and/or maintenance could result in death or serious injury. (00080a)**

The following checklist of possible operating troubles and their probable causes will be helpful in keeping your motorcycle in good operating condition. More than one of these conditions may be causing trouble and should be carefully checked.

## ENGINE: VRSC MODELS

### **Starter Does Not Operate or Does Not Turn Engine Over**

1. Engine run switch in OFF position.
2. Ignition switch not ON.
3. Discharged battery or loose or corroded connections (solenoid chatters).
4. Clutch lever not squeezed against handlebar or transmission not in neutral.
5. Blown fuse.

### **Engine Turns Over But Does Not Start**

1. Fuel tank empty.
2. Fuel vacuum line disconnected.
3. Fuel valve or filter clogged.
4. Discharged battery or loose or broken battery terminal connections.
5. Fouled spark plugs.
6. Spark plug coil connections loose or in bad condition and shorting.
7. Loose or corroded wire or cable connection(s) at coil or battery.
8. Fuel pump inoperative.
9. Blown fuse.

### **Starts Hard**

1. Spark plugs in bad condition, have improper gap, or are partially fouled.
2. Battery nearly discharged.
3. Loose wire or cable connection(s) at one of the battery terminals or at coil.
4. Engine oil too heavy (winter operation).

5. Fuel tank vent plugged or fuel line closed off, restricting fuel flow.
6. Water or dirt in fuel system.
7. Fuel pump inoperative.

### **Starts But Runs Irregularly or Misses**

1. Spark plugs in bad condition or partially fouled.
2. Spark plug gap too close or too wide.
3. Battery nearly discharged.
4. Damaged wire or loose connection at battery terminals or coils.
5. Intermittent short circuit due to damaged wire insulation.
6. Water or dirt in fuel system, filter or carburetor.
7. Fuel vent system plugged. See dealer.
8. One or more injectors fouled.

### **A Spark Plug Fouls Repeatedly**

1. Incorrect spark plug.

### **Pre-ignition or Detonation (Knocks or Pings)**

1. Incorrect fuel.
2. Incorrect spark plug for the kind of service.

### **Overheats**

1. Insufficient oil supply or oil not circulating.
2. Heavy carbon deposit from lugging engine. See dealer.

### **Excessive Vibration**

1. Rear fork pivot shaft nuts loose. See dealer.
2. Front engine mounting bolts loose. See dealer.
3. Broken frame. See dealer.
4. Belt badly worn.
5. Wheels and/or tires damaged. See dealer.
6. Vehicle not properly aligned. See dealer.

## **COOLING SYSTEM**

### **Overheats**

1. Air flow through the radiator is obstructed.
2. The radiator is internally plugged.
3. Insufficient coolant.
4. Cooling fans not operating.

## **ELECTRICAL SYSTEM**

### **Alternator Does Not Charge**

1. Module not grounded. See dealer.
2. Engine ground wire loose or broken. See dealer.
3. Loose or broken wires in charging circuit. See dealer.

### **Alternator Charge Rate is Below Normal**

1. Weak battery.
2. Excessive use of add-on accessories.
3. Loose or corroded connections.
4. Extensive periods of idling or low speed riding.

## **TRANSMISSION: VRSC MODELS**

### **Transmission Shifts Hard**

1. Bent shifter rod. See dealer.
2. Transmission shifting mechanism needs adjustment. See dealer.

### **Transmission Jumps Out of Gear**

1. Shifter rod improperly adjusted. See dealer.

2. Shifter forks (inside transmission) improperly adjusted. See dealer.
3. Worn shifter dogs in transmission. See dealer.

### **Clutch Slips**

1. Clutch controls improperly adjusted. See dealer.
2. Worn friction discs. See dealer.
3. Insufficient clutch spring tension. See dealer.

### **Clutch Drags or Does Not Release**

1. Clutch controls improperly adjusted. See dealer.
2. Insufficient clutch spring tension. See dealer.
3. Clutch discs warped. See dealer.

### **Clutch Chatters**

1. Friction discs or steel discs worn or warped. See dealer.

## **BRAKES**

### **Brakes Do Not Hold Normally**

1. Master cylinder low on fluid. See dealer.
2. Brake line contains air bubbles. See dealer.
3. Master or wheel cylinder piston worn. See dealer.

- 4. Brake pads contaminated with grease or oil. See dealer.
- 5. Brake pads badly worn. See dealer.
- 6. Brake disc badly worn or warped. See dealer.
- 7. Brake fades because of heat build up. Excessive braking or brake pads dragging. See dealer.
- 8. Brake drags. Insufficient hand lever free play. See dealer.



## WARRANTY AND MAINTENANCE

This Owner's Manual contains your new motorcycle warranty.

It is the owner's responsibility to follow the scheduled mileage intervals as specified; all of the specified maintenance services must be performed to keep your warranty valid.

1. Make an appointment with a Harley-Davidson dealer for inspection and service just before you have ridden 1000 miles (1600 kilometers).
2. Bring this Owner's Manual with you when you visit your dealer to have your motorcycle inspected and serviced.
3. Have the dealer technician sign at the proper mileage interval. The records should be retained by the owner as proof of proper maintenance.
4. Keep receipts covering any parts, service or maintenance performed. These records should be transferred to each subsequent owner.

### ⚠ WARNING

**Harley-Davidson parts and accessories are designed for Harley-Davidson motorcycles. Using non-Harley-Davidson parts or accessories can adversely affect performance, stability or handling, which could result in death or serious injury. (00001b)**

Harley-Davidson dealerships are independently owned and operated and may sell parts and accessories that are not manufactured or approved by Harley-Davidson. Therefore, you should understand that we are not and cannot be responsible for the quality, suitability, or safety of any non-Harley-Davidson part, accessory or design modification, including labor, which may be sold and/or installed by our dealers.

## KEEPING IT ALL HARLEY-DAVIDSON

1. Keep your Harley-Davidson completely Harley-Davidson.
2. Insist that your dealer uses only Genuine replacement parts to keep your Harley-Davidson motorcycle and its warranty intact.

Exact design and stringent testing ensure performance and warranty coverage. Again, insist on Genuine parts for your genuine Harley-Davidson motorcycle.

### NOTE

*Installing off-road or competition parts to enhance performance may void all or part of your new motorcycle warranty. See the Harley-Davidson Limited Warranty in this manual or a Harley-Davidson dealer for details.*

## NOTICE

**It is possible to overload the vehicle's charging system by adding too many electrical accessories. If the combined electrical accessories operating at any one time consume more electrical current than the vehicle's charging system can produce, the electrical consumption can discharge the battery and cause damage to the vehicle's electrical system. (00211d)**

## IMPORTANT MOVING INFORMATION

If you move from your present address, or sell your motorcycle, please fill out and mail the post card at the back of this manual. This is necessary in the event that the Company needs to contact the owner concerning information that could affect the safe operation of this motorcycle.

## WARRANTY/SERVICE INFORMATION

Any authorized Harley-Davidson dealer is responsible for providing the warranty repair work on your motorcycle. If you have any questions regarding warranty obligations contact your selling dealer.

For normal service work or warranty work under the above conditions, you may obtain the name and location of your nearest U.S. Harley-Davidson dealer by calling

1-800-490-9635 (toll free), in any state except Alaska and Hawaii.

### NOTE

*The number shown above is accessible only with a touch-tone phone.*

## OWNER TRANSFER IDENTIFICATION FORM

When purchasing a pre-owned Harley-Davidson or Buell, we encourage you to submit an Owner Transfer Notification Form. It is critical that new owner information is communicated to Harley-Davidson. New owner information is required to be on file with Harley-Davidson to transfer an Extended Service Plan Contract. Harley-Davidson is also required by the National Traffic and Motor Vehicle Safety Act to notify all owners in the event of a recall. The form may be obtained at any Harley-Davidson dealer.

## REQUIRED DOCUMENTATION FOR IMPORTED MOTORCYCLES

If a Harley-Davidson is imported into the United States, additional documentation is required to be eligible for the United States Manufacturer's Limited Warranty. A Harley-Davidson dealer can provide a form explaining the requirements.



## 2007 HARLEY-DAVIDSON MOTORCYCLE LIMITED WARRANTY

### 24 Months/Unlimited Miles

Harley-Davidson warrants for any new 2007 Harley-Davidson motorcycle/sidecar that an authorized Harley-Davidson dealer will repair or replace without charge any parts found under normal use to be defective in factory materials or workmanship. Such repair and replacement will be Harley-Davidson's sole obligation and the customer's sole remedy under this warranty.

THERE IS NO OTHER EXPRESS WARRANTY (OTHER THAN THE SEPARATE EMISSIONS AND NOISE WARRANTIES) ON THE MOTORCYCLE. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE IS LIMITED TO THE DURATION OF THIS WARRANTY.

Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you.

TO THE FULLEST EXTENT ALLOWED BY LAW, HARLEY-DAVIDSON AND ITS DEALERS SHALL NOT BE LIABLE FOR LOSS OF USE, INCONVENIENCE, LOST TIME, COMMERCIAL LOSS OR OTHER INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

The following terms and conditions apply to this warranty:

### Duration

1. The duration of this limited warranty is twenty four months, starting from the earlier of (a) the date of initial retail purchase and delivery from an authorized Harley-Davidson dealer, or (b) the third anniversary of the last day of the model year of the motorcycle/sidecar. Your dealer will submit an electronic Sales and Warranty Registration form to initiate your warranty.
2. Any unexpired portion of this limited warranty will be transferred to subsequent owners, upon the resale of the motorcycle/sidecar during the warranty period.

### Owner's Obligations

To obtain warranty service, return your motorcycle/sidecar at your expense within the warranty period to an authorized dealer. Our dealer should be able to provide warranty service during normal business hours and as soon as possible, depending upon the workload of the dealer's service department and the availability of necessary parts.

Harley-Davidson Motor Company, P.O. Box 653, Milwaukee, Wisconsin 53201, U.S.A.

## Exclusions

This warranty will not apply to any motorcycle/sidecar as follows:

1. Which has not been operated or maintained as specified in the Owner's Manual.
2. Which has been abused, misused, improperly stored, used "off the highway," or used for racing or competition of any kind.
3. Which is not manufactured to comply with the laws of the market in which it is registered.
4. Installing off-road or competition parts to enhance performance may void all or part of your new motorcycle warranty. See a Harley-Davidson dealer for details.

## Other Limitations

This warranty does not cover:

1. Parts and labor for normal maintenance as recommended in the Owner's Manual, or the replacement of parts due to normal wear and tear including such items as the following: tires, lubrication, oil and filter change, fuel system cleaning, battery maintenance, engine tune-up, spark plugs, brake, clutch and chain/belt adjustment (including chain replacement).

2. Cosmetic concerns that arise as a result of owner abuse, lack of proper maintenance or environmental conditions (except concerns that result from defects in material or workmanship, which are covered by this warranty for the duration of the warranty period).
3. Any cosmetic condition existing at the time of retail delivery that has not been documented by the selling dealer prior to retail delivery.
4. Defects or damage to the motorcycle caused by alterations outside of Harley-Davidson factory specifications.

## Important: Read Carefully

1. Our dealers are independently owned and operated and may sell other products. Because of this, HARLEY-DAVIDSON IS NOT RESPONSIBLE FOR THE SAFETY, QUALITY, OR SUITABILITY OF ANY NON-HARLEY-DAVIDSON PART, ACCESSORY OR DESIGN MODIFICATION INCLUDING LABOR WHICH MAY BE SOLD AND/OR INSTALLED BY OUR DEALERS.
2. This warranty is a contract between you and the manufacturer. It is separate and apart from any warranty you may receive or purchase from the dealer. The dealer is not authorized to alter, modify, or in any way change the terms and conditions of this warranty.

3. Any warranty work or parts replacement authorized by the manufacturer will not preclude the manufacturer from later relying on any exclusion where applicable.



## NOTES

---



## REGULAR SERVICE INTERVALS

Regular lubrication and maintenance will help keep your new Harley-Davidson operating at peak performance. Your Harley-Davidson dealer knows best how to service your motorcycle with factory approved methods and equipment assuring you of thorough and competent workmanship.

### NOTE

- Refer to Table 30 for all VRSC models other than VRSCX. Refer to Table 31 for VRSCX models. Regular maintenance interval operations are required to keep your new motorcycle warranty in force. The use of other than Harley-Davidson approved parts and service procedures may void the warranty. Any alterations to the emission system components, such as the exhaust system, may be in violation of Federal and State laws.
- Refer to Table 32 for all VRSC models other than VRSCX. Refer to Table 33 for VRSCX models. When servicing your motorcycle, bring this owner's manual to the dealership and complete information needed in the blank columns listed.

### ⚠ WARNING

Perform the service and maintenance operations as indicated in the regular service interval table. Lack of regular maintenance at the recommended intervals can affect the safe operation of your motorcycle, which could result in death or serious injury. (00010a)

### ⚠ WARNING

If you operate your motorcycle under adverse conditions (severe cold, extreme heat, very dusty environment, very bad roads, through standing water, etc.), you should perform the regular maintenance intervals more frequently to ensure the safe operation of your motorcycle. Failure to maintain your motorcycle could result in death or serious injury. (00094a)

**Table 30. Regular Service Intervals: 2007 VRSC Models Except VRSCX**

ITEM SERVICED	PROCEDURE	1000 MI. 1600 KM	5000 MI. 8000 KM	10,000 MI. 16,000 KM	15,000 MI. 24,000 KM	20,000 MI. 32,000 KM	25,000 MI. 40,000 KM	NOTES
Engine oil and filter	Replace	X	X	X	X	X	X	
Oil lines and brake system	Inspect for leaks	X	X	X	X	X	X	1
Air cleaner	Inspect, service as required	X	X	X	X	X	X	

**Table 30. Regular Service Intervals: 2007 VRSC Models Except VRSCX**

ITEM SERVICED	PROCEDURE	1000 MI. 1600 KM	5000 MI. 8000 KM	10,000 MI. 16,000 KM	15,000 MI. 24,000 KM	20,000 MI. 32,000 KM	25,000 MI. 40,000 KM	NOTES
Tires	Check pressure, inspect tread	X	X	X	X	X	X	
Clutch fluid	Check level and condition	X	X	X	X	X	X	
Rear belt and sprockets	Inspect, adjust belt	X	X	X	X	X	X	1
Throttle, brake and clutch controls	Check, adjust and lubricate	X	X	X	X	X	X	1
Jiffy stand	Inspect and lubricate	X	X	X	X	X	X	1
Brake fluid	Check levels and condition	X	X	X	X	X	X	5
Brake pads and discs	Inspect for wear	X	X	X	X	X	X	
Spark plugs	Inspect		X		X		X	
	Replace			X		X		
Electrical equipment and switches	Check operation	X	X	X	X	X	X	
Front fork oil		Replace every 30,000 miles (48,000 kilometers)						1
Steering head bearings	Adjust	X				X		1, 2
Rear fork bearings		Repack every 30,000 miles (48,000 kilometers)						1
Valve lash		Adjust valve lash every 12,000 miles (19,000 kilometers)						1, 4
Cooling system	Inspect; check clamps for tightness, check coolant freeze point	X		X		X		1
Coolant		Replace every 30,000 miles (48,000 kilometers)						1
Radiator	Clean	X	X	X	X	X	X	
Critical fasteners	Check tightness	X		X		X		1
Battery	Check battery and clean connections							3
Road test	Verify component and system functions	X	X	X	X	X	X	
<b>NOTES:</b>		1. Should be performed by an authorized Harley-Davidson dealer, unless you have the proper tools, service data and are mechanically qualified. 2. Disassemble, lubricate and inspect every 30,000 miles (48,000 kilometers). 3. Perform annually. 4. Could vary with frequency of operation and riding style. 5. Change D.O.T. 4 and flush brake system every two years.						

**Table 31. Regular Service Intervals: 2007 VRSCX Model**

ITEM SERVICED	PROCEDURE	1000 MI. 1600 KM	4000 MI. 6400 KM	8000 MI. 12,800 KM	12,000 MI. 19,300 KM	16,000 MI. 25,700 KM	20,000 MI. 32,100 KM	NOTES
Engine oil and filter	Replace	X	X	X	X	X	X	
Oil lines and brake system	Inspect for leaks	X	X	X	X	X	X	1
Air cleaner	Inspect, service as required	X	X	X	X	X	X	
Tires	Check pressure, inspect tread	X	X	X	X	X	X	
Wheel spokes (if so equipped)	Check tightness	X	X				X	1
Clutch fluid	Check level and condition	X	X	X	X	X	X	
Rear belt and sprockets	Inspect, adjust belt	X	X	X	X	X	X	1
Throttle, brake and clutch controls	Check, adjust and lubricate	X	X	X	X	X	X	1
Jiffy stand	Inspect and lubricate	X	X	X	X	X	X	1
Brake fluid	Check levels and condition	X	X	X	X	X	X	5
Brake pads and discs	Inspect for wear	X	X	X	X	X	X	
Spark plugs	Inspect		X		X		X	
	Replace				X			
Electrical equipment and switches	Check operation	X	X	X	X	X	X	
Front fork oil		Replace every 28,000 miles (45,000 kilometers)						1
Steering head bearings	Adjust	X					X	1, 2
Rear fork bearings		Repack every 28,000 miles (45,000 kilometers)						1
Valve lash	Adjust				X			1, 4
Cooling system	Inspect; check clamps for tightness, check coolant freeze point	X		X		X		1
Coolant		Replace every 28,000 miles (45,000 kilometers)						1
Radiator	Clean	X	X	X	X	X	X	
Critical fasteners	Check tightness	X		X		X		1
Battery	Check battery and clean connections							3

**Table 31. Regular Service Intervals: 2007 VRSCX Model**

ITEM SERVICED	PROCEDURE	1000 MI. 1600 KM	4000 MI. 6400 KM	8000 MI. 12,800 KM	12,000 MI. 19,300 KM	16,000 MI. 25,700 KM	20,000 MI. 32,100 KM	NOTES
Road test	Verify component and system functions	X	X	X	X	X	X	
<b>NOTES:</b>	1. Should be performed by an authorized Harley-Davidson dealer, unless you have the proper tools, service data and are mechanically qualified. 2. Disassemble, lubricate and inspect every 28,000 miles (45,000 kilometers). 3. Perform annually. 4. Could vary with frequency of operation and riding style. 5. Change D.O.T. 4 and flush brake system every two years.							

**Table 32. Owner's Maintenance Records: All VRSC Models Except VRSCX**

SERVICE MILE INTERVAL	DATE	DEALER NUMBER	TECHNICIAN NAME	TECHNICIAN SIGNATURE
1000 MI (1600 KM)				
5000 MI (8000 KM)				
10,000 MI (16,000 KM)				
15,000 MI (24,000 KM)				
20,000 MI (32,000 KM)				
25,000 MI (40,000 KM)				
30,000 MI (48,000 KM)				
35,000 MI (56,000 KM)				
40,000 MI (64,000 KM)				
45,000 MI (72,000 KM)				
50,000 MI (80,000 KM)				



**Table 33. Owner's Maintenance Records: VRSCX Model**

SERVICE MILE INTERVAL	DATE	DEALER NUMBER	TECHNICIAN NAME	TECHNICIAN SIGNATURE
1000 MI (1600 KM)				
4000 MI (6400 KM)				
8000 MI (12,800 KM)				
12,000 MI (19,300 KM)				
16,000 MI (25,700 KM)				
20,000 MI (32,100 KM)				
24,000 MI (38,600 KM)				
28,000 MI (45,000 KM)				
32,000 MI (51,500 KM)				
36,000 MI (57,900 KM)				
40,000 MI (64,300 KM)				

## SERVICE LITERATURE

Refer to Table 34. Visit your Harley-Davidson dealer or go to [www.harley-davidson.com](http://www.harley-davidson.com) to purchase a service or parts

manual for your motorcycle. Factory authorized manuals are the most complete and detailed source of information outside of your Harley-Davidson dealer.

**Table 34. Service Literature: 2007 VRSC Models**

DOCUMENT	LANGUAGE	PART NUMBER
Service Manual	English	99501-07
Electrical Diagnostics Manual	English	99499-07
Service and Electrical Diagnostics Manual	French	99501-07F
Service and Electrical Diagnostics Manual	German	99501-07G
Service and Electrical Diagnostics Manual	Spanish	99501-07S

**Table 34. Service Literature: 2007 VRSC Models**

DOCUMENT	LANGUAGE	PART NUMBER
Service and Electrical Diagnostics Manual	Italian	99501-07I
Parts Catalog	English	99457-07



# Index

## A

Accessories and Cargo Guidelines.....	11
Accessory and Cargo Guidelines.....	11
Address Change.....	150
Air Cleaner.....	98
Alarm.....	58
Alternator/Voltage Regulator.....	107

## B

Battery.....	41,62,108,116,122, 126
Black Denim Finish.....	139
Brake Fluid Level.....	90
Brake Pads.....	90
Brakes.....	41,43,147
Break-in.....	73
Break-in Maintenance.....	73
Break-in Riding Rules.....	66
Bulb Chart.....	19
Bulb Replacement.....	19

## C

Capacities.....	19
Catalytic Converters.....	24
Changing Engine Oil.....	77
Charging the Battery.....	108
Chassis Lubrication.....	86
Check Engine Lamp.....	41
Checking Engine Oil.....	74
Cleaning.....	141,143
Clutch.....	29,87,147
Controls.....	29,43
Coolant.....	19,33,79,146
Coolant Level.....	79
Cooling System.....	146
Customer service.....	2

## D

Dealer Locator.....	150
Dealer Locator Phone Number.....	150

## E

Electrical Protection.....	128
----------------------------	-----

# Index

Electrical System.....	147
Emergency Flashers.....	33
Engine.....	65,69,145
Engine Check Lamp.....	41
Engine Oil.....	19,33,73,74,77, 79
Engine Speed.....	65
Extended Service Plan Contract.....	150

## F

Factory Replacement Parts.....	149
Fob.....	50,61
Four-Way Flashers.....	33
Front Fork Bearings.....	90
Front Fork Oil.....	87
Fuel.....	19,24,25,41,98
Fuel and Oil.....	24
Fuel Filter.....	87
Fuel Injection.....	41
Fuses.....	62
Fuses and Relays.....	62

## G

Gasoline.....	24,25
Gasoline Blends.....	24
GAWR.....	11
GAWR/GVWR.....	11
GVWR.....	11

## H

Hand Controls.....	29
Hazard Warning 4-Way Flasher.....	33,55
Hazard Warning Four-Way Flasher.....	33
Headlamp.....	33,101,104
Horn.....	29

## I

Ignition Key.....	27
Ignition System.....	98
Importing a Motorcycle.....	150
Indicator Lamps.....	33
Instrument Lamps.....	41

# Index

Instruments.....33,37,41

## J

Jiffy Stand.....44

Jump-Starting Battery.....126

## K

Key Fob.....61

## L

Labels.....17

Leather.....141

Leather and Vinyl Care.....141

Leather Care.....141

Light Bulbs.....19

Limited Warranty.....151

Lubrication.....86

Luggage.....11

## M

Maintenance.....73,73,73,74,77,  
79, 86, 87, 87, 90, 90, 95, 98, 107, 108, 149

Manual.....1

Mirror Adjustment.....44

Mirrors.....44

Motorcycle Storage.....135

## O

Octane Rating.....25

Oil.....73

Oil Applications.....87

Oil Level.....74

Operating Maintenance.....73

Operation.....43,69

Owner Transfer Notification Form.....150

## P

Power Disconnect.....62

Pre-Riding Checklist.....66

# Index

<b>R</b>		Starting the Engine.....	68
Rear Drive Belt.....	85	Stopping the Engine.....	69
Rear Fork Pivot Shaft.....	90	Storage.....	135
Rear Shock Absorbers.....	46		
Rules of the Road.....	10	<b>T</b>	
<b>S</b>		Tire Data.....	23
Safe Operating Rules.....	5	Tire Replacement.....	96
Safety.....	11,17,19,73	Tires.....	19,95,96
Safety Definitions.....	1	Transmission.....	147
Seats.....	134	Troubleshooting.....	33,62,145,145,146, 147, 147, 147
Security System.....	33,41,49,50,50, 52, 54, 55, 58, 60, 61, 62, 62	Turn Signal Bulbs (Bullet Style).....	106
Service Intervals.....	155	Turn Signal Switches.....	32
Service Literature.....	159	Turn Signals.....	29,32,33,33
Shifting Gears.....	70	<b>V</b>	
Shock Absorbers.....	98	V.I.N.....	15
Sidestand.....	44	Vehicle Identification Number.....	15
Smart Security System.....	49,50,50,52,54, 55, 58, 59, 60, 60, 61, 62, 62	Voltage Regulator/Alternator.....	107
Spark Plugs.....	97		
Specifications.....	19,25,73		

# Index

---

## W

Warning Lamps.....	41
Warranty.....	149, 150, 151
Warranty Repair Work.....	150
Weight Limits.....	19
Wheels.....	142
Windshield.....	143
Windshield Cleaning.....	143
Winter Lubrication.....	79



## NOTES

---

